



# PYTHON-04

RGBW-48-14/G5 840



<b>LIGHT TYPE</b>	RGBW
<b>CCT</b>	4000K
<b>CCT Shift</b>	3600K
<b>CRI</b>	CRI 80+
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>PHOTOMETRIC</b>	120° beam angle
<b>LUMINOUS FLUX</b>	362 Lm/m (110 Lm/ft)
<b>EFFICACY</b>	25 Lm/W
<b>LIFETIME</b>	L70B50 50.000 h

<b>CONTROL</b>	Dimmable
----------------	----------

<b>VOLTAGE</b>	24 VDC
<b>WATTAGE</b>	14.4 W/m   4.39 W/ft

<b>CUTTING STEP</b>	125 mm (4.92")
<b>MAX RUN</b>	7 m (23')
<b>PACKING</b>	5m or customized length per reel
<b>DIMENSIONS</b>	Width: 20 mm (0.79") Height: 20 mm (0.79")

<b>TEMPERATURE</b>	Tc max <75°C ( 167°F )
<b>OPERATING TEMP.</b>	-25°C...+50°C ( -13°F...122°F )
<b>STORAGE TEMP.</b>	-25°C...+80°C ( -13°F...176°F )



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.