

xLINE IP67 TUNABLE WHITE


xLine A017M IEC PWE EOP / TW56/Nx G4 09W 820/835 L1000
Luminaire segment




COLORS

White housing

PHOTOMETRICS




SEGMENT LAYOUT




Luminaire type segment

CONNECTION TYPE



End exit wire

TECHNICAL DRAWING



26 mm
(1.02 in)

SPECTRUM

Warm LED: CRI 80+ 2000K

Cold LED: CRI 80+ 3500K

3-Step MacAdam

COVER

Opal

LUMINOUS FLUX

Per segment: 248 lm

Light source (per segment): 1232 lm

Per meter/feet: 248 lm/m | 76 lm/ft

EFFICACY

Luminaire: 26 lm/W

Light source: 128 lm/W

LIFETIME

L90B10 60.000h

HOUSING

Aluminum, polyurethane

ELECTRICAL

Segment power: 9.6 W

Power per meter/feet: 9.6 W/m

Voltage: 24 VDC

TEMPERATURE

Tc max <75°C (167°F)

Operating: -25°C...+50°C (-13°F...122°F)

OTHER DETAILS

IP67 protection

Dimmable

Install in well-ventilated areas only

DIMENSIONS

Width: 26 mm (1.02")

Height: 25 mm (0.98")

Length: 1004 mm | 3.3'