





NEMAN RECESSED

Microprism

Product code: NM R LUM MP PW W17 827 0560 D

Article No.: F1RAMDAADXX0560D



MOUNTING	Recessed
TYPE	Individual luminaire
CCT	2700K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
LUMENS LUMINAIRE	1105 Lm
LIGHT SOURCE	1504 Lm
EFFICACY LUMINAIRE	106 Lm/W
LIGHT SOURCE	161 Lm/W
LIFETIME	L90B10 60.000h

CONTROL	DALI
----------------	------

LUMINAIRE POWER	10.4 W
INPUT VOLTAGE	220-240 VAC 50/60 Hz
	Integrated driver

HOUSING	Microprism light surface
HOUSING COLOR	Extruded aluminum, White color
IP CLASS	IP20 ingress protection
OTHER DETAILS	Lead cable 2m (6.5'), transparent

DIMENSIONS	Width: 48 mm / 1.89"
	Height: 41 mm / 1.61"
	Length: 577 mm / 1.9'

MOUNTING HOLE	568 x mm / 1.86' x 1.5"
----------------------	-------------------------



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
 All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.