





NEMAN RECESSED

Microprism

Product code: NM R LUM MP PW W17 827 1120 N

Article No.: F1RAMDAADXX1120N



MOUNTING	Recessed
TYPE	Individual luminaire
CCT	2700K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
LUMENS LUMINAIRE	2209 Lm
LIGHT SOURCE	3008 Lm
EFFICACY LUMINAIRE	106 Lm/W
LIGHT SOURCE	161 Lm/W
LIFETIME	L90B10 60.000h

CONTROL	no dim
----------------	--------

LUMINAIRE POWER	20.8 W
INPUT VOLTAGE	220-240 VAC 50/60 Hz Integrated driver

HOUSING	Microprism light surface
HOUSING COLOR	Extruded aluminum, White color
IP CLASS	IP20 ingress protection
OTHER DETAILS	Lead cable 2m (6.5'), transparent

DIMENSIONS	Width: 48 mm / 1.89" Height: 41 mm / 1.61" Length: 1137 mm / 3.7'
-------------------	---

MOUNTING HOLE	1128 x mm / 3.7' x 1.5"
----------------------	-------------------------



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.