





## VENTA IP67

A130x IP67 OPL PWE L1000 / FL112/Nx 01W 830



<b>LIGHT TYPE</b>	White
<b>CCT</b>	3000K
<b>CRI</b>	CRI 80+
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>PHOTOMETRIC</b>	Opal° Beam angle
<b>LUMINOUS FLUX</b>	165 Lm/m (50 Lm/ft)
<b>EFFICACY</b>	86 Lm/W
<b>LIFETIME</b>	L90B10 60.000 h

<b>CONTROL</b>	Dimmable
----------------	----------

<b>VOLTAGE</b>	24 VDC
<b>WATTAGE</b>	1.92 W/m   0.59 W/ft

<b>CUTTING STEP</b>	62.5 mm (2.46")
<b>MAX RUN</b>	33 m (108')
<b>DIMENSIONS</b>	Width: 30 mm (1.18") Height: 30 mm (1.18")
<b>IP CLASS</b>	IP67

<b>TEMPERATURE</b>	Tc max <75°C ( 167°F )
<b>OPERATING TEMP.</b>	-25°C...+50°C ( -13°F...122°F )
<b>STORAGE TEMP.</b>	-25°C...+80°C ( -13°F...176°F )



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.