



# ULA M IP67 WHITE LIGHT

## Luminaire segment

UlaM.IP67 AULMO IEC AGY EOP / FL56/Nx G4 01W 820 L1000



|                    |                 |
|--------------------|-----------------|
| CCT                | 2000K           |
| CRI                | CRI 80+         |
| COLOR CONSISTENCY  | 3-Step MacAdam  |
| COVER              | Opal            |
| LUMENS LUMINAIRE   | 36 Lm           |
| LIGHT SOURCE       | 123 Lm          |
| EFFICACY LUMINAIRE | 30 Lm/W         |
| LIGHT SOURCE       | 103 Lm/W        |
| LIFETIME           | L90B10 60.000 h |

|         |                        |
|---------|------------------------|
| HOUSING | Aluminum, polyurethane |
|---------|------------------------|

|         |                    |
|---------|--------------------|
| VOLTAGE | 24 VDC             |
| WATTAGE | 1.2 W/m   0.4 W/ft |

|               |                             |
|---------------|-----------------------------|
| MAX RUN       | 40 m (131')                 |
| OTHER DETAILS | IP67 protection<br>Dimmable |

|                 |                                 |
|-----------------|---------------------------------|
| TEMPERATURE     | Tc max <75°C ( 167°F )          |
| OPERATING TEMP. | -25°C...+50°C ( -13°F...122°F ) |

|            |  |
|------------|--|
| DIMENSIONS | Width: 16 mm (0.63")<br>Height: 26 mm (1.02")<br>Length: 1000 mm (3.28") |
|------------|--|



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.