



ULA M IP67 WHITE LIGHT

Luminaire segment

UlaM.IP67 AULMO IEC AGY EOP / FL56/Nx G4 01W 827 L1000



CCT	2700K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
COVER	Opal
LUMENS LUMINAIRE	49 Lm
LIGHT SOURCE	170 Lm
EFFICACY LUMINAIRE	41 Lm/W
LIGHT SOURCE	142 Lm/W
LIFETIME	L90B10 60.000 h

HOUSING	Aluminum, polyurethane
---------	------------------------

VOLTAGE	24 VDC
WATTAGE	1.2 W/m 0.4 W/ft

MAX RUN	40 m (131')
OTHER DETAILS	IP67 protection Dimmable

TEMPERATURE	T _c max <75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (-13°F...122°F)

DIMENSIONS	Width: 16 mm (0.63") Height: 26 mm (1.02") Length: 1000 mm (3.28")
------------	--



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.