



ULA M IP67 WHITE LIGHT

Luminaire segment

UlaM.IP67 AULMO IEC AGY EOP / FL56/Nx G4 01W 830 L1000



CCT	3000K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
COVER	Opal
LUMENS LUMINAIRE	51 Lm
LIGHT SOURCE	175 Lm
EFFICACY LUMINAIRE	43 Lm/W
LIGHT SOURCE	146 Lm/W
LIFETIME	L90B10 60.000 h

HOUSING Aluminum, polyurethane

VOLTAGE 24 VDC
WATTAGE 1.2 W/m | 0.4 W/ft

MAX RUN 40 m (131')
OTHER DETAILS IP67 protection
 Dimmable

TEMPERATURE Tc max <75°C (167°F)
OPERATING TEMP. -25°C...+50°C (-13°F...122°F)

DIMENSIONS Width: 16 mm (0.63")
 Height: 26 mm (1.02")
 Length: 1000 mm (3.28")



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
 All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.