



OUTLINE IP67 RGBW

Outline LUM-E RGBW-48-14/L3-822 AG L375

Luminaire segment


Product code: A02 LEC EC RGBW48-14L3-822 AG 0375




COLORS

Grey housing

PHOTOMETRICS




SEGMENT LAYOUT




Luminaire type segment

CONNECTION TYPE



End exit wire

TECHNICAL DRAWING



SPECTRUM	2200K CRI 80+ 3-Step MacAdam
COVER	Clear
LUMINOUS FLUX	Per segment: 117 lm Light source (per segment): 300 lm Per meter/feet: 498 lm/m 152 lm/ft RGB only: 177 lm/m
EFFICACY	Luminaire: 22 lm/W Light source: 56 lm/W
LIFETIME	L70B50 50.000h
HOUSING	Aluminum, polyurethane
ELECTRICAL	Segment power: 5.4 W Power per meter/feet: 14.4 W/m Voltage: 24 VDC
TEMPERATURE	Tc max <75°C (167°F) Operating: -25°C...+50°C (-13°F...122°F)
OTHER DETAILS	IP67 protection Dimmable
DIMENSIONS	Width: 15 mm (0.59") Height: 6 mm (0.24") Length: 379 mm 1.2'

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.