





## OUTLINE

Outline A002M IEC AGY ECL / FL56/Nx G5 04W 820 L1000



<b>TYPE</b>	White
<b>CCT</b>	2000K
<b>CRI</b>	CRI 80+
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>LUMINOUS FLUX</b>	Luminaire: 313 Lm Light Source: 501 Lm
<b>EFFICACY</b>	Luminaire: 65 Lm/W Light Source: 104 Lm/W
<b>LIFETIME</b>	L90B10 60.000h

<b>CONTROL</b>	Dimmable
----------------	----------

<b>LUMINAIRE POWER</b>	4.8 W
<b>INPUT VOLTAGE</b>	24V DC

<b>COVER</b>	Clear
<b>HOUSING</b>	Extruded aluminum, Grey
<b>IP CLASS</b>	IP67 ingress protection
<b>OTHER DETAILS</b>	Luminaire segment

<b>DIMENSIONS</b>	Width: 16 mm / 0.63" Height: 6 mm / 0.24" Length: 1004 mm / 3.3'
-------------------	--



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.