





## SLINE

sLine A018N IEC PBK EOP / FL175/Nx G4 04W 820 L1000



<b>TYPE</b>	White
<b>CCT</b>	2000K
<b>CRI</b>	CRI 80+
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>LUMINOUS FLUX</b>	Luminaire: 170 Lm Light Source: 487 Lm
<b>EFFICACY</b>	Luminaire: 35 Lm/W Light Source: 101 Lm/W
<b>LIFETIME</b>	L90B10 60.000h

<b>CONTROL</b>	Dimmable
----------------	----------

<b>LUMINAIRE POWER</b>	4.8 W
<b>INPUT VOLTAGE</b>	24V DC

<b>COVER</b>	Opal
<b>HOUSING</b>	Extruded aluminum, Black
<b>IP CLASS</b>	IP67 ingress protection
<b>OTHER DETAILS</b>	Luminaire segment

<b>DIMENSIONS</b>	Width: 8 mm / 0.31" Height: 9 mm / 0.35" Length: 1004 mm / 3.3'
-------------------	---



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.