



SLINE IP67 WHITE

sLine LUM-E FL-224-9/L3-822 AG L750

Luminaire segment


Product code: A18 LEC EO FL224-9L3-822 AG 0750




COLORS

Grey housing

PHOTOMETRICS




SEGMENT LAYOUT




Luminaire type segment

CONNECTION TYPE



End exit wire

TECHNICAL DRAWING



SPECTRUM

2200K
CRI 80+
3-Step MacAdam

COVER

Opal

LUMINOUS FLUX

Per segment: 334 lm
Light source (per segment): 765 lm
Per meter/feet: 446 lm/m | 136 lm/ft

EFFICACY

Luminaire: 46 lm/W
Light source: 106 lm/W

LIFETIME

L70B50 50.000h

HOUSING

Aluminum, polyurethane

ELECTRICAL

Segment power: 7.2 W
Power per meter/feet: 9.6 W/m
Voltage: 24 VDC

TEMPERATURE

Tc max <75°C (167°F)
Operating: -25°C...+50°C (-13°F...122°F)

OTHER DETAILS

IP67 protection
Dimmable

DIMENSIONS

Width: 10 mm (0.39")
Height: 7 mm (0.28")
Length: 754 mm | 2.5'

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%. All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.