



SLINE IP67 WHITE

sLine LUM-E FL-224-9/L3-822 AG L875


Luminaire segment




COLORS

Grey housing

PHOTOMETRICS




SEGMENT LAYOUT




Luminaire type segment

CONNECTION TYPE



End exit wire

TECHNICAL DRAWING



SPECTRUM	2200K CRI 80+ 3-Step MacAdam
COVER	Opal
LUMINOUS FLUX	Per segment: 390 lm Light source (per segment): 893 lm Per meter/feet: 446 lm/m 136 lm/ft
EFFICACY	Luminaire: 46 lm/W Light source: 106 lm/W
LIFETIME	L70B50 50.000h
HOUSING	Aluminum, polyurethane
ELECTRICAL	Segment power: 8.4 W Power per meter/feet: 9.6 W/m Voltage: 24 VDC
TEMPERATURE	Tc max <75°C (167°F) Operating: -25°C...+50°C (-13°F...122°F)
OTHER DETAILS	IP67 protection Dimmable
DIMENSIONS	Width: 10 mm (0.39") Height: 7 mm (0.28") Length: 879 mm 2.9'

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%. All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.