



ULA L IP65

ULaL.IP65 A1112 IEC AGY EOP / TW56/Nx G5 019W 820/835 L1000



TYPE	Tunable white
CCT (WARM)	2000K
CRI (WARM)	CRI 80+
CCT (COLD)	3500K
CRI (COLD)	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 1257 Lm Light Source: 2535 Lm
EFFICACY	Luminaire: 65 Lm/W
LIFETIME	Light Source: 132 Lm/W L90B10 60.000h

CONTROL	Dimmable
----------------	----------

LUMINAIRE POWER	19.2 W
INPUT VOLTAGE	24V DC

COVER	Opal
HOUSING	Extruded aluminum, Grey
IP CLASS	IP65 ingress protection
OTHER DETAILS	Luminaire segment

DIMENSIONS	Width: 34 mm / 1.34" Height: 56 mm / 2.2" Length: 1003 mm / 3.3'
-------------------	------------------------------------------------------------------------



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.