


## ULA L IP65

UlaL.IP65 A1112 IBC PBK EOP / FL-112/Nx G5 019W 820 L1000



<b>TYPE</b>	White
<b>CCT</b>	2000K
<b>CRI</b>	CRI 80+
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>LUMINOUS FLUX</b>	Luminaire: 1002 Lm Light Source: 2021 Lm
<b>EFFICACY</b>	Luminaire: 52 Lm/W Light Source: 105 Lm/W
<b>LIFETIME</b>	L90B10 60.000h

<b>CONTROL</b>	Dimmable
----------------	----------

<b>LUMINAIRE POWER</b>	19.2 W
<b>INPUT VOLTAGE</b>	24V DC

<b>COVER</b>	Opal
<b>HOUSING</b>	Extruded aluminum, Black
<b>IP CLASS</b>	IP65 ingress protection
<b>OTHER DETAILS</b>	Luminaire segment

<b>DIMENSIONS</b>	Width: 34 mm / 1.34" Height: 60 mm / 2.36" Length: 1003 mm / 3.3'
-------------------	---



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.