



ULA M IP67

UlaM.IP67 AULMO IBC PBK EOP / RGB-48/Nx G5 011W L1000



| | |
|--------------------------|---|
| TYPE | RGB |
| COLOR CONSISTENCY | 3-Step MacAdam |
| LUMINOUS FLUX | Luminaire: 216 Lm Light Source: 480 Lm Red: 47 Lm Green: 138 Lm Blue: 31 Lm |
| EFFICACY | Luminaire: 19 Lm/W |
| LIFETIME | Light Source: 42 Lm/W L90B10 60.000h |

| | |
|----------------|----------|
| CONTROL | Dimmable |
|----------------|----------|

| | |
|------------------------|---------|
| LUMINAIRE POWER | 11.52 W |
| INPUT VOLTAGE | 24V DC |

| | |
|----------------------|--------------------------|
| COVER | Opal |
| HOUSING | Extruded aluminum, Black |
| IP CLASS | IP67 ingress protection |
| OTHER DETAILS | Luminaire segment |

| | |
|-------------------|---|
| DIMENSIONS | Width: 16 mm / 0.63" Height: 26 mm / 1.02" Length: 1003 mm / 3.3' |
|-------------------|---|



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.