



ULA M IP67 WHITE LIGHT

Luminaire segment

ULA M IP67 LUM OP FL56-1/N4-822 AG L1000

Article No.: C5ABPANABXXB1000



CCT	2200K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
COVER	Opal
LUMENS LUMINAIRE	39 Lm
LIGHT SOURCE	133 Lm
EFFICACY LUMINAIRE	33 Lm/W
LIGHT SOURCE	111 Lm/W
LIFETIME	L90B10 60.000 h

HOUSING Aluminum, polyurethane

VOLTAGE 24 VDC
WATTAGE 1.2 W/m | 0.4 W/ft

MAX RUN 40 m (131')
OTHER DETAILS IP67 protection
 Dimmable

TEMPERATURE Tc max <75°C (167°F)
OPERATING TEMP. -25°C...+50°C (-13°F...122°F)

DIMENSIONS Width: 16 mm (0.63")
 Height: 26 mm (1.02")
 Length: FullLengthM mm (FullLengthFT")



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
 All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.