



ULA M IP67 WHITE LIGHT

Luminaire segment

ULA M IP67 LUM OP FL56-1/N4-835 AG L1000

Article No.: C5ABPANAFXB1000



CCT	3500K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
COVER	Opal
LUMENS LUMINAIRE	52 Lm
LIGHT SOURCE	179 Lm
EFFICACY LUMINAIRE	43 Lm/W
LIGHT SOURCE	149 Lm/W
LIFETIME	L90B10 60.000 h

HOUSING	Aluminum, polyurethane
---------	------------------------

VOLTAGE	24 VDC
WATTAGE	1.2 W/m 0.4 W/ft

MAX RUN	40 m (131')
OTHER DETAILS	IP67 protection Dimmable

TEMPERATURE	Tc max <75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (-13°F...122°F)

DIMENSIONS	Width: 16 mm (0.63") Height: 26 mm (1.02") Length: FullLengthM mm (FullLengthFT")
------------	---



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.