



## ULA M IP67 WHITE LIGHT

Luminaire segment

UlaM.IP67 AULMO IEC AGY EOP / FL56/Nx G4 01W 820 L1000



CCT	2000K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
COVER	Opal
LUMENS LUMINAIRE	36 Lm
LIGHT SOURCE	123 Lm
EFFICACY LUMINAIRE	30 Lm/W
LIGHT SOURCE	103 Lm/W
LIFETIME	L90B10 60.000 h

HOUSING	Aluminum, polyurethane
---------	------------------------

VOLTAGE	24 VDC
WATTAGE	1.2 W/m   0.4 W/ft

MAX RUN	40 m (131')
OTHER DETAILS	IP67 protection Dimmable

TEMPERATURE	Tc max <75°C ( 167°F )
OPERATING TEMP.	-25°C...+50°C ( -13°F...122°F )

DIMENSIONS	Width: 16 mm (0.63") Height: 26 mm (1.02") Length: 1000 mm (3.28")
------------	--



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.