



# ULA M IP67 WHITE LIGHT

## Luminaire segment

UlaM.IP67 AULMO IEC AGY EOP / FL56/Nx G4 01W 825 L1000



CCT	2500K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
COVER	Opal
LUMENS LUMINAIRE	42 Lm
LIGHT SOURCE	145 Lm
EFFICACY LUMINAIRE	35 Lm/W
LIGHT SOURCE	121 Lm/W
LIFETIME	L90B10 60.000 h

**HOUSING** Aluminum, polyurethane

**VOLTAGE** 24 VDC  
**WATTAGE** 1.2 W/m | 0.4 W/ft

**MAX RUN** 40 m (131')  
**OTHER DETAILS** IP67 protection  
 Dimmable

**TEMPERATURE** T<sub>c</sub> max <75°C ( 167°F )  
**OPERATING TEMP.** -25°C...+50°C ( -13°F...122°F )

**DIMENSIONS** Width: 16 mm (0.63")  
 Height: 26 mm (1.02")  
 Length: 1000 mm (3.28")



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
 All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.