



ULA S IP67 WHITE LIGHT

Luminaire segment

ULA S IP67 LUM CL FL56-2/N4-822 AGY L1000

Article No.: C4AAPAMABXXL1000



CCT	2200K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
COVER	Clear
LUMENS LUMINAIRE	177 Lm
LIGHT SOURCE	265 Lm
EFFICACY LUMINAIRE	74 Lm/W
LIGHT SOURCE	110 Lm/W
LIFETIME	L90B10 60.000 h

HOUSING Aluminum, polyurethane

VOLTAGE 24 VDC
WATTAGE 2.4 W/m | 0.7 W/ft

MAX RUN 24.5 m (80')
OTHER DETAILS IP67 protection
 Dimmable

TEMPERATURE Tc max <75°C (167°F)
OPERATING TEMP. -25°C...+50°C (-13°F...122°F)

DIMENSIONS Width: 16 mm (0.63")
 Height: 16 mm (0.63")
 Length: 1000 mm (305")



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%. All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.