





ULA S IP67 WHITE LIGHT

Luminaire segment

ULA S IP67 LUM CL FL56-2/N4-827 AGY L1000

Article No.: C4AAPAMADXXL1000



CCT	2700K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
COVER	Clear
LUMENS LUMINAIRE	226 Lm
LIGHT SOURCE	339 Lm
EFFICACY LUMINAIRE	94 Lm/W
LIGHT SOURCE	141 Lm/W
LIFETIME	L90B10 60.000 h

HOUSING	Aluminum, polyurethane
---------	------------------------

VOLTAGE	24 VDC
WATTAGE	2.4 W/m 0.7 W/ft

MAX RUN	24.5 m (80')
OTHER DETAILS	IP67 protection Dimmable

TEMPERATURE	Tc max <75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (-13°F...122°F)

DIMENSIONS	Width: 16 mm (0.63") Height: 16 mm (0.63") Length: 1000 mm (305")
------------	-------------------------------------------------------------------------



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.