



XLINe IP67 RGB

xLine LUM-E RGB-48-14/O3 AG L250

Luminaire segment


Product code: M17 LEC EO RGB48-14O3 AG 0250




COLORS

 Grey housing

PHOTOMETRICS




SEGMENT LAYOUT




Luminaire type segment

CONNECTION TYPE



End exit wire

TECHNICAL DRAWING



SPECTRUM

3-Step MacAdam

COVER

Opal

LUMINOUS FLUX

Per segment: 8 lm
Light source (per segment): 32 lm

Per meter/feet:

Total: 127 Lm/m | 39 Lm/ft
Red: 25 Lm/m | 8 Lm/ft
Green: 84 Lm/m | 26 Lm/ft
Blue: 18 Lm/m | 5 Lm/ft

EFFICACY

Luminaire: 2 lm/W
Light source: 9 lm/W

LIFETIME

L70B50 50.000h

HOUSING

Aluminum, polyurethane

ELECTRICAL

Segment power: 3.6 W
Power per meter/feet: 14.4 W/m
Voltage: 24 VDC

TEMPERATURE

Tc max <75°C (167°F)
Operating: -25°C...+50°C (-13°F...122°F)

OTHER DETAILS

IP67 protection
Dimmable

DIMENSIONS

Width: 26 mm (1.02")
Height: 25 mm (0.98")
Length: 254 mm | 0.8'

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%. All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.