



XLINe IP67 TUNABLE WHITE

xLine LUM-E TW-56-9/N3-820/835 AG L750

Luminaire segment


Product code: M17 LEC EO TW56-9N3-820835 AG 0750




COLORS

 Grey housing

PHOTOMETRICS




SEGMENT LAYOUT




Luminaire type segment

CONNECTION TYPE



End exit wire

TECHNICAL DRAWING



SPECTRUM

Warm LED: CRI 80+ 2000K

Cold LED: CRI 80+ 3500K

3-Step MacAdam

COVER

Opal

LUMINOUS FLUX

Per segment: 68 lm

Light source (per segment): 254 lm

Per meter/feet: 339 lm/m | 103 lm/ft

EFFICACY

Luminaire: 9 lm/W

Light source: 35 lm/W

LIFETIME

L90B10 60.000h

HOUSING

Aluminum, polyurethane

ELECTRICAL

Segment power: 7.2 W

Power per meter/feet: 9.6 W/m

Voltage: 24 VDC

TEMPERATURE

T_c max <75°C (167°F)

Operating: -25°C...+50°C (-13°F...122°F)

OTHER DETAILS

IP67 protection

Dimmable

DIMENSIONS

Width: 26 mm (1.02")

Height: 25 mm (0.98")

Length: 754 mm | 2.5'

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%. All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.