


A035x

SPECIFICATION SHEET



Project

Date

Quantity

Notes

ORDER CODE


MODEL	SEGMENT	WIRE EXIT	LED ALIGN	COLOR	COVER	LED SOURCE	WATTAGE	CRI	CCT	SEGMENT LENGTH	CONNECTOR
A035x											

SEGMENT	L Individual	S start	M middle	E end	F full																				
WIRE EXIT	E end	B back	S side																						
LED ALIGN	C center	L left	R right																						
COLOR	AGY anodized gray 	PWE painted white 	PBK painted black 	CUSTOM contact sales 																					
COVER	PRM.A035x.C01.OPL opal	PRM.A035x.C02.CLR clear	PRM.A035x.C03.CLR clear	PRM.A035x.C04.CLR clear	PRM.A035x.C05.CLR clear	PRM.A035x.C06.CLR clear																			
	PRM.A035x.C07.CLR clear	PRM.A035x.C07.OPL opal																							
LED SOURCE	FL112/Nx G4 static white cutting increment 62.5 mm (2.46")	FL112/Dx G4 static white 62.5 mm (2.46")	TW56/Nx G4 tunable white 125 mm (4.92")	TW56/Dx G4 tunable white 125 mm (4.92")	TW2-112/Nx G4 dual tunable white 62.5 mm (2.46")	RGB96/Nx G4 RGB 62.5 mm (2.46")	RGBW48/Nx G4 RGB+W 125 mm (4.92")																		
WATTAGE	1 1,2W/m 0.37W/ft static white	2 2,4 W/m 0.7 W/ft static white	4 4,8 W/m 1.5 W/ft static white	7,2 7,2 W/m 2.1 W/ft RGB	9 9,6 W/m 2.9 W/ft static white, TW , TW2, RGBW	11 11,52 W/m 3.5 W/ft RGB	14 14,4 W/m 4.4 W/ft static white, RGB	18 18,2 W/m 5.54 W/ft static white , TW	19 19,2 W/m 5.8 W/ft static white , TW2																
CRI	8 CRI 80+	9 CRI 90+	0 CRI 95+ *for FL112/Nx G4, RGBW48/Nx G4 only																						
CCT	20 2000K *for Nx LED strip only	22 2200K	25 2500K *for Nx LED strip only	27 2700K	30 3000K	35 3500K	40 4000K	50 5000K	57 5700K	65 6500K															
SEGMENT LENGTH	For 62.5mm (2.46") LED strip cutting increment																								
	in mm	4.9" 125	7.4" 188	9.8" 250	1' 0.3" 313	1' 2.8" 375	1' 5.2" 438	1' 7.7" 500	1' 10" 563	2' 0.6" 625	2' 3.1" 688	2' 5.5" 750	2' 8" 813	2' 10" 875	3' 0.9" 938	3' 3.4" 1000	3' 5.9" 1063	3' 8.3" 1125	3' 11" 1188	4' 1.2" 1250	4' 3.7" 1313	4' 6.1" 1375	4' 8.6" 1438	4' 11" 1500	5' 1.5" 1563
	in mm	5' 4" 1625	5' 6.5" 1688	5' 8.9" 1750	5' 11" 1813	6' 1.8" 1875	6' 4.3" 1938	6' 6.7" 2000	6' 9.2" 2063	6' 12" 2125	7' 2.1" 2188	7' 4.6" 2250	7' 7.1" 2313	7' 9.5" 2375	7' 12" 2438	8' 2.4" 2500	8' 4.9" 2563	8' 7.3" 2625	8' 9.8" 2688	9' 0.3" 2750	9' 2.7" 2813	9' 5.2" 2875	9' 7.7" 2938	9' 10" 3000	
	For 125mm (4.92")LED strip cutting increment																								
	in mm	4.9" 125	9.8" 250	1' 2.8" 375	1' 7.7" 500	2' 0.6" 625	2' 5.5" 750	2' 10" 875	3' 3.4" 1000	3' 8.3" 1125	4' 1.2" 1250	4' 6.1" 1375	4' 11" 1500	5' 4" 1625	5' 8.9" 1750	6' 1.8" 1875	6' 6.7" 2000	6' 12" 2125	7' 4.6" 2250	7' 9.5" 2375	8' 2.4" 2500	8' 7.3" 2625	9' 0.3" 2750	9' 5.2" 2875	9' 10" 3000
CONNECTOR	NON no connectors	PH1 connector																							



COVERS


PRG.A035X.C01.OPL
opal




PRG.A035X.C02.CLR
90% light transmission, asymmetric cover




PRG.A035X.C03.CLR
82% light transmission




PRG.A035X.C04.CLR
88% light transmission



PRG.A035X.C05.CLR
90% light transmission



PRG.A035X.C06.CLR
92% light transmission



PRG.A035X.C07.CLR
92% light transmission




PRG.A035X.C07.OPL
opal




BRACKETS


PRG.A035X.F04.GZK
metal




PRG.A035X.F01.GZK
metal




PRG.A035X.F02.GZK
metal, 45°



PRG.A035X.F03.GZK



PRG.A035X.F01.RWE
plastic




PRG.A035X.F06.RWE
plastic, 15°




PRG.A035X.F08.RWE
plastic, 30°



PRG.A035X.F02.RWE
plastic, 45°




PRG.A035X.F09.RWE
plastic, 60°



WIRE


E - END EXIT WIRE

wire comes out from profile through endcap



B - BACK EXIT WIRE

wire through a hole on the back of the profile



Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.

All values in datasheet are for reference only and customers should take these values on their own risk. Holecron reserves the right for changes without prior notice.


www.holecron.com | Customizable Linear LED Lighting Products

SEGMENTS

INDIVIDUAL LUMINAIRE

Comes as individual luminaire with a connection to the power supply.

L - LUMINAIRE




Endcaps on both ends
Input wire with male connector, no output wire
Module length = **LENGTH** + 10mm (0,39") - end wire exit
Module length = **LENGTH** + 6mm (0,23") - back wire exit

CONTINUOUS LINE

Connecting LED modules to a continuous line, no connection mark is visible between the modules.

S - START MODULE




Endcap on single end only
Input wire with male connector, output with female
Module length = **LENGTH** + 4mm (0,15")

M - MIDDLE MODULE



No endcaps on both ends
Input wire with male connector, output with female
Module length = **LENGTH** + 2 mm (0,07")

E - END MODULE



Endcap on single end only
Input wire with male connector, no output cable
Module length = **LENGTH** + 4mm (0,15")

FULL SET INSTALLATION

Connecting the LED module to a line connection endcaps are visible, no continuous light line is obtained.

F - FULL SET MODULE



Endcap on both ends
Input wire with male connector, output female
Module length = **LENGTH** + 14mm (0,55") - end wire exit
Module length = **LENGTH** + 6mm (0,23") - back wire exit

F - FULL SET MODULE




L - LUMINAIRE or F - FULL SET MODULE



WIRE


PH1M - MALE CONNECTOR

for indoor use only




PH1F - FEMALE CONNECTOR

for indoor use only



NON - NO CONNECTORS (LEAD WIRES END)

any connector can be applied



CONNECTOR DIMENSIONS		MALE		FEMALE	
WHITE 2-PIN	Length	0.61"	15.5 mm	0.59"	15 mm
	Width	0.263"	6.7 mm	0.24"	6.1 mm
	Height	0.196"	5 mm	0.196"	5 mm
TW 3-PIN	Length	0.61"	15.5 mm	0.59"	15 mm
	Width	0.362"	9.2 mm	0.338"	8.6 mm
	Height	0.196"	5 mm	0.196"	5 mm
RGB 4-PIN	Length	0.61"	15.5 mm	0.59"	15 mm
	Width	0.648"	16.5 mm	0.437"	11.1 mm
	Height	0.204"	5.2 mm	0.196"	5 mm
RGBW 5-PIN	Length	0.61"	15.5 mm	0.59"	15 mm
	Width	0.559"	14.2 mm	0.535"	13.6 mm
	Height	0.196"	5 mm	0.196"	5 mm

LEAD CABLES

Lead-wire cables are used to connect the LED module to the power supply unit.

FOR WHITE LEDS

HR 2PIN P1M.NON LXXX



FOR TUNABLE WHITE LEDS

HR 3PIN P1M.NON LXXX



FOR RGB LEDS

HR 4PIN P1M.NON LXXX



FOR RGB+W LEDS

HR 5PIN P1M.NON LXXX



EXTENSION CABLES

Extension cables are used to connect two remote LED modules.

FOR WHITE LEDS

HR 2PIN P1M.P1F LXXXX



FOR TUNABLE WHITE LEDS

HR 3PIN P1M.P1F LXXXX



FOR RGB LEDS

HR 4PIN P1M.P1F LXXXX



FOR RGB+W LEDS

HR 5PIN P1M.P1F LXXXX



EXTENSION CABLES LENGTHS

LXXX	L200	L1000	L2000	L5000	L9000
LENGTH	200 mm 7.9 in	1000 mm 3 ft 3 in	2000 mm 6 ft 6 in	5000 mm 16 ft 4 in	9000 mm 29 ft 5 in

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.

All values in datasheet are for reference only and customers should take these values on their own risk. Holectron reserves the right for changes without prior notice.

www.holectron.com | Customizable Linear LED Lighting Products

LUMEN VALUES OF LED STRIPS

FL112/DX G5 - WHITE LIGHT



CRI 80+		POWER											
SPECTRUM	KELVINS	1,92 W/m	0.6 W/ft	2.4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9.6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft
		1		2		4		9		14		19	
		lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
822	2200K	-		-		568	173	1111	338	1653	503	2194	668
827	2700K	-		-		647	197	1267	386	1882	573	2499	761
830	3000K	-		-		647	197	1267	386	1882	573	2499	761
835	3500K	-		-		686	209	1342	409	1997	608	2652	808
840	4000K	-		-		686	209	1342	409	1997	608	2652	808
850	5000K	-		-		724	220	1416	431	2108	642	2800	853
857	5700K	-		-		724	220	1416	431	2108	642	2800	853
865	6500K	-		-		724	220	1416	431	2108	642	2800	853
EFFICACY						151 lm/W		148 lm/W		146 lm/W		146 lm/W	

CRI 90+		POWER											
SPECTRUM	KELVINS	1,92 W/m	0.6 W/ft	2.4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9.6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft
		1		2		4		9		14		19	
		lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
922	2200K	-		-		460	140	915	279	1346	410	1772	540
T927	2700K	-		-		672	205	1332	406	1971	600	2598	791
T930	3000K	-		-		683	208	1344	409	1993	607	2632	801
T935	3500K	-		-		683	208	1355	413	2004	610	2643	805
T940	4000K	-		-		705	215	1388	423	2049	624	2699	822
T950	5000K	-		-		705	215	1388	423	2049	624	2699	822
T957	5700K	-		-		683	208	1355	413	2004	610	2643	805
T965	6500K	-		-		683	208	1355	413	2004	610	2643	805
EFFICACY						147 lm/W		145 lm/W		142 lm/W		139 lm/W	

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.

All values in datasheet are for reference only and customers should take these values on their own risk. Holectron reserves the right for changes without prior notice.

LUMEN VALUES OF LED STRIPS

FL112/NX G5 - WHITE LIGHT



CRI 80+		POWER											
SPECTRUM	KELVINS	1,92 W/m	0.6 W/ft	2.4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9.6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft
		1		2		4		9		14		19	
		lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
820	2000K	-		-		490	149	1002	305	1516	462	2021	615
822	2200K	-		-		531	162	1084	330	1640	499	2186	666
825	2500K	-		-		581	177	1187	361	1796	547	2393	729
827	2700K	-		-		679	207	1388	423	2100	639	2799	852
830	3000K	-		-		700	213	1429	435	2162	658	2882	878
835	3500K	-		-		716	218	1462	445	2212	674	2948	898
840	4000K	-		-		718	219	1466	446	2218	675	2957	900
850	5000K	-		-		789	240	1563	476	2324	708	3070	935
857	5700K	-		-		761	232	1508	459	2242	683	2963	902
865	6500K	-		-		761	232	1508	459	2242	683	2963	902
EFFICACY						164 lm/W		163 lm/W		161 lm/W		160 lm/W	

CRI 90+		POWER											
SPECTRUM	KELVINS	1,92 W/m	0.6 W/ft	2.4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9.6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft
		1		2		4		9		14		19	
		lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
920	2000K	-		-		425	130	840	256	1244	379	1637	499
922	2200K	-		-		465	142	908	277	1346	410	1771	540
925	2500K	-		-		499	152	986	301	1460	445	1921	586
T927	2700K	-		-		701	213	1390	423	2065	629	2729	831
T930	3000K	-		-		737	224	1460	445	2170	661	2868	873
T935	3500K	-		-		755	230	1497	456	2226	678	2941	896
T940	4000K	-		-		766	233	1518	462	2257	687	2982	908
T950	5000K	-		-		768	234	1524	464	2268	691	2999	913
T957	5700K	-		-		741	226	1470	448	2188	666	2893	881
T965	6500K	-		-		741	226	1470	448	2188	666	2893	881
EFFICACY						160 lm/W		159 lm/W		158 lm/W		156 lm/W	

CRI 95+		POWER											
SPECTRUM	KELVINS	1,92 W/m	0.6 W/ft	2.4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9.6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft
		1		2		4		9		14		19	
		lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
027	2700K	-		-		491	150	973	296	1443	439	1900	579
030	3000K	-		-		501	153	994	303	1475	449	1942	591
035	3500K	-		-		512	156	1015	309	1506	459	1984	604
040	4000K	-		-		519	158	1028	313	1525	464	2009	612
050	5000K	-		-		554	169	1101	335	1637	498	2159	657
EFFICACY						115 lm/W		115 lm/W		114 lm/W		112 lm/W	

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.

All values in datasheet are for reference only and customers should take these values on their own risk. Holectron reserves the right for changes without prior notice.

www.holectron.com | Customizable Linear LED Lighting Products

LUMEN VALUES OF LED STRIPS

TW56/Nx G5 - TUNABLE WHITE LIGHT

CRI 80+		POWER			
SPECTRUM	KELVINS	9,6 W/m	2.9 W/ft	19,2 W/m	5.8 W/ft
		9		19	
		lm/m	lm/ft	lm/m	lm/ft
820/865	2000-6500K	1255	382	2491	759
825/857	2500-5700K	1347	410	2677	815
827/857	2700-5700K	1448	441	2880	877
827/850	2700-5000K	1475	449	2934	893
827/865	2700-6500K	1448	441	2880	877
EFFICACY		158 lm/W		157 lm/W	

CRI 90+		POWER			
SPECTRUM	KELVINS	9,6 W/m	2.9 W/ft	19,2 W/m	5.8 W/ft
		9		19	
		lm/m	lm/ft	lm/m	lm/ft
920/965	2000-6500K	1084	330	2124	647
925/957	2500-5700K	1161	354	2275	693
927/950	2700-5000K	1272	387	2498	761
EFFICACY		146 lm/W		146 lm/W	



TW56/DX G5 - TUNABLE WHITE LIGHT

CRI 80+		POWER			
SPECTRUM	KELVINS	9,6 W/m	2.9 W/ft	19,2 W/m	5.8 W/ft
		9		19	
		lm/m	lm/ft	lm/m	lm/ft
822/865	2200-6500K	1271	387	2488	758
827/857	2700-5700K	1348	410	2637	803
827/850	2700-5000K	1348	410	2637	803
870/865	2700-6500K	1348	410	2637	803
EFFICACY		148 Lm/W		146 Lm/W	

CRI 90+		POWER			
SPECTRUM	KELVINS	9,6 W/m	2.9 W/ft	19,2 W/m	5.8 W/ft
		9		19	
		lm/m	lm/ft	lm/m	lm/ft
922/965	2200-6500K	1153	351	2229	679
927/957	2700-5700K	1221	372	2359	718
927/950	2700-5000K	1187	361	2293	698
927/965	2700-6500K	1221	372	2359	718
EFFICACY		143 lm/W		140 lm/W	



LUMEN VALUES OF LED STRIPS

TW2-112/NX G4 - TUNABLE DUAL WHITE LIGHT

CRI 80+						POWER			
SPECTRUM	KELVINS	9,6 W/m 2.9 W/ft		19,2 W/m 5.9 W/ft		33,6 W/m 10.02 W/ft		48 W/m 14.6 W/ft	
		9		19		33		48	
822/865	2200-6500K	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
		1343	409	2665	811	-		-	
EFFICACY		140 Lm/W		139 Lm/W					



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. Holectron reserves the right for changes without prior notice.
www.holectron.com | Customizable Linear LED Lighting Products

LUMEN VALUES OF LED STRIPS

RGB48/NX G5 - RGB LIGHT

RGB	POWER			
	7,2 W/m	2.2 W/ft	11,52 W/m	3.5 W/ft
COLOR	7		11	
	lm/m	lm/ft	lm/m	lm/ft
RED	65	20	104	32
GREEN	208	63	307	93
BLUE	43	13	69	21
TOTAL RGB LUMINOUS FLUX	316	96	480	146
EFFICACY	44 lm/W		42 lm/W	



RGB96/NX G5 - RGB LIGHT

RGB	POWER			
	11,52 W/m	3.5 W/ft	14,4 W/m	4.4 W/ft
COLOR	11		14	
	lm/m	lm/ft	lm/m	lm/ft
RED	104	32	130	40
GREEN	306	93	383	117
BLUE	69	21	87	26
TOTAL RGB LUMINOUS FLUX	479	146	600	183
EFFICACY	42 lm/W		42 lm/W	



RGBW48/NX G5 - RGBW LIGHT

RGBW	POWER					
	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft
COLOR	9		14		19	
	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
RED	65	20	98	30	-	-
GREEN	208	63	287	87	-	-
BLUE	43	13	65	20	-	-
TOTAL RGB LUMINOUS FLUX	316	96	450	137		



CRI 80+		POWER					
SPECTRUM	KELVINS	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft
		9		14		19	
		lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
820	2000K	210	64	319	97	-	-
822	2200K	227	69	345	105	-	-
825	2500K	249	76	378	115	-	-
827	2700K	291	89	442	135	-	-
830	3000K	300	91	455	139	-	-
835	3500K	306	93	466	142	-	-
840	4000K	307	93	467	142	-	-
850	5000K	338	103	505	154	-	-
857	5700K	326	99	487	148	-	-
865	6500K	326	99	487	148	-	-
EFFICACY		141 lm/W		140 lm/W			

CRI 90+		POWER					
SPECTRUM	KELVINS	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft
		9		14		19	
		lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
920	2000K	182	55	271	83	-	-
922	2200K	197	60	294	90	-	-
925	2500K	213	65	318	97	-	-
T927	2700K	300	91	448	136	-	-
T930	3000K	315	96	471	143	-	-
T935	3500K	323	98	483	147	-	-
T940	4000K	328	100	490	149	-	-
T950	5000K	329	100	491	150	-	-
T957	5700K	317	97	474	144	-	-
T965	6500K	317	97	474	144	-	-
EFFICACY		137 lm/W		136 lm/W			

CRI 95+		POWER					
SPECTRUM	KELVINS	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft
		9		14		19	
		lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
027	2700K	210	64	314	96	-	-
030	3000K	215	65	321	98	-	-
035	3500K	219	67	328	100	-	-
040	4000K	222	68	332	101	-	-
050	5000K	237	72	355	108	-	-
EFFICACY		99 lm/W		99 lm/W			

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.

All values in datasheet are for reference only and customers should take these values on their own risk. Holectron reserves the right for changes without prior notice.

www.holectron.com | Customizable Linear LED Lighting Products


POWER CONSUMPTION PER FIXTURE LENGTH

		4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	17,3 W/m	5.3 W/ft	19,2 W/m	5.9 W/ft
LENGTH		4		9		14		17		19	
4.9"	125 mm	0.6	0.2	1.2	0.4	1.8	0.5	2.2	0.7	2.4	0.7
7.4"	188 mm	0.9	0.3	1.8	0.5	2.7	0.8	3.3	1.0	3.6	1.1
9.8"	250 mm	1.2	0.4	2.4	0.7	3.6	1.1	4.3	1.3	4.8	1.5
1'	313 mm	1.5	0.5	3.0	0.9	4.5	1.4	5.4	1.6	6.0	1.8
1' 2"	375 mm	1.8	0.5	3.6	1.1	5.4	1.6	6.5	2.0	7.2	2.2
1' 5"	438 mm	2.1	0.6	4.2	1.3	6.3	1.9	7.6	2.3	8.4	2.6
1' 7"	500 mm	2.4	0.7	4.8	1.5	7.2	2.2	8.7	2.6	9.6	2.9
1' 10"	563 mm	2.7	0.8	5.4	1.6	8.1	2.5	9.7	3.0	10.8	3.3
2'	625 mm	3.0	0.9	6.0	1.8	9.0	2.7	10.8	3.3	12.0	3.7
2' 3"	688 mm	3.3	1.0	6.6	2.0	9.9	3.0	11.9	3.6	13.2	4.0
2' 5"	750 mm	3.6	1.1	7.2	2.2	10.8	3.3	13.0	4.0	14.4	4.4
2' 8"	813 mm	3.4	1.0	6.8	2.1	10.3	3.1	12.3	3.8	13.7	4.2
2' 10"	875 mm	4.2	1.3	8.4	2.6	12.6	3.8	15.1	4.6	16.8	5.1
3'	938 mm	4.5	1.4	9.0	2.7	13.5	4.1	16.2	4.9	18.0	5.5
3' 3"	1000 mm	4.8	1.5	9.6	2.9	14.4	4.4	17.3	5.3	19.2	5.8
3' 5"	1063 mm	5.1	1.6	10.2	3.1	15.3	4.7	18.4	5.6	20.4	6.2
3' 8"	1125 mm	5.4	1.6	10.8	3.3	16.2	4.9	19.5	5.9	21.6	6.6
3' 10"	1188 mm	5.7	1.7	11.4	3.5	17.1	5.2	20.6	6.3	22.8	6.9
4' 1"	1250 mm	6.0	1.8	12.0	3.7	18.0	5.5	21.6	6.6	24.0	7.3
4' 3"	1313 mm	6.3	1.9	12.6	3.8	18.9	5.8	22.7	6.9	25.2	7.7
4' 6"	1375 mm	6.6	2.0	13.2	4.0	19.8	6.0	23.8	7.2	26.4	8.0
4' 8"	1438 mm	6.9	2.1	13.8	4.2	20.7	6.3	24.9	7.6	27.6	8.4
4' 11"	1500 mm	7.2	2.2	14.4	4.4	21.6	6.6	26.0	7.9	28.8	8.8
5' 1"	1563 mm	7.5	2.3	15.0	4.6	22.5	6.9	27.0	8.2	30.0	9.1
5' 4"	1625 mm	7.8	2.4	15.6	4.8	23.4	7.1	28.1	8.6	31.2	9.5
5' 6"	1688 mm	8.1	2.5	16.2	4.9	24.3	7.4	29.2	8.9	32.4	9.9
5' 9"	1750 mm	8.4	2.6	16.8	5.1	25.2	7.7	30.3	9.2	33.6	10.2
5' 11"	1813 mm	8.7	2.6	17.4	5.3	26.1	7.9	31.4	9.6	34.8	10.6
6' 2"	1875 mm	9.0	2.7	18.0	5.5	27.0	8.2	32.4	9.9	36.0	11.0
6' 4"	1938 mm	9.3	2.8	18.6	5.7	27.9	8.5	33.5	10.2	37.2	11.3
6' 6"	2000 mm	9.6	2.9	19.2	5.8	28.8	8.8	34.6	10.5	38.4	11.7
6' 9"	2063 mm	9.9	3.0	19.8	6.0	29.7	9.0	35.7	10.9	39.6	12.1
6' 11"	2125 mm	10.2	3.1	20.4	6.2	30.6	9.3	36.8	11.2	40.8	12.4
7' 2"	2188 mm	10.5	3.2	21.0	6.4	31.5	9.6	37.9	11.5	42.0	12.8
7' 4"	2250 mm	10.8	3.3	21.6	6.6	32.4	9.9	38.9	11.9	43.2	13.2
7' 7"	2313 mm	11.1	3.4	22.2	6.8	33.3	10.1	40.0	12.2	44.4	13.5
7' 9"	2375 mm	11.4	3.5	22.8	6.9	34.2	10.4	41.1	12.5	45.6	13.9
7' 11"	2438 mm	11.7	3.6	23.4	7.1	35.1	10.7	42.2	12.8	46.8	14.3
8' 2"	2500 mm	12.0	3.7	24.0	7.3	36.0	11.0	43.3	13.2	48.0	14.6
8' 5"	2563 mm	12.3	3.7	24.6	7.5	36.9	11.2	44.3	13.5	49.2	15.0
8' 7"	2625 mm	12.6	3.8	25.2	7.7	37.8	11.5	45.4	13.8	50.4	15.3
8' 10"	2688 mm	12.9	3.9	25.8	7.9	38.7	11.8	46.5	14.2	51.6	15.7
9'	2750 mm	13.2	4.0	26.4	8.0	39.6	12.1	47.6	14.5	52.8	16.1
9' 2"	2813 mm	13.5	4.1	27.0	8.2	40.5	12.3	48.7	14.8	54.0	16.4
9' 5"	2875 mm	13.8	4.2	27.6	8.4	41.4	12.6	49.7	15.1	55.2	16.8
9' 7"	2938 mm	14.1	4.3	28.2	8.6	42.3	12.9	50.8	15.5	56.4	17.2
9' 10"	3000 mm	14.4	4.4	28.8	8.8	43.2	13.2	51.9	15.8	57.6	17.5

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. Holectron reserves the right for changes without prior notice.
www.holectron.com | Customizable Linear LED Lighting Products


POWER SUPPLIES

POWER SUPPLY MEANWELL PWM-40W 24V IP67




Order code	DRI.V24.OCO.FO.MW.00043
Rated supply voltage	115 - 277 V AC
AC voltage range	90 - 305 V AC
Output voltage	24 V DC
Output power	40 W
Dimming	0-10 V / PWM
IP class	IP67

POWER SUPPLY MEANWELL PWM-60W 24V IP67




Order code	DRI.V24.OCO.DA.MW.00012
Rated supply voltage	115 - 277 V AC
AC voltage range	90 - 305 V AC
Output voltage	24 V DC
Output power	60 W
Dimming	DALI
IP class	IP67

POWER SUPPLY MEANWELL PWM-90W 24V IP67



Order code	DRI.V24.OCO.DA.MW.00011
Rated supply voltage	115 - 277 V AC
AC voltage range	90 - 305 V AC
Output voltage	24 V DC
Output power	90 W
Dimming	DALI
IP class	IP67


POWER SUPPLY MEANWELL PWM-120W 24V IP67



Order code	DRI.V24.OCO.DA.MW.00006
Rated supply voltage	115 - 277 V AC
AC voltage range	90 - 305 V AC
Output voltage	24 V DC
Output power	120 W
Dimming	DALI
IP class	IP67

POWER SUPPLY 100W 24V IP67

for outdoor and indoor use




Order code	PSU MW ELG 100W 24V 5Y IP67 UL
Rated supply voltage	100-305 V 50/60 Hz
Output voltage	24 V DC
Output power	70 W (100-180 V AC) 96 W (200-305 V AC)
Dimming	non-dimmable
IP class	IP67

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.


All values in datasheet are for reference only and customers should take these values on their own risk. Holecron reserves the right for changes without prior notice.

www.holecron.com | Customizable Linear LED Lighting Products

for outdoor and indoor use




Order code	PSU MW ELG 150W 24V 5Y IP67 UL
Rated supply voltage	100-305 V 50/60 Hz
Output voltage	24 V DC
Output power	105 W (100-180 V AC) 150 W (200-305 V AC)
Dimming	non-dimmable
IP class	IP67




Order code	DRI.V24.OCO.DA.MW.00004
Rated supply voltage	115 - 277 V AC
AC voltage range	100 - 305 V AC
Output voltage	24 V DC
Output power	200 W
Dimming	DALI-2
IP class	IP67

with 0-10V dimming for outdoor and indoor use




Order code	PSU MW PWM 40W 24V 5Y IP67 UL
Rated supply voltage	90-305 V 50/60 Hz
Output voltage	24 V DC
Output power	40 W
Dimming	0-10V
IP class	IP 67

with 0-10V / DALI dimming for outdoor and indoor use



Order code	PSU MW PWM 60W 24V 5Y IP67 UL
Rated supply voltage	90-305 V 50/60 Hz
Output voltage	24 V DC
Output power	60 W
Dimming	0-10V / DALI
IP class	IP67


with 0-10V / DALI dimming for outdoor and indoor use



Order code	PSU MW PWM 90W 24V 5Y IP67 UL
Rated supply voltage	90-305 V 50/60 Hz
Output voltage	24 V DC
Output power	90 W
Dimming	0-10V / DALI
IP class	IP67


POWER SUPPLY 120W 24V IP67 0-10V

with 0-10V / DALI dimming for outdoor and indoor use



Order code	PSU MW PWM 120W 24V 5Y IP67 UL
Rated supply voltage	90-305 V 50/60 Hz
Output voltage	24 V DC
Output power	120 W
Dimming	0-10V / DALI
IP class	IP67

POWER SUPPLY 240W 24V IP67




Order code	DRI.V24.OCO.FO.MW.00040
Rated supply voltage	115 - 277 V AC
AC voltage range	100 - 305 V AC
Output voltage	24 V DC
Output power	240 W
Dimming	no dimming
IP class	IP67

CONTROLLERS

WIRELESS BLUETOOTH


wireless controll using iOS or Android smartphones or tablets, for white, tunable white, RGB and RGB+W fixtures



Order code	DIM-CA-BT/PWM4
Control type	Wireless Bluetooth BLE Control using iOS or Android phones or tablets
LED type	Single color, Tunable white, RGB, RGB+W
Input voltage	12-24 VDC
Input current max	6A or 4A (US and Canada)
Output voltage	Same as input voltage
Output current	6 A (can be freely divided between the channels) 4 A (US and Canada)
Dimming method	PWM
IP class	IP20

0-10V FOR TUNABLE WHITE

for tunable white fixtures



Order code	DIM EL 1-10V/TW
Control type	0-10V
LED type	Tunable white
Input voltage	12-24 VDC
Input current max	8 A, irrespective of PSU voltage
Output voltage	Same as input voltage
Output current	8 A maximum, irrespective of whether using one or both LED outputs
IP class	IP20

DMX/DALI FOR RGB+W


for white, tunable white, RGB and RGB+W fixtures



Length (L)	typical: 153 mm / 6.02 in
Width (W)	typical: 50 mm / 1.97 in
Height (H)	typical: 23 mm / 0.91 in
Weight	144 g

Order code	DIM EL DALI/RGBW
Control type	DMX and DALI
LED type	Single color, Tunable white, RGB, RGB+W
Input voltage	12-48 VDC
Input current max	24 A, irrespective of PSU voltage
Output voltage	Same as input voltage
Output current	RGBW @ 24V: 6A RGB @ 24V: 6A
IP class	IP20

DRIVER ENCLOSURES








SIZE OPTIONS	A - LENGTH	C - HEIGHT	B - WIDTH
1	534 mm 21 inch	45 mm 1.7"	65 mm 2.6"
2	330 mm 13 inch	45 mm 1.7"	65 mm 2.6"

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.

All values in datasheet are for reference only and customers should take these values on their own risk. Holecron reserves the right for changes without prior notice.

www.holecron.com | Customizable Linear LED Lighting Products

INSTALLATION GUIDE




SINGLE LUMINAIRE




7

CONTINUOUS LINE



8

FULL LUMINAIRE



9

SAFETY / WARNINGS / DISCLOSURES

1. Install in accordance with national and local electrical code regulations.
2. Do not modify or disassemble this product beyond instructions or the warranty will be void.
3. Our channels, covers, end caps, and mounting brackets are also suitable for outdoor use with some considerations. Please consult with local Holecron representative to pick right fixtures for outdoor use.
4. Indoor (IP20) fixtures should never be mounted in areas receiving direct sunlight and locations where they can be submerged under water or might get in direct contact with water or puddling (rainfall, sprinkler, spray, etc.).
5. Avoid leaving gaps in any of the end cap or cover mating edges to the channel that will allow excess dust, debris, or water/moisture to enter the channel enclosure.
6. Actual product color may vary from what is pictured on this sheet and other print materials due to the limitations of photographic processes.
7. We reserve the right to modify and improve the design of our fixtures without prior notice. We cannot guarantee to match existing installed fixtures for subsequent orders or replacements in regards to product appearance, CCT, or lumen output.

SAFETY / WARNINGS / DISCLOSURES

Limited Warranty

This product has a five (5) year limited warranty from the date of shipment. This warranty does not include the additional accessories referenced in this specification sheet. Complete warranty details for fixtures and additional accessories are available online [download here](#). For warranty related questions please contact product support.

CONSUMER'S ACKNOWLEDGMENT

Holecron stands behind its products when they are used properly and according to our specifications. By purchasing our products, the purchaser agrees and acknowledges that lighting design, configuration and installation is a complex process, wherein seemingly minor factors or changes in layout and infield adjustments can have a significant impact on an entire system. Choosing the correct components is essential. Holecron is able to work with the original purchaser to make an appropriate product selection to the extent of the limited information that the customer can provide, but it is virtually impossible for Holecron to design a system that foresees every unknown factor. For this reason, this Warranty does not cover problems caused by improper design, configuration or installation issues.

Any statement from a Holecron employee or agent regarding a customer's bill of goods and/or purchase order is NOT an acknowledgment that the products

purchased are designed and configured correctly. The purchase agrees and acknowledges that it is the customer's responsibility to adhere strictly to all information contained in the Product Specification Sheets. There is often more than one way to design, configure and layout an LED lighting application properly to achieve the same lighting effect. Holecron strongly recommends that licensed professionals be used in the design and installation of lighting systems that include Holecron products. The specifications include important information that a designer and installer should carefully review and strictly follow. Qualified designers and certified and/or licensed installers, with access to the final installation environment, customer goals, and Holecron product specifications can make the requisite decisions appropriate for a successful finished lighting application.

HOLECTRON

HOLECTRON. All rights reserved.
Specifications are subject to change without notice.
Phone: +370 612 42446
email: info@holecron.com | www.holecron.com