HOLECTRON



V 5.1

Your unique lighting projects, our tailored solutions

CUSTOMIZABLE LINEAR LED LIGHTING PRODUCTS FOR PROFESSIONAL LIGHTING APPLICATIONS, ALL MANUFACTURED TO THE VERY HIGHEST STANDARD.

At Holectron, we aim to be flexible on everything - except quality. We work tirelessly to adapt our production processes in line with the latest trends in LED technology. This means we are always adding to and improving our product range. This approach keeps us constantly innovating and changing, but what never changes is our unwavering commitment to quality. Always eager to improve. Always meeting the highest EU quality marks. These are the standards we promise to our clients and hold ourselves to every day.

To meet Made in EU standards, all of our development and production is managed in-house at our headquarters in Vilnius, Lithuania. This enables us to ensure only the highest quality LED products are delivered to our global customers. We use the most advanced SMT mounters and automatic assembly machines to produce LED strips and every LED is mounted with pinpoint accuracy. Each strip undergoes high usage testing before leaving the factory. That is why we are able to offer a 5-year warranty on all our products.

Thanks to our commitment to quality, all you need to think about is which of our strips and luminaires best fits your project. And if you don't find exactly the right product, you can customize your own. Whatever you choose, our experienced team is on hand to help you every step of the way with specific project calculations and recommendations.

CONTENT | INDOOR

INDOOR FLEXIBLE LED STRIPS

STATIC WHITE LIGHT


FL28/Nx
page 12


FL56/Nx
page 13


FL60E/Nx
page 14


FL112/Nx
page 15


FL112/Nx 48V
page 16


FL120E/Nx
page 17


FL128/Nx
page 18


FL175/Nx
page 19


FL28/Dx
page 20


FL56/Dx
page 21


FL60E/Dx
page 22


FL112/Dx
page 23


FL112/Dx 48V
page 24


FL120E/Dx
page 25


FL128/Dx
page 26


FL175/Dx
page 27


TUNABLE WHITE LIGHT


TW-56/Nx
page 29


TW-70/Nx
page 30


TW-56/Dx
page 31


TW-70/Dx
page 32


TW2-112/Nx
page 33

RGB & RGBW LIGHT


RGB-48/Nx
page 35


RGB-96/Nx
page 36


RGBW-48/Nx
page 37


RGBW-48/Dx
page 38

INDOOR LUMINAIRES

MINIA MICROPRISM / OPAL


Pendant / Surface
page 42


Recessed
page 44


Wall
page 46

MINIAX


Pendant & Surface
page 52


Recessed
page 54


Wall
page 56


Wallwash Pendant & Surface
page 58


Wallwash Recessed
page 60

NERIS


Pendant & Surface
page 90

MINIA MESH


Pendant
page 62

MINIA SHAPE


Pendant & Surface
page 68

QUADRO


Surface
page 74


Recessed
page 76

VENTA


page 78

NEMAN HONEYCOMB


Pendant & Surface
page 84


Recessed
page 86



Trimless
page 88

INDOOR CONTINUOUS LINE MODULAR SYSTEMS

ULA


ULA S
page 96


ULA M
page 97


ULA L
page 98

INDOOR PROFILE FIXTURES



A001A
page 99


A001B
page 102


A002M
page 102


A005M
page 102


A007X
page 102


A017M
page 102


A018N
page 102


A020X
page 104


A035X
page 104


A016X
page 104



A003X
page 104


A008A
page 104


A015X
page 104



A019X
page 104


A030X
page 106



A011X
page 106


A032X
page 106


A042X
page 106


A006X
page 106


A025X
page 106


A036X
page 106


A009X
page 106


A050X
page 106

CONTENT | OUTDOOR

OUTDOOR FLEXIBLE LED STRIPS

ATLANTIS G2



Atlantis G2 top
page 112



Atlantis G2 side
page 114

AQUA



Aqua
page 118

SLEEVES



Python 02 – Side bend (6×12mm)
page 126



Python 03 – Side bend (12×20mm)
page 126



Python 04 – Side bend (20×20mm)
page 126



Cobra 07 – Top bend (16×16mm)
page 126



Viper – Top bend
page 126

OUTDOOR CONTINUOUS LINE MODULAR SYSTEMS

ULA IP 65 - 67



ULA S
page 134



ULA M
page 135



ULA L
page 136

OUTDOOR LINES IP67



Outline
page 139



sLine
page 140



mLine
page 141



xLine
page 142

OUTDOOR LUMINAIRES

VENTA IP67



page 128

NEMAN IP66



Honeycomb / Prism / Opal
page 146

INDOOR

LED STRIPS


Our strips are manufactured using the highest quality electronic components. Advanced automated assembly machines ensure pinpoint accuracy across the assembly process. Every strip goes through multiple stage testing to ensure that it meets our exacting quality standards. The result is a high-quality light that offers our customers
extra-long lifetime, durability and flexibility.

This is achieved through the combination of a copper PCB and a current stabilization system. Furthermore, special double-sided thermally conductive tape on the back guarantees perfect heat transfer to the mounting surface.

Tunable white light LED strips are the foundation of human-centric lighting solutions. These strips are essential light sources, for all solutions where human circadian rhythm effect is needed.


Overall, these all-purpose LED strips provide robust, reliable lighting for a range of uses, from cove and indirect to accent and decorative.


- CRI 80+ CRI 90+ CRI 95+
- 3-step MacAdam LEDs
- Stabilized current
- Highest quality LED strips
- Over 800 LED strips modifications
- Up to 7223 lm/m Luminous flux
- Production line focused only for LED strips
- Exporting to 46 different countries
- Thermaly conductive adhesive tape
- CE compliant
- UL approwed
- Made in Europe
- 5- year warranty
- L90B10 60.000 hours
- Up to 191 lm/W Luminous efficacy
- Customization for your project



HOLECTRON

WHITE LIGHT





FL112/Nx G5 19W 035 R10 NA HR J1x L0200 STD PH

ORDER CODE EXAMPLE

INDOOR
FLEXIBLE
LED STRIPS

FL28/Nx Nichia - White Light




TECHNICAL DATA

LEDs per meter	28 LEDs/m	9 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	250 mm	9.84"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	33' or 164'

MAXIMUM RUN

1,2 W	31 m	101'
2,4 W	20 m	65'
4,8 W	13 m	42'
9,12 W	8,5 m	27'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,12 W/m	2.8 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.5 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
820	2000K	122	37	250	76	505	154	926	282	-		-		-		-	
822	2200K	132	40	271	83	546	166	1001	305	-		-		-		-	
825	2500K	145	44	296	90	598	182	1096	334	-		-		-		-	
827	2700K	170	52	347	106	699	213	1282	391	-		-		-		-	
830	3000K	175	53	357	109	720	219	1320	402	-		-		-		-	
835	3500K	179	55	365	111	737	225	1351	412	-		-		-		-	
840	4000K	179	55	366	112	739	225	1354	413	-		-		-		-	
850	5000K	197	60	391	119	767	234	1412	430	-		-		-		-	
857	5700K	190	58	377	115	740	226	1363	415	-		-		-		-	
865	6500K	190	58	377	115	740	226	1363	415	-		-		-		-	
	EFFICACY	164 lm/W		163 lm/W		160 lm/W		147 lm/W									

CRI 90+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,12 W/m	2.8 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.5 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
920	2000K	106	32	210	64	409	125	742	226	-		-		-		-	
922	2200K	115	35	227	69	442	135	803	245	-		-		-		-	
925	2500K	124	38	246	75	480	146	871	265	-		-		-		-	
T927	2700K	175	53	347	106	682	208	1255	382	-		-		-		-	
T930	3000K	184	56	365	111	717	218	1319	402	-		-		-		-	
T935	3500K	189	58	374	114	735	224	1353	412	-		-		-		-	
T940	4000K	191	58	379	115	745	227	1371	417	-		-		-		-	
T950	5000K	192	58	381	116	749	228	1382	421	-		-		-		-	
T957	5700K	185	56	367	112	723	220	1334	406	-		-		-		-	
T965	6500K	185	56	367	112	723	220	1334	406	-		-		-		-	
	EFFICACY	160 lm/W		159 lm/W		156 lm/W		152 lm/W									

CRI 95+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,12 W/m	2.8 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.5 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
027	2700K	122	37	243	74	475	145	862	263	-		-		-		-	
030	3000K	125	38	248	76	485	148	881	269	-		-		-		-	
035	3500K	128	39	253	77	496	151	900	274	-		-		-		-	
040	4000K	129	39	257	78	502	153	911	278	-		-		-		-	
050	5000K	138	42	257	84	539	164	982	299	-		-		-		-	
	EFFICACY	115 lm/W		115 lm/W		112 lm/W		102 lm/W									

FL56/Nx Nichia - White Light




TECHNICAL DATA

LEDs per meter	56 LEDs/m	17 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	125 mm	4.92"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	33' or 164'

MAXIMUM RUN

2,4 W	18,5 m	61'
4,8 W	13 m	43'
9,6 W	7,5 m	31'
14,4 W	6 m	20'
18,2 W	5 m	16'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.5 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
820	2000K	-		245	75	501	153	1010	308	1490	454	1852	564	-		-	
822	2200K	-		265	81	542	165	1093	333	1612	491	2003	611	-		-	
825	2500K	-		290	88	593	181	1196	365	1765	538	2193	668	-		-	
827	2700K	-		339	103	694	212	1399	426	2064	629	2565	782	-		-	
830	3000K	-		350	107	714	218	1441	439	2126	648	2641	805	-		-	
835	3500K	-		358	109	731	223	1474	449	2174	663	2702	824	-		-	
840	4000K	-		359	109	733	223	1478	450	2180	664	2709	826	-		-	
850	5000K	-		394	120	781	238	1535	468	2262	689	2825	861	-		-	
857	5700K	-		380	116	754	230	1481	451	2182	665	2726	831	-		-	
865	6500K	-		380	116	754	230	1481	451	2182	665	2726	831	-		-	
	EFFICACY			164 lm/W		163 lm/W		160 lm/W		157 lm/W		155 lm/W					

CRI 90+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.5 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
920	2000K	-		212	65	420	128	818	249	1196	365	1484	452	-		-	
922	2200K	-		230	70	454	138	885	270	1294	394	1606	490	-		-	
925	2500K	-		249	76	493	150	960	293	1403	428	1742	531	-		-	
T927	2700K	-		350	107	695	212	1364	415	2010	612	2511	651	-		-	
T930	3000K	-		368	112	730	222	1434	437	2112	643	2638	669	-		-	
T935	3500K	-		377	115	748	228	1470	448	2166	660	2706	685	-		-	
T940	4000K	-		383	117	759	231	1491	454	2196	669	2743	692	-		-	
T950	5000K	-		384	117	762	232	1499	456	2211	673	2765	734	-		-	
T957	5700K	-		370	113	735	224	1446	440	2134	650	2668	730	-		-	
T965	6500K	-		370	113	735	224	1446	440	2134	650	2668	725	-		-	
	EFFICACY			160 lm/W		159 lm/W		156 lm/W		154 lm/W		152 lm/W					

CRI 95+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.5 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
027	2700K	-		245	75	486	148	950	290	1388	423	1724	525	-		-	
030	3000K	-		250	76	497	151	971	296	1419	433	1762	537	-		-	
035	3500K	-		256	78	507	155	992	302	1449	442	1799	548	-		-	
040	4000K	-		259	79	514	157	1004	306	1468	447	1822	555	-		-	
050	5000K	-		277	84	550	168	1079	329	1580	482	1965	599	-		-	
	EFFICACY			115 lm/W		115 lm/W		112 lm/W		110 lm/W		108 lm/W					

Disclaimer: Technical data is subject to change without prior notice.

INDOOR
FLEXIBLE
LED STRIPS

FL60E/Nx Nichia - White Light



TECHNICAL DATA

LEDs per meter	60 LEDs/m	19 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	100 mm	3.93"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	33' or 164'

MAXIMUM RUN

1,2 W	15,5 m	50'
2,4 W	10,5 m	34'
4,8 W	7 m	22'
9,6 W	4,5 m	14'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.5 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
820	2000K	105	32	209	64	426	130	867	264	-		-		-		-	
822	2200K	113	34	226	69	461	141	938	286	-		-		-		-	
825	2500K	124	38	247	75	505	154	1026	313	-		-		-		-	
827	2700K	145	44	289	88	591	180	1201	366	-		-		-		-	
830	3000K	149	45	298	91	608	185	1236	377	-		-		-		-	
835	3500K	153	47	305	93	622	190	1265	386	-		-		-		-	
840	4000K	153	47	305	93	624	190	1268	386	-		-		-		-	
850	5000K	169	52	338	103	672	205	1325	404	-		-		-		-	
857	5700K	164	50	327	100	649	198	1279	390	-		-		-		-	
865	6500K	164	50	327	100	649	198	1279	390	-		-		-		-	
	EFFICACY	141 lm/W		141 lm/W		140 lm/W		138 lm/W									

CRI 90+		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.5 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
920	2000K	91	28	182	55	409	110	709	216	-		-		-		-	
922	2200K	99	30	197	60	442	119	767	234	-		-		-		-	
925	2500K	107	33	214	65	480	129	832	254	-		-		-		-	
T927	2700K	151	46	301	92	597	182	1178	359	-		-		-		-	
T930	3000K	158	48	316	96	628	191	1238	377	-		-		-		-	
T935	3500K	162	49	324	99	644	196	1269	386	-		-		-		-	
T940	4000K	165	50	329	100	653	199	1287	392	-		-		-		-	
T950	5000K	165	50	329	100	655	199	1293	394	-		-		-		-	
T957	5700K	159	48	318	97	632	192	1248	380	-		-		-		-	
T965	6500K	159	48	318	97	632	192	1248	380	-		-		-		-	
	EFFICACY	138 lm/W		137 lm/W		136 lm/W		135 lm/W									

CRI 95+		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.5 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
027	2700K	105	32	210	64	418	127	822	250	-		-		-		-	
030	3000K	108	33	215	65	427	130	840	256	-		-		-		-	
035	3500K	110	33	220	67	437	133	858	261	-		-		-		-	
040	4000K	111	34	222	68	442	135	869	265	-		-		-		-	
050	5000K	119	36	238	72	473	144	933	284	-		-		-		-	
	EFFICACY	99 lm/W		99 lm/W		99 lm/W		97 lm/W									

FL112/Nx Nichia - White Light



TECHNICAL DATA

LEDs per meter	112 LEDs/m	34 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	62,5 mm	2.46"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

4,8W	13 m	43'
9,6W	9 m	29'
14,4W	7 m	22,9'
19,2W	5,5 m	18'
24W	4,5 m	15'
33,6W	3,5 m	11'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+		POWER															
		1,92 W/m	0.6 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	33,6 W/m	10.2 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
820	2000K	-		-		490	149	1002	305	1516	462	2021	616	2509	765	3436	1047
822	2200K	-		-		531	162	1084	330	1640	500	2186	666	2715	828	3718	1133
825	2500K	-		-		581	177	1187	362	1796	547	2393	729	2972	906	4070	1241
827	2700K	-		-		679	207	1388	423	2100	640	2799	853	3476	1059	4760	1451
830	3000K	-		-		700	213	1429	436	2162	659	2882	878	3579	1091	4901	1494
835	3500K	-		-		716	218	1462	446	2212	674	2948	899	3662	1116	5014	1528
840	4000K	-		-		718	219	1466	447	2218	676	2957	901	3672	1119	5028	1533
850	5000K	-		-		789	240	1563	476	2324	708	3070	936	3804	1159	5232	1595
857	5700K	-		-		761	232	1508	460	2242	683	2963	903	3670	1119	5048	1539
865	6500K	-		-		761	232	1508	460	2242	683	2963	903	3670	1119	5048	1539
	EFFICACY					164 lm/W		163 lm/W		161 lm/W		160 lm/W		159 lm/W		156 lm/W	

CRI 90+		POWER															
		1,92 W/m	0.6 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	33,6 W/m	10.2 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
920	2000K	-		-		425	130	840	256	1244	379	1637	499	2020	616	2755	840
922	2200K	-		-		465	142	908	277	1346	410	1771	540	2185	666	2980	908
925	2500K	-		-		499	152	986	301	1460	445	1921	586	2370	722	3233	985
T927	2700K	-		-		701	213	1390	423	2065	629	2729	831	3381	1030	4650	1416
T930	3000K	-		-		737	224	1460	445	2170	661	2868	873	3552	1082	4886	1488
T935	3500K	-		-		755	230	1497	456	2226	678	2941	896	3643	1109	5011	1526
T940	4000K	-		-		766	233	1518	462	2257	687	2982	908	3694	1125	5080	1547
T950	5000K	-		-		768	234	1524	464	2268	691	2999	913	3717	1132	5119	1559
T957	5700K	-		-		741	226	1470	448	2188	666	2893	881	3586	1092	4938	1504
T965	6500K	-		-		741	226	1470	448	2188	666	2893	881	3586	1092	4938	1504
	EFFICACY					160 lm/W		159 lm/W		158 lm/W		156 lm/W		155 lm/W		152 lm/W	

CRI 95+		POWER															
		1,92 W/m	0.6 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	33,6 W/m	10.2 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
027	2700K	-		-		491	150	973	297	1443	440	1900	579	2345	715	3199	975
030	3000K	-		-		501	153	994	303	1475	450	1942	592	2396	730	3269	996
035	3500K	-		-		512	156	1015	309	1506	459	1984	605	2448	746	3340	1018
040	4000K	-		-		519	158	1028	313	1525	465	2009	612	2478	755	3382	1031
050	5000K	-		-		554	169	1101	336	1637	499	2159	658	2667	813	3645	1111
	EFFICACY					115 lm/W		115 lm/W		114 lm/W		112 lm/W		111 lm/W		108 lm/W	

Disclaimer: Technical data is subject to change without prior notice.

INDOOR
FLEXIBLE
LED STRIPS

FL112/Nx 48V Nichia - White Light




TECHNICAL DATA

LEDs per meter	112 LEDs/m	34 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	125 mm	4.92"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	33' or 164'

MAXIMUM RUN

4,8 W	32,5 m	106'
9,6 W	22,5 m	73'
14,4 W	17,5 m	57'
19,2 W	14 m	45'
24 W	11 m	36'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft	24 W/m	7.3 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
820	2000K					490	149	1002	305	1516	461	2021	615	2509	763	-	
822	2200K					531	161	1084	330	1640	499	2186	665	2715	826	-	
825	2500K					581	177	1187	361	1796	547	2393	728	2972	905	-	
827	2700K					679	206	1388	422	2100	639	2799	852	3476	1058	-	
830	3000K					700	213	1429	435	2162	658	2882	877	3579	1089	-	
835	3500K					716	218	1462	445	2212	673	2948	897	3662	1115	-	
840	4000K					718	218	1466	446	2218	675	2957	900	3672	1118	-	
850	5000K					789	240	1563	476	2324	707	3070	935	3804	1158	-	
857	5700K					761	231	1508	459	2242	682	2963	902	3670	1117	-	
865	6500K					761	231	1508	459	2242	682	2963	902	3670	1117	-	
	EFFICACY					164 lm/W		163 lm/W		161 lm/W		160 lm/W		159 lm/W			

CRI 90+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft	24 W/m	7.3 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
920	2000K					425	129	840	256	1244	379	1637	498	2020	615	-	
922	2200K					465	142	908	276	1346	410	1771	539	2185	665	-	
925	2500K					499	152	986	300	1460	445	1921	585	2370	722	-	
T927	2700K					701	213	1390	423	2065	629	2729	831	3381	1030	-	
T930	3000K					737	224	1460	445	2170	661	2868	873	3552	1082	-	
T935	3500K					755	230	1497	456	2226	678	2941	896	3643	1109	-	
T940	4000K					766	233	1518	462	2257	687	2982	908	3694	1125	-	
T950	5000K					768	234	1524	464	2268	691	2999	913	3717	1132	-	
T957	5700K					741	226	1470	448	2188	666	2893	881	3586	1092	-	
T965	6500K					741	226	1470	448	2188	666	2893	881	3586	1092	-	
	EFFICACY					160 lm/W		159 lm/W		158 lm/W		156 lm/W		155 lm/W			

CRI 95+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft	24 W/m	7.3 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
027	2700K					491	150	973	296	1443	439	1900	579	2345	714	-	
030	3000K					501	153	994	303	1475	449	1942	591	2396	730	-	
035	3500K					512	156	1015	309	1506	459	1984	604	2448	745	-	
040	4000K					519	158	1028	313	1525	464	2009	612	2478	755	-	
050	5000K					554	169	1101	335	1637	498	2159	657	2667	812	-	
	EFFICACY					115 lm/W		115 lm/W		114 lm/W		112 lm/W		111 lm/W			

FL120E/Nx Nichia - White Light

TECHNICAL DATA

LEDs per meter	120 LEDs/m	39 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	50 mm	1.96"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	33' or 164'

MAXIMUM RUN

2.4 W	11 m	36'
4.8 W	7 m	22'
9.6 W	4,5 m	14'
14.4W	3,5 m	11'
19.2 W	3 m	9'



TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
820	2000K	-		209	64	418	127	853	260	1294	394	1734	529	-		-	
822	2200K	-		226	69	452	138	923	281	1401	427	1876	572	-		-	
825	2500K	-		248	76	495	151	1010	308	1533	467	2053	626	-		-	
827	2700K	-		290	88	579	176	1182	360	1793	547	2402	732	-		-	
830	3000K	-		298	91	596	182	1217	371	1846	563	2473	754	-		-	
835	3500K	-		305	93	610	186	1245	379	1889	576	2529	771	-		-	
840	4000K	-		306	93	611	186	1248	380	1894	577	2537	773	-		-	
850	5000K	-		339	103	677	206	1345	410	2003	611	2651	808	-		-	
857	5700K	-		327	100	653	199	1298	396	1932	589	2558	780	-		-	
865	6500K	-		327	100	653	199	1298	396	1932	589	2558	780	-		-	
	EFFICACY			141 lm/W		141 lm/W		140 Llm/W		139 lm/W		138 lm/W					

CRI 90+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
920	2000K	-		183	56	365	111	723	220	1074	327	1418	432	-		-	
922	2200K	-		198	60	395	120	783	239	1162	354	1534	468	-		-	
925	2500K	-		214	65	428	130	849	259	1261	384	1664	507	-		-	
T927	2700K	-		301	91	602	183	1195	364	1780	542	2356	717	-		-	
T930	3000K	-		316	96	632	192	1256	382	1870	569	2476	754	-		-	
T935	3500K	-		325	98	649	197	1288	392	1918	584	2539	773	-		-	
T940	4000K	-		329	100	658	200	1306	397	1945	592	2574	784	-		-	
T950	5000K	-		330	100	659	200	1310	399	1953	594	2587	788	-		-	
T957	5700K	-		318	96	636	193	1264	385	1884	573	2496	760	-		-	
T965	6500K	-		318	96	636	193	1264	385	1884	573	2496	760	-		-	
	EFFICACY			138 lm/W		1337 lm/W		136 lm/W		136 lm/W		135 lm/W					

CRI 95+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
027	2700K	-		211	64	421	128	837	255	1245	379	1645	501	-		-	
030	3000K	-		215	66	430	131	855	261	1273	388	1681	512	-		-	
035	3500K	-		220	67	440	134	874	266	1300	396	1717	523	-		-	
040	4000K	-		223	68	445	136	885	270	1316	401	1739	530	-		-	
050	5000K	-		238	73	476	145	947	289	1411	430	1867	569	-		-	
	EFFICACY			99 lm/W		99 lm/W		99 lm/W		98 lm/W		97 lm/W					

Disclaimer: Technical data is subject to change without prior notice.

INDOOR
FLEXIBLE
LED STRIPS

FL128/Nx Nichia - White Light



TECHNICAL DATA

LEDs per meter	128 LEDs/m	39 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	62,5 mm	2.46"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

4,8W	10,5 m	34'
7,2W	9 m	29'
9,6W	7 m	22'
14,4W	5,5 m	18'
19,2W	4 m	13'
24W	2,5 m	8'
33,6W	1,5 m	5'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER															
		1,92 W/m	0.6 W/ft	4,8 W/m	1.5 W/ft	7,2 W/m	2.2 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	33,6 W/m	10.2 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
820	2000K	-		560	171	851	259	1145	349	1733	528	2309	703	2868	873	3927	1196
822	2200K	-		606	185	921	280	1239	377	1875	571	2499	761	3103	945	4249	1294
825	2500K	-		664	202	1008	307	1356	413	2052	625	2735	833	3397	1034	4652	1417
827	2700K	-		777	237	1179	359	1586	483	2400	731	3199	974	3973	1210	5440	1656
830	3000K	-		800	244	1214	370	1633	497	2471	752	3294	1003	4091	1246	5601	1706
835	3500K	-		818	249	1242	378	1671	509	2528	770	3370	1026	4185	1274	5730	1745
840	4000K	-		820	250	1246	379	1676	510	2535	772	3379	1029	4196	1278	5746	1750
850	5000K	-		902	275	1346	410	1787	544	2656	809	3509	1068	4347	1324	5980	1821
857	5700K	-		870	265	1299	396	1724	525	2563	780	3386	1031	4195	1277	5770	1757
865	6500K	-		870	265	1299	396	1724	525	2563	780	3386	1031	4195	1277	5770	1757
	EFFICACY			188 lm/W		187 lm/W		186 lm/W		184 lm/W		183 lm/W		181 lm/W		178 lm/W	


CRI 90+

		POWER															
		1,92 W/m	0.6 W/ft	4,8 W/m	1.5 W/ft	7,2 W/m	2.2 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	33,6 W/m	10.2 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
920	2000K	-		486	148	724	220	960	292	1422	433	1871	570	2308	703	3149	959
922	2200K	-		525	160	783	238	1038	316	1538	468	2024	616	2497	760	3406	1037
925	2500K	-		570	174	850	259	1126	343	1668	508	2196	669	2709	825	3695	1125
T927	2700K	-		801	244	1196	364	1588	484	2361	719	3119	950	3864	1177	5314	1618
T930	3000K	-		842	256	1257	383	1669	508	2480	755	3277	998	4060	1236	5584	1700
T935	3500K	-		863	263	1289	393	1711	521	2544	775	3361	1023	4164	1268	5727	1744
T940	4000K	-		875	266	1307	398	1735	528	2579	785	3408	1038	4221	1285	5806	1768
T950	5000K	-		877	267	1311	399	1742	530	2592	789	3427	1044	4248	1294	5850	1781
T957	5700K	-		846	258	1265	385	1680	512	2500	761	3306	1007	4098	1248	5644	1719
T965	6500K	-		846	258	1265	385	1680	512	2500	761	3306	1007	4098	1248	5644	1719
	EFFICACY			183 lm/W		182 lm/W		181 lm/W		180lm/W		178 lm/W		177 lm/W		174 lm/W	

CRI 95+

		POWER															
		1,92 W/m	0.6 W/ft	4,8 W/m	1.5 W/ft	7,2 W/m	2.2 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	33,6 W/m	10.2 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
027	2700K	-		561	171	838	255	1112	339	1649	502	2172	661	2680	816	2656	809
030	3000K	-		573	174	856	261	1136	346	1685	513	2219	676	2739	834	3737	1138
035	3500K	-		585	178	874	266	1160	353	1721	524	2267	690	2797	852	3817	1162
040	4000K	-		593	181	886	270	1175	358	1743	531	2296	699	2833	863	3865	1177
050	5000K	-		634	193	948	289	1259	383	1871	570	2467	751	3048	928	4165	1268
	EFFICACY			132 lm/W		132 lm/W		131 lm/W		130 lm/W		128 lm/W		127lm/W		124 lm/W	

FL175/Nx Nichia - White Light



TECHNICAL DATA

LEDs per meter	175 LEDs/m	53 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	5 mm	0.2"
Cutting step	40 mm	1.57"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

4,8 W	5 m	16'
9,6 W	2,52 m	8'
14,4 W	1,52 m	5'
19,2 W	1 m	3'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER															
		4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
820	2000K	487	148	988	301	1501	458	2017	615	-		-		-		-	
822	2200K	527	161	1069	326	1625	495	2182	665	-		-		-		-	
825	2500K	577	176	1171	357	1778	542	2388	728	-		-		-		-	
827	2700K	675	206	1369	417	2080	634	2794	852	-		-		-		-	
830	3000K	695	212	1410	430	2142	653	2876	877	-		-		-		-	
835	3500K	711	217	1442	440	2191	668	2942	897	-		-		-		-	
840	4000K	713	217	1446	441	2197	670	2951	899	-		-		-		-	
850	5000K	790	241	1574	480	2347	715	3111	948	-		-		-		-	
857	5700K	762	232	1519	463	2265	690	3002	915	-		-		-		-	
865	6500K	762	232	1519	463	2265	690	3002	915	-		-		-		-	
	EFFICACY	165 lm/W		164 lm/W		163 lm/W		162 lm/W									

CRI 90+

		POWER															
		4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
920	2000K	426	130	847	258	1261	384	1668	508	-		-		-		-	
922	2200K	461	141	917	280	1364	416	1804	550	-		-		-		-	
925	2500K	500	152	994	303	1480	451	1958	597	-		-		-		-	
T927	2700K	702	214	1399	426	2086	635	2765	842	-		-		-		-	
T930	3000K	738	225	1470	448	2192	667	2906	885	-		-		-		-	
T935	3500K	757	231	1507	459	2248	685	2980	907	-		-		-		-	
T940	4000K	767	234	1528	465	2279	694	3021	920	-		-		-		-	
T950	5000K	769	234	1533	467	2287	696	3034	924	-		-		-		-	
T957	5700K	742	226	1479	450	2207	672	2928	892	-		-		-		-	
T965	6500K	742	226	1479	450	2207	672	2928	892	-		-		-		-	
	EFFICACY	160 lm/W		160 lm/W		159 lm/W		158 lm/W									

CRI 95+

		POWER															
		4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
027	2700	491	150	979	298	1460	445	1934	589	-		-					
030	3000	502	153	1001	305	1492	455	1976	602	-		-					
035	3500	513	156	1022	312	1524	465	2019	615	-		-					
040	4000	519	158	1035	315	1544	471	2044	623	-		-					
050	5000	555	169	1107	337	1653	504	2192	668	-		-					
	EFFICACY	116 lm/W		115 lm/W		115 lm/W		114 lm/W									

Disclaimer: Technical data is subject to change without prior notice.

INDOOR
FLEXIBLE
LED STRIPS

FL28/Dx Delta- White Light




TECHNICAL DATA

LEDs per meter	28 LEDs/m	9 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	250 mm	9.84"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	33' or 164'

MAXIMUM RUN

1.2 W	29,5 m	96'
2.4 W	18 m	59'
4.8 W	10,5 m	34'
9.6 W	5,5 m	18'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.5 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
822	2200K	142	43	277	84	548	167	997	304	-		-		-		-	
827	2700K	161	49	316	96	624	190	1135	346	-		-		-		-	
830	3000K	161	49	316	96	624	190	1135	346	-		-		-		-	
835	3500K	171	52	334	102	663	202	1202	366	-		-		-		-	
840	4000K	171	52	334	102	663	202	1202	366	-		-		-		-	
850	5000K	181	55	354	108	700	213	1272	388	-		-		-		-	
857	5700K	181	55	354	108	700	213	1272	388	-		-		-		-	
865	6500K	181	55	354	108	700	213	1272	388	-		-		-		-	
	EFFICACY	151 lm/W		148 lm/W		146 lm/W		139 lm/W									

CRI 90+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.5 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
922	2200K	115	35	228	69	443	135	796	243	-		-		-		-	
T927	2700K	168	51	333	101	649	198	1176	358	-		-		-		-	
T930	3000K	170	52	336	102	658	200	1192	363	-		-		-		-	
T935	3500K	170	52	338	103	660	201	1198	365	-		-		-		-	
T940	4000K	176	54	347	106	674	205	1209	368	-		-		-		-	
T950	5000K	176	54	347	106	674	205	1226	373	-		-		-		-	
T957	5700K	170	52	338	103	660	201	1198	365	-		-		-		-	
T965	6500K	170	52	338	103	660	201	1198	365	-		-		-		-	
	EFFICACY	147 lm/W		145 lm/W		140 lm/W		134 lm/W									

FL56/Dx Delta - White Light

TECHNICAL DATA

LEDs per meter	56 LEDs/m	17 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	125 mm	4.92"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

2,4 W	18 m	59'
4,8 W	12 m	39'
9,6 W	7 m	23'
14,4 W	5,5 m	18'
18,2 W	4 m	13'



TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.6 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
822	2200K	-		284	87	555	169	1097	334	1605	489	1995	608				
827	2700K	-		323	98	632	193	1249	381	1829	557	2270	692	-		-	
830	3000K	-		323	98	632	193	1249	381	1829	557	2270	692	-		-	
835	3500K	-		343	105	671	205	1326	404	1937	590	2405	733	-		-	
840	4000K	-		343	105	671	205	1326	404	1937	590	2405	733	-		-	
850	5000K	-		362	110	708	216	1400	427	2050	625	2544	775	-		-	
857	5700K	-		362	110	708	216	1400	427	2050	625	2544	775	-		-	
865	6500K	-		362	110	708	216	1400	427	2050	625	2544	775	-		-	
	EFFICACY			151 lm/W		148 lm/W		146 lm/W		142 lm/W		140 lm/W					

CRI 90+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.6 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
922	2200K	-		230	70	457	139	886	270	1291	393	1593	486				
T927	2700K	-		336	102	666	203	1299	396	1898	578	2352	716	-		-	
T930	3000K	-		341	104	672	205	1316	401	1920	585	2385	726	-		-	
T935	3500K	-		341	104	677	206	1321	402	1937	590	2396	730	-		-	
T940	4000K	-		352	107	694	211	1349	411	1976	602	2452	747	-		-	
T950	5000K	-		352	107	694	211	1349	411	1976	602	2452	747	-		-	
T957	5700K	-		341	104	677	206	1321	402	1937	590	2396	730	-		-	
T965	6500K	-		341	104	677	206	1321	402	1937	590	2396	730	-		-	
	EFFICACY			147 lm/W		145 lm/W		141 lm/W		137 lm/W		135 lm/W					

Disclaimer: Technical data is subject to change without prior notice.

INDOOR
FLEXIBLE
LED STRIPS

FL60E/Dx Delta- White Light



TECHNICAL DATA

LEDs per meter	60 LEDs/m	19 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	100 mm	3.93"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	33' or 164'

MAXIMUM RUN

1,2 W	15 m	49'
2,4 W	10 m	32'
4,8 W	6,5m	21'
9,6 W	3,5 m	11'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.5 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
822	2200K	129	39	257	78	484	148	941	287	-		-		-		-	
827	2700K	146	45	292	89	551	168	1071	326	-		-		-		-	
830	3000K	146	45	292	89	551	168	1071	326	-		-		-		-	
835	3500K	155	47	310	94	585	178	1136	346	-		-		-		-	
840	4000K	155	47	310	94	585	178	1136	346	-		-		-		-	
850	5000K	164	50	327	100	618	188	1202	366	-		-		-		-	
857	5700K	164	50	327	100	618	188	1202	366	-		-		-		-	
865	6500K	164	50	327	100	618	188	1202	366	-		-		-		-	
	EFFICACY	137 lm/W		136 lm/W		129 lm/W		125 lm/W									

CRI 90+		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	18,2 W/m	5.5 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
922	2200K	99	30	197	60	395	120	768	234	-		-		-		-	
T927	2700K	144	44	288	88	576	175	1122	342	-		-		-		-	
T930	3000K	150	46	294	90	582	177	1140	347	-		-		-		-	
T935	3500K	150	46	294	90	582	177	1146	349	-		-		-		-	
T940	4000K	150	46	300	91	594	181	1170	356	-		-		-		-	
T950	5000K	150	46	300	91	594	181	1170	356	-		-		-		-	
T957	5700K	150	46	294	90	582	177	1146	349	-		-		-		-	
T965	6500K	150	46	294	90	582	177	1146	349	-		-		-		-	
	EFFICACY	125 lm/W		125 lm/W		124 lm/W		122 lm/W									

FL112/Dx Delta - White Light




TECHNICAL DATA

LEDs per meter	112 LEDs/m	34 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	62,5 mm	2.46"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

4,8 W	12,5 m	41'
9,6 W	8 m	26'
14,4 W	5,5 m	18'
19,2 W	4,5 m	15'
24 W	3,5 m	11'
33,6 W	3 m	10'

TECHNICAL DRAWING



LUMEN VALUES


CRI 80+		POWER															
		1,92 W/m	0.6 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	5.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	33,6 W/m	10.2 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
822	2200K	-		-		568	173	1111	339	1653	504	2194	669	2728	831	3698	1127
827	2700K	-		-		647	197	1267	386	1882	574	2499	762	3102	945	4207	1282
830	3000K	-		-		647	197	1267	386	1882	574	2499	762	3102	945	4207	1282
835	3500K	-		-		686	209	1342	409	1997	609	2652	808	3292	1003	4457	1358
840	4000K	-		-		686	209	1342	409	1997	609	2652	808	3292	1003	4457	1358
850	5000K	-		-		724	221	1416	432	2108	643	2800	853	3483	1062	4716	1437
857	5700K	-		-		724	221	1416	432	2108	643	2800	853	3483	1062	4716	1437
865	6500K	-		-		724	221	1416	432	2108	643	2800	853	3483	1062	4716	1437
	EFFICACY					151 lm/W		148 lm/W		146 lm/W		146 lm/W		145 lm/W		141 lm/W	

CRI 90+		POWER															
		1,92 W/m	0.6 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	5.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	33,6 W/m	10.2 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
922	2200K	-		-		460	140	915	279	1346	410	1772	540	2188	667	2968	905
T927	2700K	-		-		672	205	1332	406	1971	600	2598	791	3203	975	4368	1330
T930	3000K	-		-		683	208	1344	409	1993	607	2632	801	3248	989	4424	1347
T935	3500K	-		-		683	208	1355	413	2004	610	2643	805	3270	996	4457	1357
T940	4000K	-		-		705	215	1388	423	2049	624	2699	822	3337	1016	4547	1385
T950	5000K	-		-		705	215	1388	423	2049	624	2699	822	3337	1016	4547	1385
T957	5700K	-		-		683	208	1355	413	2004	610	2643	805	3270	996	4457	1357
T965	6500K	-		-		683	208	1355	413	2004	610	2643	805	3270	996	4457	1357
	EFFICACY					147 lm/W		145 lm/W		142 lm/W		141 lm/W		139 lm/W		136 lm/W	

Disclaimer: Technical data is subject to change without prior notice.

INDOOR
FLEXIBLE
LED STRIPS

FL112/Dx 48V Delta - White Light




TECHNICAL DATA

LEDs per meter	112 LEDs/m	34 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	125 mm	4.92"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	33' or 164'

MAXIMUM RUN

4,8 W	31 m	101'
9,6 W	20 m	65'
14,4 W	13,5 m	44'
19,2 W	11 m	36'
24 W	8,5 m	27'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft	24 W/m	7.3 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
822	2200K	-		-		568	173	1111	338	1653	503	2194	668	2728	831	-	
827	2700K	-		-		647	197	1267	386	1882	573	2499	761	3102	945	-	
830	3000K	-		-		647	197	1267	386	1882	573	2499	761	3102	945	-	
835	3500K	-		-		686	209	1342	409	1997	608	2652	808	3292	1002	-	
840	4000K	-		-		686	209	1342	409	1997	608	2652	808	3292	1002	-	
850	5000K	-		-		724	220	1416	431	2108	642	2800	853	3483	1061	-	
857	5700K	-		-		724	220	1416	431	2108	642	2800	853	3483	1061	-	
865	6500K	-		-		724	220	1416	431	2108	642	2800	853	3483	1061	-	
	EFFICACY					151 lm/W		148 lm/W		146 lm/W		146 lm/W		145 lm/W			

CRI 90+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft	24 W/m	7.3 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
922	2200K	-		-		460	140	915	279	1346	410	1772	540	2188	666	-	
T927	2700K	-		-		672	205	1332	406	1971	600	2598	791	3203	975	-	
T930	3000K	-		-		683	208	1344	409	1993	607	2632	801	3248	989	-	
T935	3500K	-		-		683	208	1355	413	2004	610	2643	805	3270	996	-	
T940	4000K	-		-		705	215	1388	423	2049	624	2699	822	3337	1016	-	
T950	5000K	-		-		705	215	1388	423	2049	624	2699	822	3337	1016	-	
T957	5700K	-		-		683	208	1355	413	2004	610	2643	805	3270	996	-	
T965	6500K	-		-		683	208	1355	413	2004	610	2643	805	3270	996	-	
	EFFICACY					147 lm/W		145 lm/W		142 lm/W		141 lm/W		139 lm/W			

FL120E/Dx Delta - White Light



TECHNICAL DATA

LEDs per meter	120 LEDs/m	39 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	50 mm	1.96"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	33' or 164'

MAXIMUM RUN

2,4 W	10,5 m	34'
4,8 W	6,5 m	21'
9,6 W	4 m	13'
14,4W	3 m	10'
19,2 W	2,5 m	8'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
822	2200K	-		257	78	514	157	969	295	1427	435	1882	574	-		-	
827	2700K	-		292	89	584	178	1103	336	1625	495	2143	653	-		-	
830	3000K	-		292	89	584	178	1103	336	1625	495	2143	653	-		-	
835	3500K	-		310	94	620	189	1170	357	1723	525	2273	693	-		-	
840	4000K	-		310	94	620	189	1170	357	1723	525	2273	693	-		-	
850	5000K	-		328	100	655	200	1237	377	1818	554	2404	733	-		-	
857	5700K	-		328	100	655	200	1237	377	1818	554	2404	733	-		-	
865	6500K	-		328	100	655	200	1237	377	1818	554	2404	733	-		-	
	EFFICACY			137 lm/W		136 lm/W		129 lm/W		126 lm/W		125 lm/W					

CRI 90+

		POWER															
		1,2 W/m	0.4 W/ft	2,4 W/m	0.7 W/ft	4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
922	2200K	-		198	60	395	120	790	241	1173	358	1535	468	-		-	
T927	2700K	-		288	88	576	175	1152	351	1704	519	2244	683	-		-	
T930	3000K	-		300	91	588	179	1164	354	1728	526	2280	694	-		-	
T935	3500K	-		300	91	588	179	1164	354	1740	530	2292	698	-		-	
T940	4000K	-		300	91	600	183	1188	362	1776	541	2340	713	-		-	
T950	5000K	-		300	91	600	183	1188	362	1776	541	2340	713	-		-	
T957	5700K	-		300	91	588	179	1164	354	1740	530	2292	698	-		-	
T965	6500K	-		300	91	588	179	1164	354	1740	530	2292	698	-		-	
	EFFICACY			125 lm/W		125 lm/W		124 lm/W		123 lm/W		122 lm/W					

Disclaimer: Technical data is subject to change without prior notice.

INDOOR
FLEXIBLE
LED STRIPS

FL128/Dx Delta - White Light




TECHNICAL DATA

LEDs per meter	128 LEDs/m	39 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	62,5 mm	2.46"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

4,8W	10 m	32'
7,2W	8 m	26'
9,6W	6,5 m	21'
14,4W	4 m	13'
19,2W	3 m	10'
24W	2 m	7'
33,6W	1 m	3'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER															
		1,92 W/m	0.6 W/ft	4,8 W/m	1.5 W/ft	7,2 W/m	2.2 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	33,6 W/m	10.2 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
822	2200K	-		694	211	1030	314	1337	407	1946	593	2540	773	3129	953	4271	1301
827	2700K	-		790	241	1172	357	1521	463	2214	674	2890	880	3561	1084	4861	1480
830	3000K	-		790	241	1172	357	1521	463	2214	674	2890	880	3561	1084	4861	1480
835	3500K	-		838	255	1243	378	1613	491	2348	715	3066	934	3777	1150	5155	1570
840	4000K	-		838	255	1243	378	1613	491	2348	715	3066	934	3777	1150	5155	1570
850	5000K	-		886	270	1314	400	1706	519	2482	756	3247	989	3992	1216	5450	1660
857	5700K	-		886	270	1314	400	1706	519	2482	756	3247	989	3992	1216	5450	1660
865	6500K	-		886	270	1314	400	1706	519	2482	756	3247	989	3992	1216	5450	1660
	EFFICACY			185 lm/W		183 lm/W		178 lm/W		172 lm/W		169 lm/W		166 lm/W		163 lm/W	

CRI 90+

		POWER															
		1,92 W/m	0.6 W/ft	4,8 W/m	1.5 W/ft	7,2 W/m	2.2 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	33,6 W/m	10.2 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
922	2200K	-		544	166	804	245	1063	324	1557	474	2034	619	2507	763	3364	1024
T927	2700K	-		768	234	1152	351	1523	464	2252	686	2969	904	3660	1114	4992	1520
T930	3000K	-		780	238	1164	354	1536	468	2278	694	3008	916	3712	1130	5056	1540
T935	3500K	-		780	238	1164	354	1548	471	2291	698	3020	920	3737	1138	5094	1551
T940	4000K	-		806	245	1190	362	1587	483	2342	713	3084	939	3814	1161	5196	1582
T950	5000K	-		806	245	1190	362	1587	483	2342	713	3084	939	3814	1161	5196	1582
T957	5700K	-		780	238	1164	354	1548	471	2291	698	3020	920	3737	1138	5094	1551
T965	6500K	-		780	238	1164	354	1548	471	2291	698	3020	920	3737	1138	5094	1551
	EFFICACY			168 lm/W		165 lm/W		165 lm/W		163 lm/W		161 lm/W		159 lm/W		156 lm/W	

FL175/Dx Delta - White Light

TECHNICAL DATA

LEDs per meter	175 LEDs/m	53 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	5 mm	0.2"
Cutting step	40 mm	1.57"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

4,8 W	3,52 m	12'
9,6 W	2 m	7'
14,4 W	1 m	3'
19,2 W	1 m	3'



TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER															
		4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
822	2200K	574	175	1125	343	1668	508	2212	674	-		-		-		-	
827	2700K	653	199	1280	390	1896	578	2514	766	-		-		-		-	
830	3000K	653	199	1280	390	1896	578	2514	766	-		-		-		-	
835	3500K	692	211	1358	414	2011	613	2667	813	-		-		-		-	
840	4000K	692	211	1358	414	2011	613	2667	813	-		-		-		-	
850	5000K	732	223	1436	438	2126	648	2821	860	-		-		-		-	
857	5700K	732	223	1436	438	2126	648	2821	860	-		-		-		-	
865	6500K	732	223	1436	438	2126	648	2821	860	-		-		-		-	
	EFFICACY	153 lm/W		150 lm/W		148 lm/W		147 lm/W									

CRI 90+

		POWER															
		4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
922	2200K	461	141	923	281	1375	419	1815	553	-		-		-		-	
T927	2700K	682	208	1347	410	1995	607	2642	804	-		-		-		-	
T930	3000K	682	208	1365	416	2030	618	2677	815	-		-		-		-	
T935	3500K	700	213	1365	416	2030	618	2695	821	-		-		-		-	
T940	4000K	700	213	1400	426	2082	634	2747	836	-		-		-		-	
T950	5000K	700	213	1400	426	2082	634	2747	836	-		-		-		-	
T957	5700K	700	213	1365	416	2030	618	2695	821	-		-		-		-	
T965	6500K	700	213	1365	416	2030	618	2695	821	-		-		-		-	
	EFFICACY	146 lm/W		146 lm/W		145 lm/W		143 lm/W									

Disclaimer: Technical data is subject to change without prior notice.




TW56/Nx Nichia - Tunable White Light

TECHNICAL DATA


LEDs per meter	56 warm + 56 cold LEDs/m	17 warm + 17 cold LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	10 mm	0.39"
Cutting step	125 mm	4.92"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

9,6 W	8 m	26'
19,2 W	4,5 m	15'
33,4 W	3 m	10'



TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER											
		9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
820/865	2000-6500K	1255	382	-		2491	759	-		-		4219	1285
825/857	2500-5700K	1347	410	-		2677	815	-		-		4534	1381
827/857	2700-5700K	1448	441	-		2880	877	-		-		4877	1485
827/850	2700-5000K	1475	449			2934	893					4969	1513
827/865	2700-6500K	1448	441	-		2880	877	-		-		4877	1485
	EFFICACY	158 lm/W				157 lm/W						153 lm/W	

CRI 90+

		POWER											
		9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
920/T965	2000-6500K	1084	330	-		2124	647	-		-		3565	1086
925/T957	2500-5700K	1161	354	-		2275	693	-		-		3817	1162
T927/T950	2700-5000K	1272	387	-		2498	761	-		-		4194	1277
	EFFICACY	146 lm/W				146 lm/W						141 lm/W	

INDOOR
FLEXIBLE
LED STRIPS

TW70/Nx Nichia - Tunable White Light




TECHNICAL DATA

LEDs per meter	70 warm + 70 cold LEDs/m	21 warm + 21 cold LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	10 mm	0.39"
Cutting step	100 mm	3.94"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

9,6 W	9 m	29'
19,2 W	5,5 m	18'
33,6 W	3 m	10'
45,6 W	2 m	7'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER											
		9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	45,6 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
820/865	2000-6500K	1254	382	-		2503	762	-		-		4301	1310	5723	1743
825/857	2500-5700K	1346	410	-		2690	819	-		-		4623	1408	6150	1873
827/857	2700-5700K	1446	440	-		2893	881	-		-		4974	1515	6615	2014
827/850	2700-5000K	1473	449			2947	897					5067	1543	6739	2052
827/865	2700-6500K	1446	440	-		2893	881	-		-		4974	1515	6615	2014
	EFFICACY	158 lm/W				158 lm/W						155 lm/W		152 lm/W	

CRI 90+

		POWER													
		9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	45,6 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
920/T965	2000-6500K	1231	375	-		2433	741	-		-		4158	1266	5529	1684
925/T957	2500-5700K	1239	377	-		2455	748	-		-		4185	1274	5539	1687
T927T/950	2700-5000K	1274	388	-		2519	767	-		-		4289	1306	5680	1730
	EFFICACY	146 lm/W				147 lm/W						144 lm/W		140 lm/W	

Disclaimer: Technical data is subject to change without prior notice.

TW56/Dx Delta - Tunable White Light




TECHNICAL DATA

LEDs per meter	56 warm + 56 cold LEDs/m	17 warm + 17 cold LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	10 mm	0.39"
Cutting step	125 mm	4.92"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

9,6 W	6,5 m	25'
19,2 W	3,5 m	13'
33,4 W	2,5 m	9'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER													
		9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
827/840	2700-4000K	1271	387	-		2488	758	-		-		3239	986	-	
827/850	2700-5700K	1348	410	-		2637	803	-		-		4457	1357	-	
827/857	2700-5700K	1348	410	-		2637	803	-		-		4457	1357	-	
827/865	2700-6500K	1348	410	-		2637	803	-		-		4457	1357	-	
	EFFICACY	148 lm/W				146 lm/W						139 lm/W			

CRI 90+tri

		POWER													
		9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
T927/T940	2700-4000K	1153	351	-		2229	679	-		-		3713	1131	-	
T927/T950	2700-5700K	1221	372	-		2359	718	-		-		3933	1198	-	
T927/T957	2700-5700K	1187	361	-		2293	698	-		-		3827	1165	-	
T927/T965	2700-6500K	1221	372	-		2359	718	-		-		3933	1198	-	
	EFFICACY	143 lm/W				140 lm/W						134 lm/W			

INDOOR
FLEXIBLE
LED STRIPS

TW70/Dx Delta - Tunable White Light




TECHNICAL DATA

LEDs per meter	70 warm + 70 cold LEDs/m	21 warm + 21 cold LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	10 mm	0.39"
Cutting step	100 mm	3.94"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

9,6 W	8 m	31'
19,2 W	4,5 m	17'
33,6 W	2,5 m	9'
45,6 W	1,5 m	6'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+


		POWER											
		9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
827/840	2700-4000K	1270	387	-		2506	763	-		-		3592	1094	5675	1728
827/850	2700-5700K	1347	410	-		2659	810	-		-		4551	1386	6018	1832
827/857	2700-5700K	1347	410	-		2659	810	-		-		4551	1386	6018	1832
827/865	2700-6500K	1347	410	-		2659	810	-		-		4551	1386	6018	1832
	EFFICACY	148 lm/W				146 lm/W						143 lm/W		140 lm/W	

CRI 90+tri

		POWER													
		9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
T927/T940	2700-4000K	1160	353	-		2256	687	-		-		3818	1163	5020	1529
T927/T950	2700-5700K	1228	374	-		2387	727	-		-		4042	1231	5318	1619
T927/T957	2700-5700K	1194	364	-		2321	707	-		-		3929	1196	5168	1574
T927/T965	2700-6500K	1228	374	-		2387	727	-		-		4042	1231	5318	1619
	EFFICACY	143 lm/W				141 lm/W						137 lm/W		133 lm/W	

Disclaimer: Technical data is subject to change without prior notice.

TW2-112/Nx - Tunable Dual White Light



TECHNICAL DATA

LEDs per meter	112 dual white and cold white LEDs/m	34 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	8 mm	0.32"
Cutting step	62,5 mm	2.46"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

9W	10,5 m	34'
19W	7 m	23'
33W	4,5 m	15'
48W	3,5 m	11'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER											
		9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
827/865	2700-6500K	1343	409	-		2665	812	-		-		4524	1379	6462	1970
	EFFICACY	140 lm/W				139 lm/W						135 lm/W		135 lm/W	



RGB48/Nx Nichia - RGB Light

TECHNICAL DATA

LEDs per meter	48 LEDs/M	15 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	10 mm	0.39"
Cutting step	125 mm	4.92"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

7,2 W	9 m	29'
11,52 W	6,5 m	21'



TECHNICAL DRAWING



LUMEN VALUES

RGB

	POWER													
	7,2 W/m	2,2 W/ft	11,52 W/m	3,5 W/ft	17,3 W/m	5,3 W/ft	24 W/m	7,3 W/ft	28,8 W/m	8,8 W/ft	33,4 W/m	10,2 W/ft	48 W/m	14,6 W/ft
COLOR	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
RED	65	20	104	32	-		-		-		-		-	
GREEN	208	63	307	93	-		-		-		-		-	
BLUE	43	13	69	21	-		-		-		-		-	
TOTAL RGB LUMINOUS FLUX	316	96	480	146	-		-		-		-		-	
EFFICACY	44 lm/W		42 lm/W											

INDOOR
FLEXIBLE
LED STRIPS

RGB96/Nx Nichia - RGB Light



TECHNICAL DATA

LEDs per meter	96 LEDs/M	29 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	10 mm	0.39"
Cutting step	62.5 mm	2.46"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

11,52 W	9,5 m	31'
14,4 W	8 m	26'
23 W	5,5 m	18'

TECHNICAL DRAWING



LUMEN VALUES

RGB

		POWER												
		11,52 W/m	3.5 W/ft	14,4 W/m	4.4 W/ft	17,3 W/m	5.3 W/ft	23 W/m	7 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
COLOR		lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
RED		104	32	130	40	-		209	64	-		-		-	
GREEN		306	93	383	117	-		614	187	-		-		-	
BLUE		69	21	87	26	-		139	42	-		-		-	
TOTAL RGB LUMINOUS FLUX		479	146	600	183	-		962	293	-		-		-	
	EFFICACY	42 lm/W		42 lm/W				42 lm/W							

RGBW48/Nx Nichia -RGBW Light

TECHNICAL DATA


LEDs per meter	48 RGB + 48 white LEDs/m	15 RGB + 15 white LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	10 mm	0.39"
Cutting step	125 mm	4.92"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

9,6 W	8 m	26'
14,4 W	7 m	23'
19,2 W	5,5 m	18'
24 W	5 m	16'



TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER													
		4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
820	2000K	-		210	64	319	97	693	211	1116	340						
822	2200K	-		227	69	345	105	750	228	1208	368	-		-		-	
825	2500K	-		249	76	378	115	821	250	1322	403	-		-		-	
827	2700K	-		291	89	442	135	960	292	1546	471	-		-		-	
830	3000K	-		300	91	455	139	989	301	1592	485	-		-		-	
835	3500K	-		306	93	466	142	1012	308	1629	496	-		-		-	
840	4000K	-		307	93	467	142	1014	309	1633	497	-		-		-	
850	5000K	-		338	103	505	154	1060	323	1692	515	-		-		-	
857	5700K	-		326	99	487	148	1023	312	1633	497	-		-		-	
865	6500K	-		326	99	487	148	1023	312	1633	497	-		-		-	
	EFFICACY			141 lm/W		140 lm/W		138 lm/W		136 lm/W							

CRI 90+

		POWER													
		4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
920	2000K	-		182	55	271	83	567	173	898	273	-		-		-	
922	2200K	-		197	60	294	90	613	187	971	296	-		-		-	
925	2500K	-		213	65	318	97	665	202	1053	321	-		-		-	
T927	2700K	-		300	91	448	136	942	287	1504	458	-		-		-	
T930	3000K	-		315	96	471	143	990	301	1580	481	-		-		-	
T935	3500K	-		323	98	483	147	1015	309	1621	494	-		-		-	
T940	4000K	-		328	100	490	149	1029	313	1643	500	-		-		-	
T950	5000K	-		329	100	491	150	1035	315	1654	504	-		-		-	
T957	5700K	-		317	97	474	144	998	304	1595	486	-		-		-	
T965	6500K	-		317	97	474	144	998	304	1595	486	-		-		-	
	EFFICACY			137 lm/W		136 lm/W		135 lm/W		133 lm/W							

CRI 95+

		POWER													
		7,2 W/m	2.2 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
027	2700K	-		210	64	314	96	658	200	1042	317	-					
030	3000K	-		215	65	321	98	672	205	1065	324	-					
035	3500K	-		219	67	328	100	687	209	1088	331	-					
040	4000K	-		222	68	332	101	695	212	1102	336	-					
050	5000K	-		237	72	355	108	746	227	1185	361	-					
	EFFICACY			99 lm/W		99 lm/W		97 lm/W		95 lm/W							

INDOOR
FLEXIBLE
LED STRIPS

RGBW48/Dx Delta -RGBW Light




TECHNICAL DATA

LEDs per meter	48 RGB + 48 white LEDs/m	15 RGB + 15 white LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC)	
Tape width	10 mm	0.39"
Cutting step	125 mm	4.92"
Tc temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	120°	
Dimmable	YES	
Strip length per reel	10 m or 50 m	32' or 164'

MAXIMUM RUN

9,6 W	8 m	26'
14,4 W	7 m	22'
19,2 W	5,5 m	18'
24 W	5 m	16'

TECHNICAL DRAWING



LUMEN VALUES

CRI 80+

		POWER															
		7,2 W/m	2.2 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
827	2700K	-		270	82	401	122	854	260	1327	404	-		-		-	
830	3000K	-		283	86	419	128	888	270	1376	419	-		-		-	
835	3500K	-		292	89	433	132	918	280	1424	434	-		-		-	
840	4000K	-		289	88	432	132	926	282	1444	440	-		-		-	
850	5000K	-		298	91	441	134	933	284	1446	440	-		-		-	
857	5700K	-		294	90	436	133	926	282	1438	438	-		-		-	
865	6500K	-		287	87	428	130	917	279	1431	436	-		-		-	
	EFFICACY			124 lm/W		123 lm/W		121 lm/W		116 lm/W							

CRI 90+tri

		POWER															
		7,2 W/m	2.2 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft	33,4 W/m	10.2 W/ft	48 W/m	14.6 W/ft
SPECTRUM	KELVINS	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft	lm/m	lm/ft
T927	2700K	-		288	88	432	132	897	273	1425	434	-		-		-	
T930	3000K	-		292	89	436	133	912	278	1444	440	-		-		-	
T935	3500K	-		292	89	436	133	916	279	1454	443	-		-		-	
T940	4000K	-		302	92	446	136	936	285	1483	452	-		-		-	
T950	5000K	-		302	92	446	136	936	285	1483	452	-		-		-	
T957	5700K	-		292	89	436	133	916	279	1454	443	-		-		-	
T965	6500K	-		292	89	436	133	916	279	1454	443	-		-		-	
	EFFICACY			126 lm/W		124 Lm/W		122 lm/W		119 lm/W							

ACCESSORIES



CONNECTORS

CON-ON-FL0-2	2pin, transparent, indoor
CON-ON-FL1-2	2pin, non-transparent, indoor
CON-ON-FL2-2	2pin + wire, indoor
CON-ON-FL3-2	2pin wire extended, indoor




WIRING

WIR.IR.WE2×20.00003	2 core Holectron cable
WIR.IR.WE3×20.00002	3 core Holectron cable
WIR.IR.WE4×20.00002	4 core Holectron cable
WIR.IR.WE5×20.00002	5 core Holectron cable

MINIA
MICROPRISM & OPAL






Minia S IND OPL PWE W16 822 L1960 FO EU / PH


ORDER CODE EXAMPLE


Minia Pendant & Surface











TECHNICAL DETAILS


Housing	Powder coated extruded aluminum	
LEDs	Nichia 3-step MacAdam	
LED lumen maintenance	L90B10 > 60.000 h	
Electrical	220 -240 VAC, Integrated driver	
	110-277 VAC, Integrated driver (for 0-10V)	
Suspension rope (for pendant)	Silver coloured, lenght - 2 m	6.56’
Lead cable (for pendant)	Transparent, lenght - 2 m	6.56’

SELECTABLE FEATURES

Light diffuser	Microprism, Opal
Housing color	Black, White, Grey, Custom
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output (Direct / Indirect)	W16/W8 - Standart output (~24W/m 7.2W/ft)
	W23/W12- High output (~35W/m 10.5W/ft)
Light output (Direct Only)	W16 - Standart output (~16W/m 5W/ft)
	W23- High output (~23W/m 7W/ft)
Efficacy	Microprism 109-112 Lm/W, Opal 105-110 Lm/W
Length, mm, ft	L560, L840, L1120, L1400, L1680, L1960, L2240, L2520, L2800, L3080
	1.8ft, 2.8ft, 3.7ft, 4.6ft, 5.5ft, 6.4ft, 7.3ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V


SEGMENT TYPE

INDIVIDUAL LUMINAIRE



Luminaire - IND
Endcaps at both ends

CONTINUOUS LINE MODULES



Start module - STA
Endcap at the start


Middle module - MID
No endcaps


End module - END
Endcap at the end

Minia Recessed









TECHNICAL DETAILS

Housing	Powder coated extruded aluminum
LEDs	Nichia 3-step MacAdam
LED lumen maintenance	L90B10 > 60.000 h
Electrical	220 -240 VAC, Driver included
	110-277 VAC, Driver included

SELECTABLE FEATURES

Light diffuser	Microprism, Opal
Housing color	Black, White, Grey, Custom
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output	W16 - Standart output (~16W/m 5W/ft)
	W23- High output (~23W/m 7W/ft)
Efficacy	Microprism 109-112 Lm/W, Opal 105-110 Lm/W
Length, mm, ft	L560, L840, L1120, L1400, L1680, L1960, L2240, L2520, L2800, L3080
	1.8ft, 2.8ft, 3.7ft, 4.6ft, 5.5ft, 6.4ft, 7.3ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V


SEGMENT TYPE

INDIVIDUAL LUMINAIRE




Luminaire - IND
Endcaps at both ends


CONTINUOUS LINE MODULES



Start module - STA
Endcap at the start



Middle module - MID
No endcaps





End module - END
Endcap at the end

Minia Wall









TECHNICAL DETAILS


Housing	Powder coated extruded aluminum
LEDs	Nichia 3-step MacAdam
LED lumen maintenance	L90B10 > 60.000 h
Electrical	220 -240 VAC, Integrated driver
	110-277 VAC, Integrated driver (for 0-10V)

SELECTABLE FEATURES

Light diffuser	Microprism, Opal
Housing color	Black, White, Grey, Custom
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output (Direct / Indirect)	W16/W16 - Standart output (~32W/m 9.7W/ft)
Light output (Direct Only)	W16 - Standart output (~16W/m 5W/ft)
Efficacy	Microprism 109-112 Lm/W, Opal 105-110 Lm/W
Length, mm, ft	L560, L840, L1120, L1400, L1680, L1960, L2240, L2520, L2800, L3080
	1.8ft, 2.8ft, 3.7ft, 4.6ft, 5.5ft, 6.4ft, 7.3ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V


SEGMENT TYPE

INDIVIDUAL LUMINAIRE



Luminaire - IND
Endcaps at both ends

CONTINUOUS LINE MODULES




Start module - STA
Endcap at the start

Middle module - MID
No endcaps

End module - END
Endcap at the end

MiniaX





MiniaX P IND PWE.PWE B.PWE B560 D080C W23/W23 950/P30 L1960 DA

ORDER CODE EXAMPLE

Color combinations

MiniaX luminaires housings come in standard white, black or grey colors which can be combined to various baffle colors. However, this MiniaX luminaire can be customized to any RAL color.



Black body, white blackout, white mat baffles



Grey body, white blackout, white mat baffles



White body, white blackout, white mat baffles



White body, white blackout, black mat baffles



Black body, black blackout, silver metalized baffles



Grey body, grey blackout, silver metalized baffles



White body, white blackout, silver metalized baffles



White body, white blackout, black metalized baffles



Black body, black blackout, black mat baffles



Grey body, black blackout, black mat baffles



White body, black blackout, black mat baffles



Custom color on request



Black body, black blackout, black metalized baffles



Grey body, black blackout, black metalized baffles




White body, black blackout, black metalized baffles

Lengths

LENGTHS OF INDIVIDUAL SEGMENT


With 280 mm blackout

840 mm | 2.8 ft
1400 mm | 4.6 ft
1960 mm | 6.4 ft
2520 mm | 8.3 ft
3080 mm | 10 ft



With 560 mm blackout

1120 mm | 3.7 ft
1960 mm | 6.4 ft
2800 mm | 9.2 ft



LENGTHS OF CONTINUOUS LINE SEGMENTS


With 280 mm blackout

1120 mm | 3.7 ft
1680 mm | 5.5 ft
2240 mm | 7.3 ft
2800 mm | 9.2 ft




With 560 mm blackout

840 mm | 2.8 ft
1680 mm | 5.5 ft
2520 mm | 8.3 ft



FOR INDIVIDUAL AND CONTINUOUS LINE MODULES (NO BLACKOUT)

280 mm | 0.91 ft
560 mm | 1.8 ft
840 mm | 2.8 ft
1120 mm | 3.7 ft
1400 mm | 4.6 ft
1680 mm | 5.5 ft
1960 mm | 6.4 ft
2240 mm | 7.3 ft
2520 mm | 8.3 ft
2800 mm | 9.2 ft
3080 mm | 10 .1 ft




MiniaX Pendant & Surface






BAFFLE







TECHNICAL DETAILS


Housing	Powder coated extruded aluminum	
LEDs	Nichia 3-step MacAdam	
LED lumen maintenance	L90B10 > 60.000 h	
Electrical	220 -240 VAC, Integrated driver	
	110-277 VAC, Integrated driver (for 0-10V)	
Suspension rope (for pendant)	Silver coloured, lenght - 2 m	6.56’
Lead cable (for pendant)	Transparent, lenght - 2 m	6.56’

SELECTABLE FEATURES

Light diffuser	Shades
Housing color	Black, White, Grey, Custom
Baffle color	Black, White, Black Metalized, Silver Metalized
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output (Direct / Indirect)	W16/W8 - Standart output (~24W/m 7.2W/ft)
	W23/W12- High output (~35W/m 10.5W/ft)
Light output (Direct Only)	W16 - Standart output (~16W/m 5W/ft)
	W23- High output (~23W/m 7W/ft)
Efficacy	Up to 146 lm/W luminaire
Length, mm, ft	L280, L560, L840, L1120, L1400, L1680, L1960, L2240, L2520, L2800, L3080
	0.9Ft, 1.8ft, 2.8ft, 3.7ft, 4.6ft, 5.5ft, 6.4ft, 7.3ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V


SEGMENT TYPE

INDIVIDUAL LUMINAIRE



Luminaire - IND
Endcaps at both ends

CONTINUOUS LINE MODULES



Start module - STA
Endcap at the start

Middle module - MID
No endcaps

End module - END
Endcap at the end


MiniaX Recessed






BAFFLE







TECHNICAL DETAILS

Housing	Powder coated extruded aluminum
LEDs	Nichia 3-step MacAdam
LED lumen maintenance	L90B10 > 60.000 h
Electrical	220 -240 VAC, Driver included
	110-277 VAC, Driver included

SELECTABLE FEATURES

Light diffuser	Shades
Housing color	Black, White, Grey, Custom
Baffle color	Black, White, Black Metalized, Silver Metalized
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output	W16 - Standart output (~16W/m 5W/ft)
	W23- High output (~23W/m 7W/ft)
Efficacy	Up to 146 Lm/W luminaire
Length, mm, ft	L280, L560, L840, L1120, L1400, L1680, L1960, L2240, L2520, L2800, L3080
	0.9ft, 1.8ft, 2.8ft, 3.7ft, 4.6ft, 5.5ft, 6.4ft, 7.3ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V


SEGMENT TYPE

INDIVIDUAL LUMINAIRE



Luminaire - IND
Endcaps at both ends

CONTINUOUS LINE MODULES



Start module - STA
Endcap at the start



Middle module - MID
No endcaps



End module - END
Endcap at the end

MiniaX Wall







BAFFLE



50˚ 80˚



DIRECT / INDIRECT DIRECT



TECHNICAL DETAILS


Housing	Powder coated extruded aluminum
LEDs	Nichia 3-step MacAdam
LED lumen maintenance	L90B10 > 60.000 h
Electrical	220 -240 VAC, Integrated driver
	110-277 VAC, Integrated driver (for 0-10V)

SELECTABLE FEATURES

Light diffuser	Shades
Housing color	Black, White, Grey, Custom
Baffle color	Black, White, Black Metalized, Silver Metalized
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output (Direct / Indirect)	W16/W16 - Standart output (~32W/m 9.7W/ft)
Light output (Direct Only)	W16 - Standart output (~16W/m 5W/ft)
Efficacy	Up to 157 Lm/W luminaire
Length, mm, ft	L280, L560, L840, L1120, L1400, L1680, L1960, L2240, L2520, L2800, L3080
	0.9ft, 1.8ft, 2.8ft, 3.7ft, 4.6ft, 5.5ft, 6.4ft, 7.3ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V


SEGMENT TYPE

INDIVIDUAL LUMINAIRE



Luminaire - IND
Endcaps at both ends

CONTINUOUS LINE MODULES



Start module - STA
Endcap at the start

Middle module - MID
No endcaps

End module - END
Endcap at the end


MiniaX Wallwash Pendant & Surface






BAFFLE







TECHNICAL DETAILS


Housing	Powder coated extruded aluminum	
LEDs	Nichia 3-step MacAdam	
LED lumen maintenance	L90B10 > 60.000 h	
Electrical	220 -240 VAC, Integrated driver	
	110-277 VAC, Integrated driver (for 0-10V)	
Suspension rope (for pendant)	Silver coloured, lenght - 2 m	6.56'
Lead cable (for pendant)	Transparent, lenght - 2 m	6.56'

SELECTABLE FEATURES

Light diffuser	Shades
Housing color	Black, White, Grey, Custom
Baffle color	Black, White, Black Metalized, Silver Metalized
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output (Direct / Indirect)	W16/W8 - Standart output (~24W/m 7.2W/ft)
	W23/W12- High output (~35W/m 10.5W/ft)
Light output (Direct Only)	W16 - Standart output (~16W/m 5W/ft)
	W23- High output (~23W/m 7W/ft)
Efficacy	Up to 146 Lm/W luminaire
Length, mm, ft	L280, L560, L840, L1120, L1400, L1680, L1960, L2240, L2520, L2800, L3080
	0.9ft, 1.8ft, 2.8ft, 3.7ft, 4.6ft, 5.5ft, 6.4ft, 7.3ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V


SEGMENT TYPE

INDIVIDUAL LUMINAIRE



Luminaire - IND
Endcaps at both ends

CONTINUOUS LINE MODULES



Start module - STA
Endcap at the start

Middle module - MID
No endcaps


End module - END
Endcap at the end


MiniaX Wallwash Recessed



BAFFLE









TECHNICAL DETAILS

Housing	Powder coated extruded aluminum
LEDs	Nichia 3-step MacAdam
LED lumen maintenance	L90B10 > 60.000 h
Electrical	220 -240 VAC, Driver included
	110-277 VAC, Driver included

SELECTABLE FEATURES

Light diffuser	Shades
Housing color	Black, White, Grey, Custom
Baffle color	Black, White, Black Metalized, Silver Metalized
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output	W16 - Standart output (~16W/m 5W/ft)
	W23- High output (~23W/m 7W/ft)
Efficacy	Up to 146 Lm/W luminaire
Length, mm, ft	L280, L560, L840, L1120, L1400, L1680, L1960, L2240, L2520, L2800, L3080
	0.9ft, 1.8ft, 2.8ft, 3.7ft, 4.6ft, 5.5ft, 6.4ft, 7.3ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V


SEGMENT TYPE

INDIVIDUAL LUMINAIRE



Luminaire - IND
Endcaps at both ends

CONTINUOUS LINE MODULES



Start module - STA
Endcap at the start



Middle module - MID
No endcaps




End module - END
Endcap at the end

MINIA MESH



Set the mood and elevate your space with Minia Mesh and Shapes luminaires. Their captivating geometric designs – triangles, squares, and hexagons – diffuse soft, uniform light, creating a serene atmosphere. Perfect for any setting, from classic to modern, Minia Mesh and Shape luminaires are ideal for retail stores, offices, restaurants, and homes alike.





Minia.Mesh P MID PWE.XXX B.PWE B000 OPL W16 950 L1960 DA EU / PH


ORDER CODE EXAMPLE



Minia Mesh
Pendant & Surface








TECHNICAL DETAILS


Housing	Powder coated extruded aluminum	
LEDs	Nichia 3-step MacAdam	
LED lumen maintenance	L90B10 > 60.000 h	
Electrical	230 VAC 50 Hz, integrated driver	
Suspension rope (for pendant)	Silver coloured, lenght - 2 m	6.56'
Lead cable (for pendant)	Transparent, lenght - 2 m	6.56'

SELECTABLE FEATURES

Light diffuser	Microprism, Opal, Baffle
Housing color	Black, White, Grey, Custom
Baffle color	Black, White, Black Metalized, Silver Metalized
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output (Direct / Indirect)	W16/W8 - Standart output (~24W/m 7.2W/ft)
	W23/W12- High output (~35W/m 10.5W/ft)
Light output (Direct Only)	W16 - Standart output (~16W/m 5W/ft)
	W23- High output (~23W/m 7W/ft)
Efficacy	Up to 146 lm/W luminaire
Length, mm, ft	L840, L1120, L1400, L1680, L1960, L2240, L2520, L2800, L3080
	2.8ft, 3.7ft, 4.6ft, 5.5ft, 6.4ft, 7.3ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V

JOINTS






Only one mains feed cable to supply the whole mesh system. Each module passes mains power to all connected modules through its own integrated through-wiring system.


Minia Mesh
Pendant & Surface

MESH FORMS IDEAS


HEXAGONS




LINES & SQUARES




MIXED





SQUARE MINIA MESH SYSTEM DIMENSIONS

Length, mm	L, mm	L1, mm
840	929	1812
1120	1209	2372
1400	1489	2932
1680	1769	3492
1960	2049	4052
2240	2329	4612
2520	2906	5172
2800	2889	5732
3080	3169	6292




HEXAGON MINIA MESH SYSTEM DIMENSIONS


Length, mm	L1, mm	L2, mm	l, mm	L, mm	Ams, mm
840	1544	3043	914	1760	3058
1120	2029	4013	1194	2320	4038
1400	2514	4983	1474	2880	5018
1680	2999	5953	1754	3440	5998
1960	3484	6923	2034	4000	6978
2240	3969	7893	2314	4560	7958
2520	4454	8863	2594	5120	8938
2800	4939	9833	2874	5680	9918
3080	5424	10803	3154	6240	10898

MINIA SHAPE
PENDANT & SURFACE









TECHNICAL DETAILS

Housing	Powder coated extruded aluminum	
LEDs	Nichia 3-step MacAdam	
LED lumen maintenance	L90B10 > 60.000 h	
Electrical	220 -240 VAC, Integrated driver	
	110-277 VAC, Integrated driver (for 0-10V)	
Suspension rope (for pendant)	Silver coloured, lenght - 2 m	6.56’
Lead cable (for pendant)	Transparent, lenght - 2 m	6.56’

SELECTABLE FEATURES


Light diffuser	Microprism, Opal
Light diffuser color	White
Housing color	Black, White, Grey, Custom
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output (Direct / Indirect)	W16/W8 - Standart output (~24W/m 7.2W/ft)
	W23/W12- High output (~35W/m 10.5W/ft)
Light output (Direct Only)	W16 - Standart output (~16W/m 5W/ft)
	W23- High output (~23W/m 7W/ft)
Efficacy	Microprism 109-112 Lm/W, Opal 105-110 Lm/W
Length, mm, ft	L560, L840, L1120, L1400, L1680, L1960, L2240, L2520, L2800, L3080
	1.8ft, 2.8ft, 3.7ft, 4.6ft, 5.5ft, 6.4ft, 7.3ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V

Minia Shape
Pendant & Surface




SIZES AND DIMENSIONS

Possibility to choose from 3 geometric shapes which can be in any size from 560mm to 3080mm



HEXAGON

Length, mm	O, mm	O1, mm	O2, mm	L, mm
840	867	1734	1501.69	1671.04
1400	1427	2854	2417.11	2791.04
1400	1427	2854	2417.11	2791.04
1680	1707	3414	2956.61	3351.04
1960	1987	3974	3441.59	3911.04
2240	2267	4534	3926.56	4471.04
2520	2547	5094	4411.53	5031.04
2800	2827	5654	4896.51	5591.04
3080	3107	6214	5381.48	6151.04



SQUARE

Length, mm	O, mm	I, mm
840	885	832.5
1120	1165	1112.5
1400	1445	1392.5
1680	1725	1672.5
1960	2005	1952.5
2240	2285	2232.5
2520	2565	2512.5
2800	2845	2792.5
3080	3125	3072.5




TRIANGLE

Length, mm	L, mm	I, mm
840	916	819.72
1120	1196	1099.72
1400	1476	1379.72
1680	1756	1659.72
1960	2036	1939.72
2240	2316	2219.72
2520	2596	2499.72
2800	2876	2779.72
3080	3156	3059.72

QUADRO





Quadro_R 8W 50D.CLR SW Nx T930 PBK BBK.GLO XX / PH

ORDER CODE EXAMPLE

QUADRO SURFACE





BLACK MATT BAFFLE




BLACK GLOSS BAFFLE



50° CLEAR



50° OPAL




80° CLEAR



80° OPAL



DIRECT



TECHNICAL DETAILS

Housing	Powder coated aluminum
LEDs	Nichia 3-step MacAdam
LED lumen maintenance	L90B10 > 60.000 h
Electrical	220 -240 VAC, External driver

SELECTABLE FEATURES

Light diffuser	Shades
Housing color	Black, White, Custom
Baffle color	Black matt, Black gloss
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K
Power	Up to 8W
Efficacy	Up to 138 lm/W luminaire
Control	Fixed output, DALI

QUADRO RECESSED





BLACK MATT BAFFLE



BLACK GLOSS BAFFLE



50° CLEAR



50° OPAL




80° CLEAR




80° OPAL



DIRECT





TECHNICAL DETAILS


Housing	Powder coated aluminum
LEDs	Nichia 3-step MacAdam
LED lumen maintenance	L90B10 > 60.000 h
Electrical	220 -240 VAC, External driver

SELECTABLE FEATURES

Light diffuser	Shades
Housing color	Black, White, Custom
Baffle color	Black matt, Black gloss
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K
Power	Up to 8W
Efficacy	Up to 138 lm/W luminaire
Control	Fixed output, DALI

VENTA INDOOR







A130x.HU IBC PWE 30D.UGR-V.CL L1010(3'4") / FL112/Nx G5 33W T930 L1000 HR J1x L0200 STD PH

ORDER CODE EXAMPLE


Surface holders



PRG.A130x.F04




PRG.A130x.F05




PRG.A130x.F06.RGY

Angle holders


Colors – white, grey, black



PRG.A130x.F01




PRG.A130x.F02




PRG.A130x.F03

MICROPRISM MICROPRISM+UGR.V




LENS LENS+UGR.V LENS+UGR.H



14° 14° 14°

30° 30° 30°





TECHNICAL DETAILS

Housing	Powder coated extruded aluminum
LEDs	Nichia 3-step MacAdam
LED lumen maintenance	L90B10 > 60.000 h
Input Voltage	24 VDC
Fix rotation angle	Up to 200°
Lead cable (for pendant)	Transparent, lenght - 2 m 6.56’

SELECTABLE FEATURES

Light diffuser	Lense 30D, Lense 30D + UGR, Lense 14D, Lense 14D + UGR, Microprism, Opal
Housing color	Black, White, Grey, Custom
CRI	Ra80+, Ra90+, Ra95+
CCT	2000K, 2200K, 2500K, 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K, 2700-6500K (tunable white), RGB, 2700-6500K RGBW
Max. Wattage	Up to 33W/m (10W/ft)
Light output ratio (LOR)	Microprism 81%, 14D - 78%, 30D - 84%
Length, mm, ft	Minimum length 500mm (19.68in) - maximum length - 3000mm (118.11in)

SEGMENT TYPE

INDIVIDUAL LUMINAIRE

Luminaire - IND
Endcaps at both ends


CONTINUOUS LINE MODULES

Start module - STA
Endcap at the start

Middle module - MID
No endcaps

End module - END
Endcap at the end

NEMAN HONEYCOMB




Neman P IND HCB PWE W17 T930 L0560 DA EU / PH

ORDER CODE EXAMPLE


Neman Pendant & Surface






HONEYCOMB







TECHNICAL DETAILS

Housing	Powder coated extruded aluminum	
LEDs	Nichia 3-step MacAdam	
LED lumen maintenance	L90B10 > 60.000 h	
Electrical	220 -240 VAC, Integrated driver	
Suspension rope (for pendant)	Silver coloured, lenght - 2 m	6.56’
Lead cable (for pendant)	Transparent, lenght - 2 m	6.56’

SELECTABLE FEATURES

Honeycomb light diffuser color	Black, Gold, Silver
Housing color	Black, White, Grey, Custom
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output (Direct / Indirect)	W17/W8 - Standart output
	W27/W12- High output
Light output (Direct Only)	W17 - Standart output
	W27 - High output
Efficacy	Up to 112 Lm/W luminaire
Length, mm, ft	L280, L560, L840, L1120, L1400, L1680, L1960, L2240, L2520, L2800, L3080
	0.9ft, 1.8ft, 2.8ft, 3.7ft, 4.6ft, 5.5ft, 6.4ft, 7.3ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V

SEGMENT TYPE

INDIVIDUAL LUMINAIRE



Luminaire - IND
Endcaps at both ends

CONTINUOUS LINE MODULES




Start module - STA
Endcap at the start

Middle module - MID
No endcaps

End module - END
Endcap at the end


Neman Recessed



HONEYCOMB







TECHNICAL DETAILS

Housing	Powder coated extruded aluminum
LEDs	Nichia 3-step MacAdam
LED lumen maintenance	L90B10 > 60.000 h
Electrical	220 -240 VAC, Driver included

SELECTABLE FEATURES

Honeycomb light diffuser color	Black, Silver, Gold
Housing color	Black, White, Grey, Custom
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output (Direct Only)	W17 - Standart output
	W27- High output
Efficacy	Up to 84 lm/W
Length, mm, ft	L560, L840, L1120, L1400, L1680, L1960, L2240, L2520, L2800, L3080
	1.10ft, 2.9ft, 3.8ft, 4.7ft, 5.6ft, 6.4ft, 7.4ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V
Sensors - daylight/presence	DALI, DIM, On/Off


SEGMENT TYPE

INDIVIDUAL LUMINAIRE




Luminaire - IND
Endcaps at both ends


CONTINUOUS LINE MODULES



Start module - STA
Endcap at the start




Middle module - MID
No endcaps



End module - END
Endcap at the end


Neman Trimless



HONEYCOMB







TECHNICAL DETAILS

Housing	Powder coated extruded aluminum
LEDs	Nichia 3-step MacAdam
LED lumen maintenance	L90B10 > 60.000 h
Electrical	220 -240 VAC, Integrated driver

SELECTABLE FEATURES

Honeycomb light diffuser color	Black, Silver, Gold
Housing color	Black, White, Grey, Custom
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output (Direct Only)	W17 - Standart output
	W27 - High output
Efficacy	Up to 84 lm/W
Length, mm, ft	L560, L840, L1120, L1400, L1680, L1960, L2240, L2520, L2800, L3080
	1.10ft, 2.9ft, 3.8ft, 4.7ft, 5.6ft, 6.4ft, 7.4ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V


SEGMENT TYPE

INDIVIDUAL LUMINAIRE




Luminaire - IND
Endcaps at both ends


CONTINUOUS LINE MODULES



Start module - STA
Endcap at the start




Middle module - MID
No endcaps



End module - END
Endcap at the end

NERIS








Neris P IND OPL PWE W16 920 L1400 DA EU / PH


ORDER CODE EXAMPLE

Neris Pendant & Surface









TECHNICAL DETAILS

Housing	Powder coated extruded aluminum	
LEDs	Nichia 3-step MacAdam	
LED lumen maintenance	L90B10 > 60.000 h	
Electrical	rom 26W to 136 power	External driver for
	230 VAC 50 Hz Integrated driver	North American market
Suspension rope (for pendant)	Silver coloured, lenght - 2 m	6.56'
Lead cable (for pendant)	Transparent, lenght - 2 m	6.56'

SELECTABLE FEATURES

Light diffuser	Microprism, Opal
Housing color	Black, White, Grey, Custom
CRI	Ra80+, Ra90+, Ra95+
CCT	2700K, 3000K, 3500K, 4000K, 2700-6500K (tunable white)
Light output (Direct / Indirect)	W16/W8 - Standart output (~24W/m 7.2W/ft)
	W23/W12- High output (~35W/m 10.5W/ft)
Light output (Direct Only)	W16 - Standart output (~16W/m 5W/ft)
	W23- High output (~23W/m 7W/ft)
Efficacy	Microprism 109-112 Lm/W, Opal 105-110 Lm/W
Length, mm, ft	L560, L840, L1120, L1400, L1680, L1920, L2240, L2520, L2800, L3080
	1.8ft, 2.8ft, 3.7ft, 4.6ft, 5.5ft, 6.4ft, 7.3ft, 8.3ft, 9.2ft, 10.1ft
Control	Fixed output, DALI, PushDim, 0-10V

SEGMENT TYPE

INDIVIDUAL LUMINAIRE



Luminaire - IND
Endcaps at both ends

CONTINUOUS LINE MODULES




Start module - STA
Endcap at the start

Middle module - MID
No endcaps

End module - END
Endcap at the end

ULA





UlaL..A111x.H IBC PGY OPL L1008(3'4") / FL112/Nx G5 19W T930 L1000 NC / HR.P1F.L00030 / PH

ORDER CODE EXAMPLE

INDOOR
MODULAR
LED LIGHT
SYSTEMS


Ula S - Clear



TECHNICAL DATA

Cover	Clear / Opal (available on request)
Housing color	Black, White, Grey, Custom
Light engine	Any LED strip up to 24 W/m
Beam angle	107°
Connection	Input: plug; Output: socket
Light output ratio (LOR)	88%
Dimmable	YES
Voltage	24 VDC (22.5 - 25 VDC)

TECHNICAL DRAWING



LIGHT ENGINE

WHITE

SPECTRUM	KELVINS	POWER 4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft
820/822/825/827/830/	**CRI 80+**	431-670 lm/m		882-1327 lm/m		1334-1973 lm/m		1778-2607 lm/m		-	
835/840/850/857/865	2000-6500K	131-204 lm/ft		269-404 lm/ft		406-601 lm/ft		541-794 lm/ft		-	
920/922/925/T927/T930/	**CRI 90+tri**	374-652 lm/m		739-1294 lm/m		1095-1925 lm/m		1441-2546 lm/m		-	
T935/T940/T950/T957/T965	2000-6500K	114-199 lm/ft		225-394 lm/ft		333-586 lm/ft		439-775 lm/ft		-	
027/030/035/040/050	**CRI 95+**	432-488 lm/m		856-969 lm/m		1270-1441 lm/m		1672-1900 lm/m		-	
	2700-5000K	132-149 lm/ft		261-295 lm/ft		387-439 lm/ft		509-579 lm/ft		-	
Cutting step: 125 mm	**EFFICACY**	**148 lm/W**		**144 lm/W**		**139 lm/W**		**137 lm/W**		-	
	MAX RUN	**13m 43'**		**9m 30'**		**7m 23'**		**5.5m 18'**		-	

TUNABLE

SPECTRUM	KELVINS	POWER 4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft
Any combination within	**CRI 80+**	-		1119-1330 lm/m		-		1844-2674 lm/m		-	
this range 820 - 865	2000-6500K	-		341-415 lm/ft		-		562-815 lm/ft		-	
Any combination within	**CRI 90+tri**	-		954-1172 lm/m		-		1910-2276 lm/m		-	
this range 920 - T965	2000-6500K	-		291-357 lm/ft		-		582-694 lm/ft		-	
Any combination within	**CRI 95+**	-		946-998 lm/m		-		1757-1859 lm/m		-	
this range 020 - 050	2000-5000K	-		288-304 lm/ft		-		536-567 lm/ft		-	
Cutting step: 125 mm	**EFFICACY**			**121 lm/W**				**120 lm/W**			
	MAX RUN			**8 m 26'**				**4,5 m 15'**			

Custom color temperatures ranges available on request.


RGB

SPECTRUM	COLOR	POWER 4,8 W/m	1.5 W/ft	7,2 W/m	2.2 W/ft	11,52 W/m	3.5 W/ft	14,4 W/m	4.4 W/ft	24 W/m	7.3 W/ft
RGB	Total	-		278 lm/m	85 lm/ft	422 lm/m	128 lm/ft	528 lm/m	161 lm/ft	-	
Cutting step: 125 mm	**EFFICACY**			**39 lm/W**		**37 lm/W**		**37 lm/W**			
	MAX RUN										

SEGMENT TYPES

STANDALONE

Luminaire
Endcaps at both ends




CONTINUOUS LINE


Start module
Endcap at the start




Middle module
No endcaps



End module
Endcap at the end




Full module
Endcaps at both ends




Ula M - Opal

TECHNICAL DATA

Cover	Opal / Clear (available on request)
Housing color	Black, White, Grey, Custom
Light engine	Any LED strip up to 24 W/m
Beam angle	113°
Connection	Input: plug; Output: socket
Light output ratio (LOR)	39%
Dimmable	YES
Voltage	24 VDC (22.5 - 25 VDC)



TECHNICAL DRAWING



LIGHT ENGINE

WHITE

SPECTRUM	KELVINS	POWER 4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft	19,2 W/m	5.9 W/ft	24 W/m	7.3 W/ft
820/822/825/827/830/	**CRI 80+**	235-365 lm/m		481-724 lm/m		728-1076 lm/m		970-1422 lm/m		1204-1762 lm/m	
835/840/850/857/865	2000-6500K	72-111 lm/ft		146-220 lm/ft		222-328 lm/ft		295-433 lm/ft		367-537 lm/ft	
920/922/925/T927/T930/	**CRI 90+tri**	204-356 lm/m		403-706 lm/m		597-1050 lm/m		786-1389 lm/m		970-1721 lm/m	
T935/T940/T950/T957/T965	2000-6500K	62-108 lm/ft		123-215 lm/ft		182-320 lm/ft		239-423 lm/ft		295-524 lm/ft	
027/030/035/040/050	**CRI 95+**	236-266 lm/m		467-528 lm/m		693-786 lm/m		912-1036 lm/m		1126-1280 lm/m	
	2700-5000K	72-81 lm/ft		142-161 lm/ft		211-239 lm/ft		278-315 lm/ft		343-390 lm/ft	
Cutting step: 125 mm	**EFFICACY**	58 lm/w		57 lm/w		57 lm/w		57 lm/w		57 lm/w	
	MAX RUN	**13 m** 43'		**9 m** 30'		**7 m** 23'		**5,5 m** 18'		**4,5 m** 15'	

RGB

SPECTRUM	COLOR	POWER 7.2W/m	2.2W/ft	11.52W/m	3.5W/ft	14.4W/m	4.4W/ft	23W/m	7W/ft	24 W/m	7.3 W/ft	28,8 W/m	8.8 W/ft
RGB	Total	152 lm/m	46 lm/ft	230 lm/m	70 lm/ft	228 lm/m	88 lm/ft	462 lm/m	141 lm/ft	-		-	
Cutting step: 125 mm	**EFFICACY**	**20 lm/W**		**21 lm/W**		**20 lm/W**		**20 lm/W**					
	MAX RUN	**9m 30'**		**6.5m 21'**		**8m 26'**		**5.5m 18'**					

SEGMENT TYPES

STANDALONE

Luminaire
Endcaps at both ends




CONTINUOUS LINE


Start module
Endcap at the start



Middle module
No endcaps



End module
Endcap at the end



Full module
Endcaps at both ends



INDOOR
MODULAR
LED LIGHT
SYSTEMS


Ula L - Opal



TECHNICAL DATA

Cover	Opal / Clear (available on request)
Housing color	Black, White, Grey, Custom
Light engine	Any LED strip up to 48 W/m
Beam angle	111°
Connection	Input: plug; Output: socket
Light output ratio (LOR)	52%
Dimmable	YES
Voltage	24 VDC (22.5 - 25 VDC)

TECHNICAL DRAWING



LIGHT ENGINE

WHITE

SPECTRUM	KELVINS	POWER 9,6 W/m 2.9 W/ft	14,4 W/m 4.4 W/ft	18,2 W/m 5.5 W/ft	19,2 W/m 5.9 W/ft	24 W/m 7.3 W/ft	33,4 W/m 10.2 W/ft
820/822/825/827/830/	CRI 80+	525-770 lm/m	775-1135 lm/m	963-1418 lm/m	1051-1541 lm/m	1305-1908 lm/m	1787-2625 lm/m
835/840/850/857/865	2000-6500K	160-234 lm/ft	234-346 lm/ft	293-432 lm/ft	320-469 lm/ft	397-581 lm/ft	544-799 lm/ft
920/922/925/T927/T930/	CRI 90+tri	425-752 lm/m	622-1110 lm/m	772-1387 lm/m	1387-581 lm/m	1050-1865 lm/m	1433-2568 lm/m
T935/T940/T950/T957/T965	2000-6500K	129-229 lm/ft	189-338 lm/ft	235-422 lm/ft	422-259 lm/ft	320-568 lm/ft	436-782 lm/ft
027/030/035/040/050	CRI 95+	494-561 lm/m	722-822 lm/m	896-1022 lm/m	1022-988 lm/m	1219-1387 lm/m	1663-1895 lm/m
	2700-6500K	150-171 lm/ft	220-250 lm/ft	273-311 lm/ft	311-301 lm/ft	371-422 lm/ft	506-577 lm/ft
Cutting step: 125 mm (62,5 mm for 33W, 48W)	EFFICACY	58 lm/W	57 lm/W	58 lm/W	58 lm/W	56 lm/W	56 lm/W
	MAX RUN	7.5 m 25'	6 m 20'	5 m 16'	5.5 m 18'	4.5 m 15'	3.5 m 11'

TUNABLE

SPECTRUM	KELVINS	POWER 14,4 W/m 4.4 W/ft	19,2 W/m 5.9 W/ft	24 W/m 7.3 W/ft	28,8 W/m 8.8 W/ft	33,4 W/m 10.2 W/ft	48 W/m 14.6 W/ft
Any combination within	CRI 80+	-	1318-1580 lm/m	-	-	2201-2641 lm/m	-
this range 820 - 865	2000-6500K	-	402-482 lm/ft	-	-	671-805 lm/ft	
Any combination within	CRI 90+tri	-	1090-1340 lm/m	-	-	1804-2227 lm/m	-
this range 920 - T965	2000-6500K	-	332-408 lm/ft	-	-	550-679 lm/ft	
Any combination within	CRI 95+	-	1038-1099 lm/m	-	-	1688-1792 lm/m	-
this range 020 - 050	2700-5000K	-	316-355 lm/ft	-	-	515-546 lm/ft	-
Cutting step: 125 mm	EFFICACY	69 lm/W				67 lm/W	
	MAX RUN	4,5 m 15'				3m 10'	

RGB

SPECTRUM	COLOR	POWER 7.2W/m 2.2W/ft	11.52W/m 3.5W/ft	14.4W/m 4.4W/ft	23W/m 7W/ft	28,8 W/m 8.8 W/ft	33,4 W/m 10.2 W/ft	48 W/m 14.6 W/ft
RGB	Total	164 50	250 76	312 95	500 152		-	-
Cutting step: 125 mm	EFFICACY	23 lm/W	22 lm/W	22 lm/W	22 lm/W			
	MAX RUN	9 m 30'	6,5 m 21'	8 m 26'	5.5 m 18'			

RGBW

SPECTRUM	KELVINS	POWER 14,4 W/m 4.4 W/ft	19,2 W/m 5.9 W/ft	24 W/m 7.3 W/ft	28,8 W/m 8.8 W/ft	33,4 W/m 10.2 W/ft	48 W/m 14.6 W/ft
822 / 825 / 827 / 830	CRI 80+	416-513 lm/m	468-552 lm/m	660-822 lm/m	-	-	-
835 / 840 / 850 / 865	2200-6500K	127-156 lm/ft	143-168 lm/ft	201-251 lm/ft	-	-	-
922 / T927 / T930 / T935	CRI 90+tri	407-441 lm/m	433-478 lm/m	596-680 lm/m	-	-	-
T940 / T950 / T965	2200-6500K	124- 134 lm/ft	133-146 lm/ft	182-207 lm/ft	-	-	-
Cutting step: 125 mm	EFFICACY	28 lm/W	23 lm/W	25 lm/W			
	MAX RUN	7 m 23'	5.5 m 18'	5 m 16'			

SEGMENT TYPES

STANDALONE

Luminaire
Endcaps at both ends



CONTINUOUS LINE

Start module
Endcap at the start




Middle module
No endcaps



End module
Endcap at the end



Full module
Endcaps at both ends



ACCESSORIES


SOCKET CONNECTORS

CODE	DESCRIPTION
CON-PH-TP-2F LXXX	2-pin socket
CON-PH-TP-3F LXXX	3-pin socket
CON-PH-TP-4F LXXX	4-pin socket
CON-PH-TP-5F LXXX	5-pin socket




SOCKET/PLUG CONNECTORS

CODE	DESCRIPTION
CON-PH-TP-2M/2F LXXX	2-pin extention
CON-PH-TP-3M/3F LXXX	3-pin extention
CON-PH-TP-4M/4F LXXX	4-pin extention
CON-PH-TP-5M/5F LXXX	5-pin extention



PLUG CONNECTORS

CODE	DESCRIPTION
CON-PH-TP-2M LXXX	2-pin plug
CON-PH-TP-3M LXXX	3-pin plug
CON-PH-TP-4M LXXX	4-pin plug
CON-PH-TP-5M LXXX	5-pin plug



MOUNTING BRACKETS


CODE	DESCRIPTION
PRG.AULSI.F01.GZK	Mounting bracket (Ula S / M)
PRG.AULSI.F02.GZK	Mounting bracket with magnet (Ula S / M)
PRG.AULSI.F03.GZK	Mounting bracket adjustable (Ula S / M)
PRG.A111x.ASM.00009	Mounting bracket (Ula L)



WIRE LENGTHS AVAILABLE

CODE	L150	L500	L1000	L2000
Length	150 mm	500 mm	1000 mm	2000 mm
	5.9 in	1 ft 8 in	3 ft 3 in	6 ft 6 in

CORNER MODULES AVAILABLE FOR ULA L



L-shaped





X-shaped



T-shaped

INDOOR PROFILE FIXTURES





A007x.Round IEC AGY 07x.1.CLR.30D L1022(3'5") / FL112/Nx G5 19W T930 L1000 HR J1x L0200 STD PH


ORDER CODE EXAMPLE

INDOOR PROFILE FIXTURES

Housing colors: Black, White, Grey, Custom


A001A






A001B





A002M





COVERS




PRG.AULSI.C01.CLR
Clear



PRG.AULSI.C01.OPL
Opal

BRACKETS




PRG.A002x.F01.GZK



PRG.A002x.F06.RGY



PRG.A002x.F06.PBK




PRG.A002x.F01.PBK



PRG.A002x.F04.RGY

A005M





COVERS




PRG.AULSI.C01.CLR
Clear




PRG.AULSI.C01.OPL
Opal


BRACKETS




PRG.A002x.F01.GZK




PRG.A002x.F06.RGY



PRG.A002x.F06.PBK




PRG.A002x.F01.PBK



PRG.A002x.F04.RGY

A007X





COVERS




PRG.A002x.C01.CLR
Opal




PRG.A002x.C01.OPL
Clear



PRG.A002x.C02.OPL
Opal




PRM.A007x.C01.CLR
Clear



PRG.A007x.C01.OPL
Opal

BRACKETS




PRG.A002x.F01.GZK



PRG.A002x.F06.RGY




PRG.A002x.F06.PBK



PRG.A002x.F01.PBK

A017M





COVERS



PRG.A017M.C01.OPL
Opal




PRG.A017x.C03.RBK
Black

BRACKETS



PRG.A016x.F02.RGY



PRG.A019x.F01.GZK


BRACKETS



PRG.A017x.PRT.02



PRG.A015x.F04.RWE



PRG.A017x.PRT.00004



PRG.A006x.PRT.00002



PRG.A016x.F01.GCM



PRG.A016x.PRT.00001




PRG.A017x.PRT.00006




PRG.A016x.F01.RGY

A018N





COVERS



PRG.A018N.C01.OPL
Opal


BRACKETS




PRG.A018N.F01.GZK

A020X





COVERS



PRM.A002x.C01.CLR
Clear



PRM.A002x.C01.OPL
Opal



PRM.A002x.C02.OPL
Opal



PRM.A007x.C01.CLR
Clear




PRM.A007x.C01.OPL
Opal

A035X






COVERS



PRG.A035x.C01.OPL
Opal



PRG.A035x.C02.CLR
85 °clear



PRG.A035x.C03.CLR
15 ° clear



PRG.A035x.C04.CLR
30 ° clear



PRG.A035x.C05.CLR
60 °clear



PRG.A035x.C06.CLR
90 ° clear




PRG.A035x.C07.CLR
120 ° clear




PRG.A035x.C07.OPL
Opal

BRACKETS



PRG.A035x.F03.GZK



PRG.A035x.F01.RWE
plastic



PRG.A035x.F06.RWE
plastic, 15 °



PRG.A035x.F08.RWE
plastic, 30 °



PRG.A035x.F02.RWE
plastic, 45 °




PRG.A035x.F09.RWE
plastic, 60 °

BRACKETS



PRG.A035x.F04.GZK




PRG.A035x.F01.GZK



PRG.A035x.F02.GZK
metal, 45 °

A016X






COVERS



PRG.A016x.C01.CLR
Clear



PRG.A016x.C01.OPL
Opal



PRG.A016x.C02.FRO
Frosted



PRG.A016x.C03.CLR
Clear




PRG.A016x.C03.OPL
Opal


BRACKETS




PRG.A016x.F01.GCM




PRG.A016x.PRT.00001



PRG.A017x.PRT.00006



PRG.A017x.PRT.00005




PRG.A016x.F01.RGY



PRG.A017x.F02.RGY

A003X





COVERS



PRG.A016x.C03.CLR
Clear



PRG.A016x.C03.OPL
Opal


BRACKETS



PRG.A019x.F01.GZK




PRG.A015x.F04.RWE




PRG.A017x.PRT.00004



PRG.A006x.PRT.00002



PRG.A017x.PRT.00006




PRG.A017x.PRT.00005



PRG.A017x.F02.RGY

A008A





COVERS



PRG.A002x.C01.CLR
Clear



PRG.A002x.C01.OPL
Opal



PRG.A002x.C02.OPL
Opal




PRG.A007x.C01.CLR
Clead



PRG.A007x.C01.OPL
Opal

A015X





COVERS




PRG.A016x.C03.CLR
Clear



PRG.A016x.C03.OPL
Opal


BRACKETS




PRG.A019x.F01.GZK



PRG.A015x.F04.RWE



PRG.A017x.PRT.00004




PRG.A017x.PRT.00006



PRG.A017x.PRT.00005

A019X





COVERS




PRG.A016x.C03.CLR
Clear



PRG.A016x.C03.OPL
Opal


BRACKETS




PRG.A019x.F01.GZK



PRG.A015x.F04.RWE



PRG.A017x.PRT.00004




PRG.A017x.PRT.00006



PRG.A017x.PRT.00005

A030X





COVERS



PRG.A002x.C01.CLR
Clear



PRG.A002x.C01.OPL
Opal



PRG.A002x.C02.OPL
Opal




PRG.A007x.C01.CLR
Clear



PRG.A007x.C01.OPL
Opal

A011X





COVERS



PRG.A016x.C03.CLR
Clear



PRG.A016x.C03.OPL
Opal


BRACKETS



PRG.A015x.F04.RWE

A032X





COVERS



PRG.A032x.C01.OPL
Opal



PRG.A032x.C02.OPL
Opal

BRACKETS



PRG.A032x.F01.GZK

A042X





COVERS



PRG.A042x.C01.CLR
Clear



PRG.A042x.C01.OPL
Opal

BRACKETS



PRG.A042x.F01.GZK



PRG.A042x.F02.RWE

A006X





COVERS



PRG.A006x.C01.OPL
Opal

BRACKETS




PRG.A006x.PRT.00001



PRG.A006x.PRT.002




PRG.A016x.F01.GCM



PRG.A016x.PRT.00001

A025X





COVERS




PRG.A002x.C01.CLR
Clear




PRG.A002x.C01.OPL
Opal



PRG.A002x.C02.OPL
Opal




PRG.A007x.C01.CLR
Clear




PRG.A007x.C01.OPL
Opal

BRACKETS





PRG.A009x.F01.GZK



PRG.A025x.F01.GZK


A036X





A009X





COVERS




PRM.A002x.C01.CLR
Clear




PRM.A002x.C01.OPL
Opal



PRM.A002x.C02.OPL
Opal




PRM.A007x.C01.CLR
Clear




PRM.A007x.C01.OPL
Opal


BRACKETS




PRG.A009x.F01.GZK




PRG.A009x.F01.PBK



PRG.A009x.F02.GZK




PRG.A009x.F02.PBK



PRG.A009x.F03.GZK

A050X






COVERS

PRM.A050x.C01.CLR
Clear

PRM.A050x.C01.OPL
Opal

BRACKETS




PRG.A050x.F01.RGY

OUTDOOR

ATLANTIS





AtlantisSideG2 IB RWE.EOP L1025(3'5")/ FL112/Nx G5 14W 920 L1000 HR J1x L0200 STD PH

ORDER CODE EXAMPLE


Atlantis Top



One way to bend the rules


Bendable at the top or side and fully connectable, the Atlantis is a flexible LED line suitable for a wide range of outdoor and indoor uses. This LED line has been designed for easy installation along uneven surfaces like rounded edges, pillars, and coves. Individual lines can be connected seamlessly for a continuous light effect.

The Atlantis Side is dust and waterproof, salt and solvent-proof, and UV resistant. It has been rated at IP67 for ingress protection.



BEND TYPE: TOP. R = 15CM (5,9 IN)





TECHNICAL DATA

LEDs per meter	112 LEDs/m	34 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC), 48 VDC	
Cutting step	62,5 mm	2.46 in
Maximum length L+-3mm/m (0.11in)	4,5 m	177.1 in
Height	16 mm	0.63 in
Width	14 mm	0.55 in
Bend radius	Rmin=15cm	Rmin = 5.91 in
Light output ratio (LOR)	59%	
TC temperature	<75° C	<167° F
Operating temperature	-25°C...+40°C	-13°F...104°F
Beam angle	115°	
Dimmable	YES	

L90B10 NICHIA

LIGHT ENGINE

WHITE 24V

SPECTRUM	KELVINS	POWER 4.8w/m	1.5W/ft	9.6w/m	2.92W/ft	14.4w/m	4.38W/ft
820/822/825/827/830/	**CRI 80+**	293-455 lm/m		599-902		907-1341	
835/840/850/865	**2000-6500K**	89-139 lm/ft		170-275		276-408	
920/922/925/T927/T930/	**CRI 90+tri**	254-443 lm/m		503-880		744-1309	
T935/T940/T950/T965	**2000-6500K**	77-135 lm/ft		153-268		227-399	
Cutting step: 125 mm	**EFFICACY**	**93** lm/w		**92** lm/w		**92** lm/w	
	MAX RUN	**13m 43'**		**9m 30'**		**7m 23'**	

WHITE 48V

SPECTRUM	KELVINS	POWER 4.8w/m	1.5W/ft	9.6w/m	2.92W/ft	14.4w/m	4.38W/ft
820/822/825/827/830/	**CRI 80+**	293-455 lm/m		599-902			
835/840/850/865	**2000-6500K**	89-139 lm/ft		170-275			
920/922/925/T927/T930/	**CRI 90+tri**	254-443 lm/m		503-880			
T935/T940/T950/T965	**2000-6500K**	77-135 lm/ft		153-268			
Cutting step: 125 mm	**EFFICACY**	**93** lm/w		**92** lm/w			
	MAX RUN	**32.5m 107'**		**14m 46'**			

TUNABLE


SPECTRUM	KELVINS	POWER 9,6 W/m	2.9 W/ft
Any combination within	**CRI 80+**	804 lm/m	
this range 820-865	**2000-6500K**	245 lm/ft	
Cutting step: 125 mm	**EFFICACY**	**84** lm/w	
	MAX RUN	**4.5m 15'**	

RGB

SPECTRUM	COLOR	POWER 7.2W/m	2.2W/ft	11.52W/m	3.5W/ft
RGB	**Total**	183 lm/m	56 lm/ft	287	87
Cutting step: 125 mm	**EFFICACY**	**25** lm/w		**25** lm/w	
	MAX RUN	**9m 30'**		**9.5m 31'**	

Disclaimer: Technical data is subject to change without prior notice.
Tolerances of +-5% in luminous flux and light color should be accepted.

Atlantis Side




Innovations

The second-generation Atlantis, at 14 × 16 mm, is sleeker yet maintains the benefits of its predecessor. It features added side grooves for simpler installation, an improved endcap for easier unit connection, redesigned mounting clips for secure mounting, and is waterproof and dust resistant due to better materials. Both Top and Side models are the same size, enabling vertical and horizontal bends in one continuous line.

FRONT VIEW


SIDE VIEW



14mm +-1mm
(0,55in +-0.04in)

BEND TYPE: SIDE. R = 15CM (5,9 IN)





TECHNICAL DATA

LEDs per meter	112 LEDs/m	34 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC), 48VDC	
Cutting step	62,5 mm	2.46 in
Height	16 mm	0.63 in
Width	14 mm	0.55 in
Maximum length L+-3mm/m (0.11in)	4,5 m	177.1 in
Bend radius	Rmin= 15cm	Rmin = 5.91 in
Light output ratio (LOR)	54%	
TC temperature	<75° C	<167° F
Operating temperature	-25°C...+40°C	-13°F...104°F
Beam angle	120°	
Dimmable	YES	

LIGHT ENGINE

WHITE 24V

SPECTRUM	KELVINS	POWER 4.8w/m	1.5W/ft	9.6w/m	2.92W/ft	14.4w/m	4.38W/ft
820/822/825/827/830/	**CRI 80+**	269-417 lm/m		549-827		831-1229	
835/840/850/865	**2000-6500K**	82-126 lm/ft		167-252		253-374	
920/922/925/T927/T930/	**CRI 90+tri**	233-406 lm/m		460-806		682-1199	
T935/T940/T950/T965	**2000-6500K**	71-124 lm/ft		140-245		208-365	
Cutting step: 125 mm	**EFFICACY**	**86 lm/w**		**86 lm/w**		**85 lm/w**	
	MAX RUN	**13m 43'**		**9m 30'**		**7m 23'**	

WHITE 48V

SPECTRUM	KELVINS	POWER 4.8w/m	1.5W/ft	9.6w/m	2.92W/ft	14.4w/m	4.38W/ft
820/822/825/827/830/	**CRI 80+**	269-417 lm/m		549-827			
835/840/850/865	**2000-6500K**	82-126 lm/ft		167-252			
920/922/925/T927/T930/	**CRI 90+tri**	233-406 lm/m		460-806			
T935/T940/T950/T965	**2000-6500K**	71-124 lm/ft		140-245			
Cutting step: 125 mm	**EFFICACY**	**86 lm/w**		**86 lm/w**			
	MAX RUN	**32.5m 107'**		**14m 46'**			

TUNABLE

SPECTRUM	KELVINS	POWER 9,6 W/m	2.9 W/ft
Any combination within	**CRI 80+**	736 lm/m	
this range 820-865	**2000-6500K**	224 lm/ft	
Cutting step: 125 mm	**EFFICACY**	**77 lm/w**	
	MAX RUN	**4.5m 15'**	

RGB


SPECTRUM	COLOR	POWER 7.2W/m	2.2W/ft	11.52W/m	3.5W/ft
RGB	**Total**	173 lm/m	53 lm/ft	263	80
Cutting step: 125 mm	**EFFICACY**	**24 lm/w**		**23 lm/w**	
	MAX RUN	**9m 30'**		**9.5m 31'**	

Disclaimer: Technical data is subject to change without prior notice.
Tolerances of +-5% in luminous flux and light color should be accepted.

ACCESSORIES


SOCKET CONNECTORS

CODE	DESCRIPTION
CON-HI-IP-2F LXXX	2-pin socket
CON-HI-IP-3F LXXX	3-pin socket
CON-HI-IP-4F LXXX	4-pin socket
CON-HI-IP-5F LXXX	5-pin socket



SOCKET/PLUG CONNECTORS

CODE	DESCRIPTION
CON-HI-IP-2M/2F LXXX	2-pin extention
CON-HI-IP-3M/3F LXXX	3-pin extention
CON-HI-IP-4M/4F LXXX	4-pin extention
CON-HI-IP-5M/5F LXXX	5-pin extention




PLUG CONNECTORS

CODE	DESCRIPTION
CON-HI-IP-2M LXXX	2-pin plug
CON-HI-IP-3M LXXX	3-pin plug
CON-HI-IP-4M LXXX	4-pin plug
CON-HI-IP-5M LXXX	5-pin plug



ATLANTIS MOUNTING PROFILE


CODE	DESCRIPTION
Atlantis.Fix L50	ALU anod. profile, 50 mm
Atlantis.Fix L1000	ALU anod. profile, 1000 mm
Atlantis.Fix L2000	ALU anod. profile, 2000 mm



WIRE LENGTHS AVAILABLE

CODE	L150	L500	L1000	L2000
Length	150 mm	500 mm	1000 mm	2000 mm
	5.9 in	1 ft 8 in	3 ft 3 in	6 ft 6 in

AQUA



Aqua IE RWE.ECL L01020(3'5")/ FL56/NN G5 09W 920 L02600 HR J1x L0200 STD PH

ORDER CODE EXAMPLE

AQUA




Wraps around one’s little finger. Literally.

Our Aqua IP67 LED line combines exceptional flexibility and robustness together with a small size, for an outdoor lighting solution that’s ideal for lighting hard-to-reach areas.


It features high-mark ingress protection and excellent LED strip durability for long-term outdoor use.

Ideal for linear decorative lighting, cove lighting, edge lighting and curved applications, this slim LED line offers versatility and reliability for lighting outdoor spaces and wet indoor locations.





BEND TYPE: TOP. R = 10CM (3,93 IN)



TECHNICAL DATA

LEDs per meter	56 LEDs/m	17 LEDs/ft
Voltage	24 VDC (22.5 - 25 VDC), 48VDC	
Cutting step	125 mm	4.92 in
Height	4 mm	0.15 in
Width	12 mm	0.47 in
Bend radius	Rmin=10cm	Rmin = 3.94 in
Light output ratio (LOR)	80%	
TC temperature	<75° C	<167° F
Operating temperature	-25°C...+50°C	-13°F...122°F
Beam angle	112°	
Dimmable	YES	

L90B10 NICHIA

LIGHT ENGINE

WHITE 24V

		POWER							
SPECTRUM	KELVINS	2.4 W/m	0.73 W/ft	4.8 W/m	1.46 W/ft	9.6 W/m	2.92 W/m	14.4 W/m	4.38 W/ft
820/822/825/827/830/	CRI 80+	197-306 lm/m		403-606		806-1213		1219-1803	
835/840/850/865	2000-6500K	60-93 lm/ft		123-185		245-369		371-549	
920/922/925/T927/T930/	CRI 90+tri	170-298 lm/m		338-591		676-1182		1000-1760	
T935/T940/T950/T965	2000-6500K	52-91 lm/ft		103-180		206-360		305-536	
027/030/035/040/050	CRI 95+	197-223 lm/m		391-442		782-885		1160-1316	
	2700-5000K	60-68 lm/ft		119-135		238-269		353-401	
Cutting step: 125 mm	EFFICACY	104 lm/w		105 lm/w		105 lm/w		105 lm/w	
	MAX RUN	18.5m 61'		13m 43'		9m 30'		7m 23'	

WHITE 48V

		POWER							
SPECTRUM	KELVINS	2.4 W/m	0.73 W/ft	4.8 W/m	1.46 W/ft	9.6 W/m	2.92 W/m	14.4 W/m	4.38 W/ft
820/822/825/827/830/	CRI 80+	-		394-612 lm/m		806-1213		-	
835/840/850/865	2000-6500K	-		120-186 lm/ft		245-369		-	
920/922/925/T927/T930/	CRI 90+tri	-		342-596 lm/m		676-1182		-	
T935/T940/T950/T965	2000-6500K	-		104-181 lm/ft		206-360		-	
027/030/035/040/050	CRI 95+	-		395-446 lm/m		782-885		-	
	2700-5000K	-		120-136 lm/ft		238-269		-	
Cutting step: 125 mm	EFFICACY	-		105 lm/w		105 lm/w		-	
	MAX RUN	-		32.5m 107'		22.5m 74'		-	

TUNABLE

		POWER	
SPECTRUM	KELVINS	9,6 W/m	2.9 W/ft
Any combination within	CRI 80+	812-1023 lm/m	
this range 820-865	2000-6500K	257-312 lm/ft	
Any combination within	CRI 90+tri	658-1064 lm/m	
this range 920-T965	2000-6500K	200-324 lm/ft	
Any combination within	CRI 95+	658-1064 lm/m	
this range 020-065	2000-5000K	200-324 lm/ft	
Cutting step: 125 mm	EFFICACY	111 lm/w	
	MAX RUN	8m 26'	

RGB


		POWER					
SPECTRUM	COLOR	7.2W/m	2.2W/ft	11.52W/m	3.5W/ft	14.4W/m	4.4W/ft
RGB	Total	254 lm/m	77 lm/ft	385	117	483	147
Cutting step: 125 mm	EFFICACY	35 lm/w		34 lm/w		34	
	MAX RUN	9m 30'		6.5m 21'		8m 26'	

Disclaimer: Technical data is subject to change without prior notice.
Tolerances of +-5% in luminous flux and light color should be accepted.

ACCESSORIES

SOCKET CONNECTORS

CODE	DESCRIPTION
CON-HI-IP-2F LXXX	2-pin socket
CON-HI-IP-3F LXXX	3-pin socket
CON-HI-IP-4F LXXX	4-pin socket
CON-HI-IP-5F LXXX	5-pin socket




SOCKET/PLUG CONNECTORS

CODE	DESCRIPTION
CON-HI-IP-2M/2F LXXX	2-pin extention
CON-HI-IP-3M/3F LXXX	3-pin extention
CON-HI-IP-4M/4F LXXX	4-pin extention
CON-HI-IP-5M/5F LXXX	5-pin extention



PLUG CONNECTORS

CODE	DESCRIPTION
CON-HI-IP-2M LXXX	2-pin plug
CON-HI-IP-3M LXXX	3-pin plug
CON-HI-IP-4M LXXX	4-pin plug
CON-HI-IP-5M LXXX	5-pin plug




AQUA MOUNTING KITS

CODE	DESCRIPTION
Mounting kit BASIC	Silicon dispenser pistol; clear end-cap (10 pcs); sealant; static mixers (5pcs)
Mounting kit PRO	Silicon dispenser pistol (pro); clear end-cap (10 pcs); sealant; static mixers (10pcs); sealing mould (2pcs)



AQUA MOUNTING BRACKETS

CODE	DESCRIPTION
Aqua.FIX L1000	Mounting profile, transparent length - 1000 mm
Aqua.FIX L2000	Mounting profile, transparent length - 2000 mm
Aqua.FIX L3000	Mounting profile, transparent length - 3000 mm
Aqua FIX L50	Plastic holder, transparent
Tape DB	Double adhesive tape 25m



WIRE LENGTHS AVAILABLE

CODE	L150	L500	L1000	L2000
Length	150 mm	500 mm	1000 mm	2000 mm
	5.9 in	1 ft 8 in	3 ft 3 in	6 ft 6 in


SLEEVES

LED strips sleeves are designed for decorative, ambient and indirect lighting applications.

The virtually unlimited length of sleeves and individual segment junctions invisible to the user means that these products are an excellent decorative solutions for large rooms, hallways, etc.

The sleeves are securely sealed from dust, water and offer a wide selection of wiring options. They are also resistant to ambient temperature changes.






Python 02 IE RWE L1012(3'4") / FL112/Dx G5 14W 940 L1000 HR J1x L0200 STD PH

ORDER CODE EXAMPLE


SLEEVES

PYTHON 02






BEND RADIUS




10 cm (3,94 in) Opal. Side bend

BRACKETS




INDIVIDUAL MODULE



Wire end


WIRE ENDS




Bare ends With connector

PYTHON 03






BEND RADIUS




15 cm (5.90 in) Opal. Side bend

BRACKETS




INDIVIDUAL MODULE



Wire end Wire bottom Wire side


WIRE ENDS




Bare ends With connector

PYTHON 04






BEND RADIUS




15 cm (5.90 in) Opal. Side bend

BRACKETS




INDIVIDUAL MODULE



Wire end Wire bottom Wire side


WIRE ENDS



Bare ends With connector


COBRA 07








BEND RADIUS




15 cm (5.90 in) Opal. Top bend


BRACKETS



INDIVIDUAL MODULE




Wire end Wire bottom



Wire side

WIRE ENDS





Bare ends With connector

VIPER

VIPER-08 VIPER-09











BEND RADIUS





10 cm (3,94 in)




Clear. Top bend

BRACKETS






INDIVIDUAL MODULE




Wire end

WIRE ENDS




Bare ends



With connector

VENTA IP67







A130x.IP67.HU IBC PWE 30D.UGR-V.ECL L1010(3'4") / FL112/Nx G5 33W T930 L1000 HR J1x L0200 STD PH

ORDER CODE EXAMPLE

Venta IP67







TECHNICAL DETAILS

Housing	Powder coated extruded aluminum	
LEDs	Nichia 3-step MacAdam	
LED lumen maintenance	L90B10 > 60.000 h	
Electrical	220 -240 VAC, Integrated driver	
	110-277 VAC, Integrated driver (for 0-10V)	
Fix rotation angle	Up to 200°	
Lead cable (for pendant)	Transparent, lenght - 2 m	6.56'

SELECTABLE FEATURES

Light diffuser	Lense 30D, Lense 30D + UGR, Lense 14D, Lense 14D + UGR, Microprism, Opal
Housing color	Black, White, Grey, Custom
CRI	Ra80+, Ra90+, Ra95+
CCT	2000K, 2200K, 2500K, 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K, 2700-6500K (tunable white), RGB, 2700-6500K RGBW
Light output (Direct Only)	Up to 19W/m (5.9W/ft)
Efficacy	Microprism 109-112 Lm/W, Opal 105-110 Lm/W ;up to 130 lm/W
Length, mm, ft	Minimum length 500mm (19.68in) - maximum length - 3000mm (118.11in)
Control	Control sold separately; DALI, Casambi, 1- 10V, Phase Cut

SEGMENT TYPE

INDIVIDUAL LUMINAIRE

Luminaire - IND
Endcaps at both ends

CONTINUOUS LINE MODULES


Start module - STA
Endcap at the start

Middle module - MID
No endcaps

End module - END
Endcap at the end

ULA IP67





AULMO IBC AGY EOP L1006(3'4") / FL112/Nx G5 14W T930 L1000 NC / HR.J1X.L00030 / PH

ORDER CODE EXAMPLE


Ula S IP67 - Clear



TECHNICAL DATA

Cover	Clear (available on request)	
Housing color	Black, White, Grey, Custom	
Beam angle	120°	
Connection	Input: plug; Output: socket	
Light output ratio (LOR)	66%	
Dimmable	YES	
Operating temperature	-25°C...+50°C	-13°F...122°F
Storage temperature	-40°C — 80°C	-40°F — 176°F
Voltage	24 VDC (22.5 - 25 VDC)	

TECHNICAL DRAWING



LIGHT ENGINE

WHITE

SPECTRUM	KELVINS	POWER 1,2 W/m (0.36 W/ft)	1,92 W/m (0.58 W/ft)	2,4 W/m (0.73 W/ft)	4,8 W/m (1.5 W/ft)	9,6 W/m (2.9 W/ft)	14,4 W/m (4.4 W/ft)	18,2 W/m (5.5 W/ft)
820/822/825/827/830/	CRI 80+	-	-	163-253 lm/m	334-503	674-988	994-1455	1348-1976
835/840/850/857/865	2000-6500K	-	-	50-77 lm/ft	102-153	205-301	303-443	410-602
920/922/925/T927/T930/	CRI 90+tri	-	-	114-247 lm/m	280-490	546-964	798-1423	1092-1930
T935/T940/T950/T957/T965	2000-6500K	-	-	35-75 lm/ft	85-149	166-294	243-433	333-458
027/030/035/040/050	CRI 95+	-	-	163-185 lm/m	324-367	634-720	926-1054	1267-1440
	2700-5000K	-	-	50-56 lm/ft	99-112	193-219	282-321	386-438
Cutting step: 125 mm	EFFICACY			68 lm/w	70 lm/w	70 lm/w	69 lm/w	70 lm/w
	MAX RUN			18,5 m 61'	13 m 43'	9 m 30'	7 m 23'	5,5 m 18'

TUNABLE

SPECTRUM	KELVINS	POWER 4,8 W/m (1.5 W/ft)	9,6 W/m (2.9 W/ft)	14,4 W/m (4.4 W/ft)	19,2 W/m (5.9 W/ft)	24 W/m (7.3 W/ft)	28,8 W/m (8.8 W/ft)	33,4 W/m (10.2 W/ft)	48 W/m (14.6 W/ft)
Any combination within	CRI 80+	-	791-810 lm/m	-		-	-	-	-
this range 827 - 865	2000-6500K	-	241-247 lm/ft	-		-	-	-	-
Any combination within	CRI 90+tri	-	654-682 lm/m	-					
this range 920 - T965	2000-6500K	-	199-208 lm/ft	-					
Any combination within	CRI 95+	-	618-646 lm/m	-		-	-	-	-
this range 020 - 065	2000-6500K	-	188-197 lm/ft	-		-	-	-	-
Cutting step: 125 mm	EFFICACY		99 lm/w						
	MAX RUN		6,5 m 21'						

Custom color temperatures ranges available on request.


RGB

SPECTRUM	COLOR	POWER 4,8 W/m (1.5 W/ft)	7,2 W/m (2.2 W/ft)	11,52 W/m (3.5 W/ft)	14,4 W/m (4.4 W/ft)	23 W/m (7 W/ft)	28,8 W/m (8.8 W/ft)
RGB	TOTAL	-	201 lm/m 61 lm/ft	306 93	382 116	613 187	-
Cutting step: 125 mm	EFFICACY		28 lm/w	27 lm/w	27 lm/w	27 lm/w	
	MAX RUN		9 m 30'	6,5 m 21'	8 m 26'	5,5 m 18'	

SEGMENT TYPES

STANDALONE

Luminaire
Endcaps at both ends



CONTINUOUS LINE


Start module
Endcap at the start




Middle module
No endcaps




End module
Endcap at the end



Full module
Endcaps at both ends




Ula M IP67 - Opal



TECHNICAL DATA

Cover	Opal PUR (available on request)	
Housing color	Black, White, Grey, Custom	
Beam angle	120°	
Connection	Input: plug; Output: socket	
Light output ratio (LOR)	29%	
Dimmable	YES	
Operating temperature	-25°C...+50°C	-13°F...122°F
Storage temperature	-40°C — 80°C	-40°F — 176°F
Voltage	24 VDC (22.5 - 25 VDC)	

TECHNICAL DRAWING



LIGHT ENGINE

WHITE

SPECTRUM	KELVINS	POWER 1,2 W/m (0.36 W/ft)	1,92 W/m (0.58 W/ft)	2,4 W/m (0.73 W/ft)	4,8 W/m (1.5 W/ft)	9,6 W/m (2.9 W/ft)	14,4 W/m (4.4 W/ft)	18,2 W/m (5.5 W/ft)	19,2 W/m (5.9 W/ft)
820/822/825/827/830/	CRI 80+	-	-	71-114 lm/m	145-226	293-445	432-656	537-819	586-890
835/840/850/857/865	2000-6500K	-	-	22-35 lm/ft	44-69	89-135	132-200	164-249	178-271
920/922/925/T927/T930/	CRI 90+tri	-	-	61-111 lm/m	122-221	237-435	347-641	430-802	475-869
T935/T940/T950/T957/T965	2000-6500K	-	-	19-34 lm/ft	37-67	72-132	106-195	131-244	145-265
027/030/035/040/050	CRI 95+	-	-	71-80 lm/m	141-159	275-313	402-458	500-570	551-626
	2700-5000K	-	-	22-24 lm/ft	43-48	84-95	122-139	152-174	168-190
Cutting step: 125 mm	EFFICACY			46 lm/w	46 lm/w	45 lm/w	45 lm/w	44 lm/w	45 lm/w
	MAX RUN			18.5m 61'	13m 43'	7.5m 25'	7m 23'	5m 16'	5.5m 18'

RGB

SPECTRUM	COLOR	POWER 7,2 W/m (2.2 W/ft)	11,52 W/m (3.5 W/ft)	14,4 W/m (4.4 W/ft)	23 W/m (7 W/ft)
RGB	TOTAL	143 44	216 66	271 83	434 132
Cutting step: 125 mm	EFFICACY	20 lm/w	19 lm/w	19 lm/w	19 lm/w
	MAX RUN	9m 30'	6.5m 21'	8m 26'	5.5m 18'

SEGMENT TYPES

STANDALONE

Luminaire
Endcaps at both ends



CONTINUOUS LINE


Start module
Endcap at the start




Middle module
No endcaps



End module
Endcap at the end



Full module
Endcaps at both ends



Disclaimer: Technical data is subject to change without prior notice.
Tolerances of +-5% in luminous flux and light color should be accepted.

OUTDOOR
MODULAR
LIGHTING

Ula L IP65 - Opal



TECHNICAL DATA

Cover	Opal / Clear (available on request)	
Housing color	Black, White, Grey, Custom	
Light engine	Any LED strip up to 48 W/m	
Beam angle	120°	
Connection	Input: plug; Output: socket	
Light output ratio (LOR)	50%	
Dimmable	YES	
Operating temperature	-25°C...+50°C	-13°F...122°F
Storage temperature	-40°C — 80°C	-40°F — 176°F
Voltage	24 VDC (22.5 - 25 VDC)	

LIGHT ENGINE

WHITE

		POWER					
SPECTRUM	**KELVINS**	**19.2W/m**	5.84W/ft	**24W/m**	7.3W/ft	**33.6W/m**	10.2W/ft
820/822/825/827/830/	**CRI 80+**	1002-1470 lm/m		1244-1820		1704-2504	
835/840/850/857/865	**2000-6500K**	305-448 lm/ft		379-554		519-762	
920/922/925/T927/T930/	**CRI 90+tri**	812-1435 lm/m		1002-1779		1366-2449	
T935/T940/T950/T957/T965	**2000-6500K**	247-437 lm/ft		305-542		416-746	
027/030/035/040/050	**CRI 95+**	942-107 1lm/m		1163-1323		1587-1808	
	2700-5000K	287-326 lm/ft		354-403		483-550	
Cutting step: 125 mm (62,5 mm for 33W, 48W)	**EFFICACY**	**56 lm/w**		**55 lm/w**		**54 lm/w**	
	MAX RUN	**5.5m 18'**		**4.5m 15'**		**3.5m 11'**	

TUNABLE

SPECTRUM		**KELVINS**	**19,2 W/m**	5.9 W/ft	**24 W/m**	7.3 W/ft	**33,4 W/m**	10.2 W/ft
820/865	**825/857**	**CRI 80+**	1257-1331 lm/m		-		2099-2225	
827/857	**827/850**	**2000-6500K**	383-405 lm/ft		-		639-677	
920/965	**925/957**	**CRI 90+tri**	1040-1283 lm/m		-		1721-2124	
927/950		**2000-6500K**	316-391 lm/ft		-		524-647	
027/030	**035/050**	**CRI 95+**	991-1048 lm/m		-		1610-1709	
		2000-6500K	301-319 lm/ft		-		490-520	
Cutting step: 125 mm		**EFFICACY**	**65 lm/w**				**67 lm/w**	
		MAX RUN	**4.5m 15'**				**3m 10'**	

RGB

		POWER							
SPECTRUM	**COLOR**	**7,2 W/m**	2.2 W/ft	**11,52 W/m**	3.5 W/ft	**14,4 W/m**	4.4 W/ft	**23 W/m**	7 W/ft
RGB	**Total**	157	48	238	72	298	91	447	136
Cutting step: 125 mm	**EFFICACY**	**23 lm/w**		**22 lm/w**		**22 lm/w**		**22 lm/w**	
	MAX RUN	**9m 30'**		**6.5m 21'**		**8m 26'**		**5.5m 18'**	

RGBW

		POWER							
SPECTRUM	**KELVINS**	**4,8 W/m**	1.5 W/ft	**9,6 W/m**	2.9 W/ft	**14,4 W/m**	4.4 W/ft	**19,2 W/m**	5.9 W/ft	**24 W/m**	7.3 W/ft
Any combination within	**CRI 80+**	-		269-318lm/m		394-465lm/m		610-745lm/m		837-1048lm/m	
this range 822 - 850	2200-5000K	-		82-97lm/ft		120-142lm/ft		186-227lm/ft		255-319lm/ft	
Any combination within	**CRI 90+**	-		254-302lm/m		369-439lm/m		542-692lm/m		720-959lm/m	
this range 922 - T950	2200-5000K	-		77-92lm/ft		112-134lm/ft		165-211lm/ft		219-292lm/ft	
Cutting step: 125 mm	**EFFICACY**			**31 lm/w**		**31 lm/w**		**36 lm/w**		**40 lm/w**	
	MAX RUN			**8m 26'**		**7m 23'**		**5.5m 18'**		**5m 16'**	


TECHNICAL DRAWING



SEGMENT TYPES


STANDALONE

Luminaire
Endcaps at both ends



CONTINUOUS LINE


Full module
Endcaps at both end



ACCESSORIES


SOCKET CONNECTORS

CODE	DESCRIPTION
CON-HI-IP-2F LXXX	2-pin socket
CON-HI-IP-3F LXXX	3-pin socket
CON-HI-IP-4F LXXX	4-pin socket
CON-IH-IP-5F LXXX	5-pin socket



SOCKET/PLUG CONNECTORS

CODE	DESCRIPTION
CON-HI-IP-2M/2F LXXX	2-pin extention
CON-HI-IP-3M/3F LXXX	3-pin extention
CON-HI-IP-4M/4F LXXX	4-pin extention
CON-HI-IP-5M/5F LXXX	5-pin extention



PLUG CONNECTORS

CODE	DESCRIPTION
CON-HI-IP-2M LXXX	2-pin plug
CON-HI-IP-3M LXXX	3-pin plug
CON-HI-IP-4M LXXX	4-pin plug
CON-HI-IP-5M LXXX	5-pin plug



MOUNTING BRACKETS

CODE	DESCRIPTION
PRG.AULSI.F01.GZK	Mounting bracket (Ula S / M)
PRG.AULSI.F02.GZK	Mounting bracket with magnet (Ula S / M)
PRG.AULSI.F03.GZK	Mounting bracket adjustable (Ula S / M)
PRG.A111x.ASM.00009	Mounting bracket (Ula L)




WIRE LENGTHS AVAILABLE

CODE	L150	L500	L1000	L2000
Length	150 mm	500 mm	1000 mm	2000 mm
	5.9 in	1 ft 8 in	3 ft 3 in	6 ft 6 in

Disclaimer: Technical data is subject to change without prior notice.
Tolerances of +-5% in luminous flux and light color should be accepted.

OUTDOOR LINES





A018N IEC AGY EOP L1011(3'4") / FL175/Nx G4 14W 830 L1000 HR J1x L0200 STD PH

ORDER CODE EXAMPLE

OUTDOOR
MODULAR
LIGHTING

OUTLINE IP67



TECHNICAL DATA

Cover	Clear / Opal (available on request)	
Housing colors	Black, White, Grey, Custom	
Light engine	Any LED strip up to 24 W/m	
Beam angle	108°	
Connection	Imput: plug; Output: socket	
Light output ratio (LOR)	62%	
Dimmable	YES	
Operating temperature	-25°C...+50°C	-13°F...122°F
Storage temperature	-40°C — 80°C	-40°F — 176°F
Voltage	24 VDC (22.5 - 25 VDC)	

LIGHT ENGINE

WHITE

SPECTRUM	KELVINS	POWER 4,8 W/m 1.5 W/ft	9,6 W/m 2.9 W/ft	14,4 W/m 4.4 W/ft
820/822/825/827/830/	CRI 80+	313-471 lm/m	643-924	930-1362
835/840/850/857/865	2000-6500K	95-143lm/ft	196-281	283-415
920/922/925/T927/T930/	CRI 90+TRI	262-459 lm/m	511-902	746-1332
T935/T940/T950/T957/T965	2000-6500K	80-140 lm/ft	156-275	227-406
Cutting step: 125 mm	EFFICACY	97 lm/w	96 lm/w	94 lm/w
	MAX RUN	13 m 43'	7.5 m 25'	6 m 20'

TUNABLE

SPECTRUM		KELVINS	POWER 4,8 W/m 1.5 W/ft	9,6 W/m 2.9 W/ft	14,4 W/m 4.4 W/ft
820/865	825/857	CRI 80+	-	775-912 lm/m	-
827/857	827/850	2000-6500K	-	236-278 lm/ft	-
920/T965	925/T957	CRI 90+TRI	-	706-767 lm/m	-
T927/T950		2000-6500K	-	215-234 lm/ft	-
Cutting step: 125 mm		EFFICACY		89 lm/w	
		MAX RUN		7,5 m 25'	

RGB

SPECTRUM	COLOR	POWER 7,2 W/m	2,2 W/ft	11,52 W/m	3,5 W/ft	14,4 W/m	4.4 W/ft
RGB	TOTAL	196	60	298	91	372	113
Cutting step: 125 mm	EFFICACY	27		26		26	
	MAX RUN	9m	30'	6,5 m	21'	8 m	26'

RGBW

SPECTRUM	KELVINS	POWER 4,8 W/m	1.5 W/ft	9,6 W/m	2.9 W/ft	14,4 W/m	4.4 W/ft
822 / 825 / 827 / 830	CRI 80+	-		339-401 lm/m		493-585	
835 / 840 / 850 / 865	2200-6500K	-		103-122 lm/m		151-178	
922 / T927 / T930 / T935	CRI 90+TRI	-		320-379 lm/m		464-553	
T940 / T950 / T965	2200-6500K	-		97-115 lm/m		141-168	
Cutting step: 125 mm	EFFICACY			40 lm/w		38 lm/w	
	MAX RUN			8m	26'	7 m	23'

TECHNICAL DRAWING



CONNECTION TYPES

Side exit wire



Back exit wire



End exit wire



SEGMENT TYPES

STANDALONE

Luminaire
Endcaps at both ends




CONTINUOUS LINE

Start module
Endcap at the start



Middle module
No endcaps



End module
Endcap at the end



Full module
Endcaps at both ends



sLine IP67

TECHNICAL DATA


Cover	Opal	
Housing colors	Black, White, Grey, Custom	
Light engine	FL-175/N4	
Beam angle	112°	
Connection	Imput: plug; Output: socket	
Light output ratio (LOR)	35%	
Dimmable	YES	
Operating temperature	-25°C...+50°C	-13°F...122°F
Storage temperature	-40°C — 80°C	-40°F — 176°F
Voltage	24 VDC (22.5 - 25 VDC)	

LIGHT ENGINE

WHITE

SPECTRUM	KELVINS	POWER 4,8 W/m 1.5 W/ft	9,6 W/m 2.9 W/ft	14,4 W/m 4.4 W/ft	19,2 W/m 5.8 W/ft
822/825/827/830/	CRI 80+	170-267	346-532	525-793	706-1051
835/840/850/865	2000-6500K	52-81	105-162	160-241	215-320
922/927/930/	CRI 90+	149-260	296-518	441-772	584-1025
935/940/950/965	2000-6500K	45-79	90-158	134-235	178-312
027/030/035/040/050	CRI 95+	172-194	343-387	511-579	677-767
	2000-6500K	52-59	104-118	155-176	206-234
Cutting step: 40 mm	EFFICACY	42 lm/w	42 lm/w	42 lm/w	42 lm/w
	MAX RUN	5m 16'	2,5 m 8'	1,5 m 5'	1 m 3'

TECHNICAL DRAWING



CONNECTION TYPES

Side exit wire



Back exit wire



End exit wire



SEGMENT TYPES

STANDALONE

Luminaire
Endcaps at both ends



CONTINUOUS LINE

Start module
Endcap at the start



Middle module
No endcaps



End module
Endcap at the end




Full module
Endcaps at both ends



Disclaimer: Technical data is subject to change without prior notice.
Tolerances of +-5% in luminous flux and light color should be accepted.

OUTDOOR
MODULAR
LIGHTING

mLine IP67



TECHNICAL DATA

Cover	Opal	
Housing colors	Black, White, Grey, Custom	
Light engine	Any LED strip up to 24W/m	
Beam angle	105°	
Connection	Imput: plug; Output: socket	
Light output ratio (LOR)	25%	
Dimmable	YES	
Operating temperature	-25°C...+50°C	-13°F...122°F
Storage temperature	-40°C — 80°C	-40°F — 176°F
Voltage	24 VDC (22.5 - 25 VDC)	

LIGHT ENGINE

WHITE


SPECTRUM	KELVINS	POWER 4,8 W/m 1.5 W/ft	9,6 W/m 2.9 W/ft	14,4 W/m 4.4 W/ft	19,2 W/m 5.9 W/ft
820/822/825/827/830/	CRI 80+	124-193 lm/m	254-382	384-568	512-751
835/840/850/857/865	2000-6500K	38-59 lm/ft	77-116	117-173	156-229
920/922/925/T927/T930/	CRI 90+TRI	108-188 lm/m	213-372	315-554	415-733
T935/T940/T950/T957/T965	2000-6500K	33-57 lm/ft	65-113	96-169	126-223
027/030/035/040/050	CRI 95+	124-140 lm/m	246-279	366-415	481-547
	2700-5000K	38-43 lm/ft	75-85	111-126	146-167
Cutting step: 62.5 mm	EFFICACY	41 lm/w	40 lm/w	40 lm/w	40 lm/w
	MAX RUN	13 m 43'	9 m 30'	7 m 23'	5.5 m 18'

TUNABLE

SPECTRUM		KELVINS	POWER 4,8 W/m 1.5 W/ft	9,6 W/m 2.9 W/ft	14,4 W/m 4.4 W/ft	19,2 W/m 5.9 W/ft
820/865	825/857	CRI 80+	-	310-372 lm/m	-	
827/857	827/850	2000-6500K	-	94-113 lm/ft	-	
920/T965	925/T957	CRI 90+TRI	-	267-326 lm/m	-	
T927/T950		2000-6500K	-	81-99 lm/ft	-	
Cutting step: 100 mm		EFFICACY		34 lm/w		
		MAX RUN		9 m 30'		



TECHNICAL DRAWING



CONNECTION TYPES

Side exit wire



Back exit wire



End exit wire



SEGMENT TYPES

STANDALONE

Luminaire
Endcaps at both ends



CONTINUOUS LINE


Start module
Endcap at the start




Middle module
No endcaps



End module
Endcap at the end



Full module
Endcaps at both ends



xLine IP67

TECHNICAL DATA

Cover	Opal	
Housing colors	Black, White, Grey, Custom	
Light engine	Any LED strip up to 24 W/m	
Beam angle	113°	
Connection	Imput: plug; Output: socket	
Light output ratio (LOR)	20%	
Dimmable	YES	
Operating temperature	-25°C...+50°C	-13°F...122°F
Storage temperature	-40°C — 80°C	-40°F — 176°F
Voltage	24 VDC (22.5 - 25 VDC)	

LIGHT ENGINE

WHITE

SPECTRUM	KELVINS	POWER 4,8 W/m 1.5 W/ft	9,6 W/m 2.9 W/ft	14,4 W/m 4.4 W/ft	18,2 W/m 5.5 W/ft	24 W/m 7.3 W/ft
820/822/825/827/830/	CRI 80+	101-152 lm/m	203-298	300-439	373-549	
835/840/850/857/865	2000-6500K	31-46 lm/ft	62-91	91-134	114-167	
920/922/925/T927/T930/	CRI 90+TRI	85-148 lm/m	165-291	241-430	299-537	
T935/T940/T950/T957/T965	2000-6500K	26-45 lm/ft	50-87	73-131	91-164	
027/030/035/040/050	CRI 95+	98-111 lm/m	191-217	280-318	347-396	
	2700-5000K	30-34 lm/ft	58-66	85-97	106-121	
Cutting step: 125 mm	EFFICACY	32 lm/w	31 lm/w	31 lm/w	31 lm/w	
	MAX RUN	13 m 43'	7.5 m 25'	6 m 20'	5 m 16'	

TUNABLE


SPECTRUM		KELVINS	POWER 4,8 W/m 1.5 W/ft	9,6 W/m 2.9 W/ft	14,4 W/m 4.4 W/ft	19,2 W/m 5.9 W/ft	24 W/m 7.3 W/ft
820/865	825/857	CRI 80+	-	248-296 lm/m	-	500-588 lm/m	-
827/857	827/850	2000-6500K	-	76-90 lm/ft	-	152-179 lm/m	-
920/T965	925/T957	CRI 90+TRI	-	211-257 lm/m	-	414-506 lm/m	-
T927/T950		2000-6500K	-	64-78 lm/ft	-	126-154 lm/m	-
Cutting step: 125 mm		EFFICACY		31 lm/w		31 lm/w	
		MAX RUN		8 m 26'		4,5 m 15'	

RGB


SPECTRUM	COLOR	POWER 4,8 W/m 1.5 W/ft	7,2 W/m 2.2 W/ft	11,52 W/m 3.5 W/ft	14,4 W/m 4.4 W/ft
RGB	TOTAL	-	63 lm/m 19 lm/ft	96 29	120 36
Cutting step: 125 mm	EFFICACY		9 lm/w	13 lm/w	17 lm/w
	MAX RUN		9 m 30'	6,5 m 21'	8 m 26'

RGBW

SPECTRUM	KELVINS	POWER 9,6 W/m 2.9 W/ft	14,4 W/m 4.4 W/ft	19,2 W/m 5.9 W/ft	24 W/m 7.3 W/ft
822 / 825 / 827 / 830	CRI 80+	109-129 lm/m	160-189	248-303	
835 / 840 / 850 / 865	2200-5000K	33-39 lm/ft	49-58	76-92	
922 / T927 / T930 / T935	CRI 90+TRI	103-127 lm/m	150-186	220-298	
T940 / T950 / T965	2200-5000K	31-39 lm/ft	46-57	67-91	
Cutting step: 125 mm	Efficacy	13 lm/w	13 lm/w	13 lm/w	
	Max run	8 m 26'	7 m 23'	5,5 m 18'	



TECHNICAL DRAWING



CONNECTION TYPES

Side exit wire



Back exit wire



End exit wire



SEGMENT TYPES

STANDALONE

Luminaire
Endcaps at both ends



CONTINUOUS LINE


Start module
Endcap at the start




Middle module
No endcaps



End module
Endcap at the end



Full module
Endcaps at both ends




Disclaimer: Technical data is subject to change without prior notice.
Tolerances of +-5% in luminous flux and light color should be accepted.

ACCESSORIES


SOCKET CONNECTORS

CODE	DESCRIPTION
CON-PH-TP-2F LXXX	2-pin socket
CON-PH-TP-3F LXXX	3-pin socket
CON-PH-TP-4F LXXX	4-pin socket
CON-PH-TP-5F LXXX	5-pin socket




SOCKET/PLUG CONNECTORS

CODE	DESCRIPTION
CON-PH-TP-2M/2F LXXX	2-pin extention
CON-PH-TP-3M/3F LXXX	3-pin extention
CON-PH-TP-4M/4F LXXX	4-pin extention
CON-PH-TP-5M/5F LXXX	5-pin extention




PLUG CONNECTORS

CODE	DESCRIPTION
CON-PH-TP-2M LXXX	2-pin plug
CON-PH-TP-3M LXXX	3-pin plug
CON-PH-TP-4M LXXX	4-pin plug
CON-PH-TP-5M LXXX	5-pin plug



MOUNTING BRACKETS

CODE	DESCRIPTION
PRG.A002x.F01.GZK	Mounting bracket (Outline / mLine)
PRG.A002x.F04.RGY	Plastic rotatable holder (Outline / mLine)mLine)
PRG.A016x.F02.RGY	Stainless steel holder (xLine)




WIRE LENGTHS AVAILABLE

CODE	L150	L500	L1000	L2000
Length	150 mm	500 mm	1000 mm	2000 mm
	5.9 in	1 ft 8 in	3 ft 3 in	6 ft 6 in




NEMAN IP66



A1112.NM.S.IP66 IBC PWE ECL L1008(3'4") / FL112/Nx G5 33W T940 L1000 HR J1x L0200 STD PH

ORDER CODE EXAMPLE

Neman IP66
Honeycomb / Prism / Opal





HONEYCOMB



MICROPRISM



OPAL











SURFACE



RECESSED



TECHNICAL DETAILS


Housing	Powder coated extruded aluminum
LEDs	Nichia 3-step MacAdam
LED lumen maintenance	L90B10 > 60.000 h
Electrical	24 VDC, driver can be hidden inside luminaire

SELECTABLE FEATURES

Honeycomb light diffuser color	Black, Silver, Gold
Housing color	Black, White, Grey, Custom
CRI	Ra80+, Ra90+, Ra95+
CCT	2000K, 2200K, 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K, 2700-6500K (tunable white), RGB, RGBW
Efficacy	108-113 Lm/W, (17-32 Lm/W RGBW)
Length, mm, ft	L250, L500, L750, L1000, L1250, L1500, L1750, L2000, L2250, L2500, L2750, L3000 0.9ft, 1.7ft, 2.5ft, 3.3ft, 4.1ft, 4.9ft, 5.9ft, 6.7ft, 7.5ft, 8.2ft, 9ft, 9,8
Control	Fixed output, DALI, PushDim, 0-10V

SEGMENT TYPE

SURFACE INDIVIDUAL LUMINAIRE



Luminaire - IND
Endcaps at both ends

RECESSED INDIVIDUAL LUMINAIRE



Luminaire - IND
Endcaps at both ends

Disclaimer: Technical data is subject to change without prior notice.
Tolerances of +-5% in luminous flux and light color should be accepted.

Visit **www.holectron.com** and use interactyve product search engine to find the right products for your project.

Phone: +370 612 42446
Salininku st. 84, LT-02223
Vilnius, Lithuania
info@holectron.com
www.holectron.com